



**Wiha Insulated TorqueControl Tools**



**1000V**

Includes Certificate

**285 Insulated TorqueVario-S, With Window Scale Insulation**

up to 1000 Volt. EN/IEC 60900

EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy  
Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible and perceptible click when torque setting has been attained. Includes Certificate

Item No.	Range	Inch lbs.	Increments	mm	lbs.	pkg.
285 14	7.5 - 20	.5 Inch lbs	126 - 131	.43	1	
285 16	10 - 50	2 Inch lbs	133 - 138	.40	1	
285 20	20 - 70	2 Inch lbs	137 - 142	.69	1	

Each TorqueVario handle has unique serial number and certificate of calibration



**287 Insulated Slotted Interchangeable Blades For TorqueVario-S**

Slotted tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum tool steel, hardened.

Item No.	mm	Inch	mm	lbs.	Nm	pkg.
287 01	3.0	.118	190	.07	0.6	1
287 03	3.5	.139	190	.07	1.1	1
287 05	4.0	.157	190	.07	2.5	1
287 07	5.5	.216	190	.07	3.8	1

These Insulated Blades work in Insulated handles only



**287 Insulated Phillips Interchangeable Blades For TorqueVario-S**

Phillips tip blades on narrow 5/32 Hex shafts. High alloy chrome-vanadium-molybdenum tool steel, hardened.

Item No.	Size	mm	mm	lbs.	Nm	pkg.
287 10	0	190	4.0	.07	0.9	1
287 11	1	190	4.0	.07	3.8	1
287 12	2	190	4.0	.07	5.5	1

These Insulated Blades work in Insulated handles only

**Wiha Multi-Bit Screwdrivers**

**Six Tools in One!**



**1000volt**

**380 Sets Multi-Bit Screwdriver Sets** with Wiha Powerhandle,

cellulose-acetate, impact resistant. Snap-lock rotatable cap. Chambered bit holder equipped with transparent selector and 6 bits. 1/4" Bit holder, stainless steel. Shaft chrome-vanadium-molybdenum steel, hardened, chrome-plated. Packaged in clear blister package. Blade Length = 120mm (4.7") Overall Length = 230mm (9")

**380 06 Slotted/Phillips Multi-Bit Screwdriver** with Wiha Powerhandle and insulated shaft.

Set includes the following 1/4" bits:

Slotted Sizes: 5.5, 6.5mm lbs.

Phillips Sizes: 0, 1, 2, 3 .39

**380 07 Slotted/Phillips/Square Multi-Bit Screwdriver** with Wiha

Powerhandle and insulated shaft.

Set includes the following 1/4" bits:

Slotted Sizes: 6.5, 8.0mm lbs.


Phillips Sizes: 1, 2 .39

Square Sizes: 1, 2

Insulation meets EN 60900

**Insulated Terminal Block Xeno Screwdrivers**

**Combination Slotted/Phillips Terminal Block Drivers**



**1000Volt**

Slotted & Phillips



**307 Combination Terminal Block Xeno Screwdriver, With Wiha**

**SoftFinish® Handle** Insulation According to ASTM F-1505-01, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E.

Individually Tested. Blade CVM steel, hardened, black finish. Insulation molded directly onto blade. Wiha-SoftFinish® handle, multi-component, cushion grip. For combination Slotted/Phillips head terminal screws.

Item No.	Size	mm	mm	Inch	lbs.	pkg.
307 00	1	80	191	7.5	1.23	10
307 01	2	100	218	8.6	1.23	10