

## CASTER SKIRT

The Caster skirt is an attractive solution to conceal our heavy duty casters.

### APPLICATION

Fits on our 9225W, 9220W & 9215 series racks with four 3 1/2" heavy duty nonlocking casters. (9200 - 35)

### FEATURES

- 16 ga. CRS with black powder coat finish.
- 4 heavy duty 3 1/2" non locking casters (9200 - 35).
- All fastening hardware included.

CODE	HEIGHT	WIDTH	DEPTH	WEIGHT (LBS)	MATERIAL	FINISH
9200	4.25"	22.25"	25.00"	24	16 ga. CRS	black powder coat
9201	4.25"	22.25"	20.00"	21	16 ga. CRS	black powder coat
9202	4.25"	19.00"	19.00"	20	16 ga. CRS	black powder coat



## LOCKING DOOR

Locking door secures welded and gangable racks from unwanted tampering.

### APPLICATION

Attaches to any AVM welded or gangable rack front or back, left or right open.

### FEATURES

- 16 ga. steel black powder coat.
- Locking latch.
- Available in 7 sizes.
- Available in solid (9210), plexiglass (9211) and perforated vented (9212).

CODE	RACK SPACE	HEIGHT	WIDTH	WEIGHT (LBS)	MATERIAL	FINISH
9210 - 14	14	25.25"	19.125"	9.5	16 ga. CRS	black powder coat
9210 - 18	18	32.25"	19.125"	12	16 ga. CRS	black powder coat
9210 - 21	21	37.50"	19.125"	14	16 ga. CRS	black powder coat
9210 - 27	27	48.00"	19.125"	18	16 ga. CRS	black powder coat
9210 - 37	37	65.50"	19.125"	24	16 ga. CRS	black powder coat
9210 - 40	40	70.75"	19.125"	26.5	16 ga. CRS	black powder coat
9210 - 44	44	77.75"	19.125"	29	16 ga. CRS	black powder coat
9211 - 14	14	25.25"	19.125"	9.5	16 ga. CRS	plexi glass
9211 - 18	18	32.25"	19.125"	12	16 ga. CRS	plexi glass
9211 - 21	21	37.50"	19.125"	14	16 ga. CRS	plexi glass
9211 - 27	27	48.00"	19.125"	18	16 ga. CRS	plexi glass
9211 - 37	37	65.50"	19.125"	24	16 ga. CRS	plexi glass
9211 - 40	40	70.75"	19.125"	26.5	16 ga. CRS	plexi glass
9211 - 44	44	77.75"	19.125"	29	16 ga. CRS	plexi glass
9212 - 14	14	25.25"	19.125"	9.5	16 ga. CRS	perforated
9212 - 18	18	32.25"	19.125"	12	16 ga. CRS	perforated
9212 - 21	21	37.50"	19.125"	14	16 ga. CRS	perforated
9212 - 27	27	48.00"	19.125"	18	16 ga. CRS	perforated
9212 - 37	37	65.50"	19.125"	24	16 ga. CRS	perforated
9212 - 40	40	70.75"	19.125"	26.5	16 ga. CRS	perforated
9212 - 44	44	77.75"	19.125"	29	16 ga. CRS	perforated

