

## Weatherproof Fully Adjustable IR Camera

- 420 lines of resolution
- 6mm Lens
- 1/3" interline transfer CCD
- 0.5 lux color (led off),
- 0 lux (led on)
- IP 66 weatherproof operation
- IR trigger 4 lux/8 lux IR on/off
- 40' IR Range (depending on scene reflection)
- Video S/N ratio greater than 48dB (AGC off)
- 12V DC  $\pm$  power supply required (model PSW5)
- Power requirements: 12V DC @ 230mA



Wall/Ceiling  
Mounting  
Bracket  
Included

**Value Line Cameras  
When Price Counts!**



VL12

## Ultra High Resolution Color Dome Camera

- 550 line Color resolution
- .5 lux • 1/3" format
- 3.6mm lens
- Can be rotated 360°
- Tilt angle +/- 90°
- Built-in electronic shutter
- Video output/BNC
- Regulated 12V DC power supply (UL & CSA listed) included
- Power requirements: 12V DC @ 110mA
- 4" Diameter x 2.5"H



**Includes video  
test connector**



**CVC646HR** black housing  
**CVC646HRW** white housing

## Dome Camera with 4-9mm Varifocal Lens

**B/W Version** 420 line resolution • 0.02 lux • 1/3" format  
**Color Version** 420 line resolution • .92 lux • 1/4" format

- Can be rotated 360° • Built-in electronic shutter • Video output - BNC
- Color domes have built-in test connectors • Ceiling Mount
- Power requirements: Regulated 12V DC @ 110mA power supply (UL & CSA listed) included
- 4.4" Diameter x 3"H



**CVC6405DC**  
includes video  
test connector

**CVC1805DC** B/W version  
**CVC6405DC** color version



B/W lens options include 2.5mm, 6mm, 8mm, & 12mm. Color lens options include UWA (2.2mm), 3.6mm, 6mm, 8mm, 12mm, & 16mm. Please inquire on specific model availability & pricing.