

Indoor Tamper/Vandal Resistant Color Dome Camera For Wall or Ceiling Mounting

Includes a unique internal 3-way gimble, making the unit perfect for both wall and ceiling mounting.

The VL64TP provides a crisp picture under a wide variety of lighting conditions.

Please provide your own regulated 12V DC power supply or use Speco PSW5.

- 420 lines resolution
- 1 lux
- 1/4" image sensor interline transfer
- 2.9mm lens
- S/N ratio- better than 48dB
- Shutter Control 1/60 to 1/100,000 Sec
- Electronic Shutter 256 steps
- Power requirements: 12V DC regulated @ 110mA power supply not included
- Power consumption: 200mA
- Housing metal & polycarbonate with lined dome
- Gamma Correction 0.45
- Operating Temperature 4°F-131°F / 30 to 90% RH
- Video Out: Composite 1.0 VP.P / 75 OHM
- Weight 1lb.
- Dimensions 3.6" Dia. x 3" H

Can withstand hits from a 10lb. sledgehammer!



VL64TP
white housing VL64TPW

Economy Color and B/W Dome Camera with White or Black Housing

3 Way Gimble Wall or Ceiling Mountable

- B/W Version** 420 line resolution • 0.2 lux • 3.6mm lens
- 1/3" B/W CCD
- Color Version** 420 line resolution • 0.2 lux • 1/3" format
- 3.6mm lens
- Can be rotated 360° • Tilt angle +/- 90°
- Video output - BNC, NTSC
- Power requirements: 12V DC regulated @ 110mA power supply not included (See PSW5 in power supply section)
- 4" Diameter x 2.5"H



B/W version with black housing
VL183

B/W version with white housing
VL183W

3.6mm 1/3" color format with black housing
VL644DC

3.6mm 1/3" color format with white housing
VL644DCW



B/W lens options include 2.5mm, 6mm, 8mm, & 12mm. Color lens options include UWA (2.2mm), 3.6mm, 6mm, 8mm, 12mm, & 16mm. Please inquire on specific model availability & pricing.