

H.264 HYBRID Pentaplex DVR with Network/DDNS Video Server

PC/Mac® compatible
Download Mac® compatible software at:
www.specotech.com



DVR4TH250*
4 Channel DVR with audio

DVR8TH250*
8 Channel DVR with audio

DVR16TH250*
16 Channel DVR with audio

DVR16THU with 480 FPS
recording at D1 Resolution.

**Learn one unit
- know them all!**



TH Series Features

EZ Record: set the number of days you want to record and the DVR takes care of the rest
EZ Copy: auto copy what you are playing onto a DVD/RW or USB flash drive
EZ Set-Up: for quick installation

- Free Speco DDNS service for use with dynamic IP addresses
- MAC® & PC compatible software included
- Hybrid Operation: Up to 4 channels with popular protocols supported including Speco Internet Protocol (SIP), ACTi, Axis, Sony, Vivotek, Hunt, Sanyo & others
- Selectable H.264, MPEG4, or MJPEG compression
- POS/ATM support with text overlay and searchable database
- Pentaplex operation enabling simultaneous live view or playback while continuing to record, network transfer
- Remote monitoring, recording, playback, change system settings and dome camera control via network and/or internet
- Jog shuttle for easy operation
- Real Time live display
- IR Remote control included - individually control up to 16 DVRs
- Recording rate up to 480 fps
- 4/8/16 channels of audio input
- 3/7/15 channels of 2-way audio local only
- Supports 3 Sata HDDs
- Digital output via HDMI cable
- DVD/RW Standard for video clip exporting
- USB 2.0 port for video clip exporting, supports USB Flash drive
- Easy software upgrade via Network, USB Flash drive, or CD/DVD
- Auto reboot feature: on/off
- Up to 30 second pre-alarm recording
- Configurable per channel normal and event recording frame rate & picture quality or globally via EZ record
- Free Central Management System (CMS) software allows viewing of 256 simultaneous channels on a PC
- Email notification of alarm events
- Per channel built-in PTZ camera protocol (through RS485): including Pelco D, Pelco P, AD422, Fastrax, JVC
- Automatic camera detection (Plug & Play)
- Digital Zoom 2 x 2 in live mode and playback
- Covert camera operation provides enhanced security and administrator control
- Programmable call-monitor switching sequence
- USB mouse and keyboard supported
- Rack ears included
- Multiple language on-screen menus
- Password to secure with 8 configurable user authentication levels
- DVR supports static IP, DHCP, PPPoE & DDNS
- NICE10/100/1000 mbs
- Dimensions: 4 7/8" H X 17 1/4" W X 16 3/4" D
- Weight: 18.45 lbs. with 1 HDD (HDD weighs 1 lb.)
- Power Consumption: Start up @ 90W, Running @ 60W
- HDD size: 250GB, 1TB, 2TB and 3TB configurations**
- Operating temperature: 14° F to 120° F
- UL Listed

**Includes Digital Deterrent™
On all channels**

Audio For Security or Retail Applications

Standard DVR comes with a 250GB HDD - other configurations available up to 6TB internal*

**8TB maximum if DVD-RW is removed