

Toll Free: (800) 494-6104

Wiha Insulated Pliers & Cutters

Insulated Diagonal Cutters



Insulated High Leverage Diagonal Cutters



Insulated Electrician's Diagonal Cutters



Insulated Cable Cutters



Diagonal Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E, aup to 1000 volt.

Individually Tested. DIN ISO 5749 Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 60 HRC. Special tool steel hardened and tempered.

For soft & medium hard wire. 32832 & 32834 for soft, hard & piano wire.

Item	→	→	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
328 30 Z12014006	140	5.5	#6	1	.47
328 32 Z12016006	160	6.3	#6	1	.49
328 34 Z12018006	180	7.0	#6	1	.62

Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Lightweight action, clean cutting. Long term cutting is achieved through additional inductive hardening to approx. 64 HRC. C 60 special tool steel hardened and tempered to high quality. For soft, hard and piano wire, lay-on joint, optimized power transmission.

Item	\leftarrow	\rightarrow	Cutting Capacity		•••
No.	mm	Inch	Copper AWG	Pkg.	wt.
328 35 Z16016006	160	6.3	#6	1	.54
328 36 Z16018006	180	7.0	#5	1	.57
328 38 Z16020006	200	8.0	#4	1	.64

Diagonal Cutters W/Stripping Holes. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E,

up to 1000 volt. Individually Tested.

Drop-forged from special tool steel, cutters additionally induction hardened (approx. 60 HRC), chrome-nickel plated, mirror-polished. Ergonomic comfort grip with slip guard. Holes in the cutting edge for stripping copper wire of Ø 1.5 and 2.5. Strips AWG sizes #10 & #14.

Item	\leftrightarrow	\leftarrow	Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	wt.
328 61 Z14016006	160	6.3	#6	1	.54

Cable Cutters. Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505-01, NFPA70E, Qup to 1000 volt. Individually Tested. Drop-forged from durable CV steel, cutters additionally induction hardened, chrome & nickel plated, Mirror-polished. For copper and aluminum cables (not for steel wires), integrated release spring, one-hand locking, adjustable joint, anti-squeeze feature.

Item	\leftarrow	\leftarrow	Min	Max		•	
No.	mm	Inch	mm	mm	Pkg.	wt.	
328 46 Z50023006	210	8.3	17	40	1	.98	
328 48 Z50017006	170	6.75	10	60	1	.67	





