

Includes video test connector



HTB10X

Includes video test connector



HT7816DNP

INTENSIFIER<sup>2</sup>



HTINTB4

Includes video test connector

## 10X Optical Motorized Zoom!

- 580 lines resolution (IR on)
- 560 lines resolution (IR off)
- 3.8-38mm auto iris motorized zoom lens
- 1/4" Sony Super-HAD™ CCD
- On board controls
- **Split Glass Technology**
- **Minimum illumination:**  
30 IR LEDs - 0.1 Lux LED OFF  
0 Lux (up to 130 ft. range) LED ON
- **Electronic Shutter:**  
Auto: 1/60~1/100,000 sec.  
Manual : 1/60, FLK(1/120),  
1/250, 1/500, 1/1,000, 1/2,000,  
1/4,000, 1/10,000
- **On-Screen Display (OSD)**
- **Optical Zoom 10X - RS-485 control**
- **Digital Zoom 10X**
- Dual voltage: 12V DC/24V AC @ 230mA
- S/N Ratio more than 46dB (weight on)
- **Weatherproof operation**
- Operating Temperature: -20°F to 140°F
- **Dimensions:** 3.1" W x 3" H x 6.8" L
- **Weight:** 3.3 lbs.
- **Warranty:** 5 years

## True Day/Night

- 600 lines resolution (IR on)
- 550 lines resolution (IR off)
- 2.8-12mm auto iris varifocal lens
- 1/3" Sony Super-HAD™ CCD
- **Split Glass Technology**
- **Minimum illumination:**  
30 IR LEDs - 0.5 Lux LED OFF  
0 Lux (up to 130 ft. range) LED ON
- **Electronic Shutter:**  
1/60~1/100,000 sec. (NTSC)  
[at ELC Mode]
- Dual voltage: 12V DC/24V AC @ 230mA
- S/N Ratio more than 50dB
- Weatherproof operation
- Operating Temperature: -20°F to 122°F
- **Dimensions:** 3.1" W x 3" H x 6.8" L
- **Weight:** 3.3 lbs.
- **Warranty:** 5 years

## Intensifier™!

- 580 lines resolution (IR on)
- 520 lines resolution (IR off)
- 3.8-9.5mm auto iris varifocal lens
- 1/3" Sony Super-HAD™ CCD
- **Split Glass Technology**
- **Minimum illumination:**  
30 IR LEDs - 0.5 Lux LED OFF  
0.02 Lux / F1.2 with IR OFF  
(40IRE, AGC Middle, DNR Low),  
0 Lux / F1.2 with IR ON  
(40IRE, AGC Middle, DNR Low)  
**0.002 in Intensifier™ mode**
- **Electronic Shutter:**  
1/60~1/100,000 sec. (NTSC)  
[at ELC Mode]
- **On-Screen Display (OSD)**
- SLC (Speco Light Compensation) low, middle, high, off selectable
- Dual voltage: 12V DC/24V AC @ 230mA
- S/N Ratio more than 50dB (weight on)
- **Weatherproof operation**
- Operating Temperature: -20°F to 122°F
- **Dimensions:** 3.1" W x 3" H x 6.8" L
- **Weight:** 3.3 lbs.
- **Warranty:** 5 years