


# Fire Alarm Plenum Cables

**WEST PENN WIRE**



## Fire Alarm Cables Nonpower-Limited/ Shielded & Unshielded Plenum

### Description:

- ASTM bare copper • Fluoropolymer insulation • Twisted pair or cabled construction • Unshielded and Shielded Versions (Shielded versions) 100% coverage of aluminum polyester foil with TC drain wire
- Overall fluoropolymer jacket

### Rating:

- NEC Type NPLFP
- (UL) or (ETL)us Listed
- Meets 150V requirements as specified in the NEC
- Flame Rating: NFPA-262 Smoke & Flame Test

Standard pool size 1000ft.

### Applications:

Indoor for:

- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness Inches	Shielding & % Coverage	Jacket Type & Thickness Inches	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
251980†	1 Pair	18 AWG Solid 6.5 Ω/Mft	Fluoro-polymer .020	None	.010	.185	<b>NPLFP</b>	--	Red
251975	1 Pair	18 AWG Solid 6.5 Ω/Mft	Fluoro-polymer .020	Al. Foil 100%	.010	.195	<b>NPLFP</b>	--	Red
251991	1 Pair	16 AWG Solid 4.1 Ω/Mft	Fluoro-polymer .020	Al. Foil 100%	.010	.214	<b>NPLFP</b>	--	Red
251994†	1 Pair	14 AWG Solid 2.6 Ω/Mft	Fluoro-polymer .020	None	.010	.210	<b>NPLFP</b>	--	Red
251995	1 Pair	14 AWG Solid 2.6 Ω/Mft	Fluoro-polymer .020	Al. Foil 100%	.010	.220	<b>NPLFP</b>	--	Red

### Special Notes:

† Unshielded version

- Plenum Installation Precautions see Technical Reference Section Page 192

Color Code	
All Cables	1.Black, 2. Red
	<b>JACKET: Red</b>