

NO HUB COUPLINGS

REGULAR SHIELDED NO HUB COUPLINGS

MI-HUB

Model Number	Size	Carton Qty	Pallet Qty	List Price
MI-HUB-150	1-1/2"	60	2,160	\$14.45
MI-HUB-2	2"	60	2,160	14.45
MI-HUB-3	3"	24	1,440	17.25
MI-HUB-32	3"x2"	24	1,440	26.20
MI-HUB-4	4"	24	864	20.40
MI-HUB-42	4"x2"	24	864	37.15
MI-HUB-43	4"x3"	24	864	31.10
MI-HUB-5	5"	36	432	49.60
MI-HUB-6	6"	36	432	51.70
MI-HUB-8	8"	15	180	97.60
MI-HUB-10	10"	9	108	128.90
MI-HUB-12	12"	5	60	140.45
MI-HUB-15	15"	5	60	196.50



Tested and certified to ASTM Standard #C1277-03 and ASTM Standard #C564. All models are listed with IAPMO (U.P.C.).
5/16" driver required to tighten bolts.



U.P.C. Approved

Note: Tighten bolts to 60 inch lbs. min./max torque.
Tested to maintain 4.3 p.s.i. maximum line pressure with 10' head.

HEAVY DUTY SHIELDED NO HUB COUPLINGS

MI-XHUB

Model Number	Size	Carton Qty	Pallet Qty	List Price
MI-XHUB-150	1-1/2"	72	1,728	\$16.15
MI-XHUB-2	2"	72	1,728	17.25
MI-XHUB-3	3"	24	912	19.90
MI-XHUB-32	3"x2"	24	912	26.50
MI-XHUB-4	4"	24	576	23.20
MI-XHUB-42	4"x2"	24	576	36.70
MI-XHUB-43	4"x3"	24	576	31.40
MI-XHUB-5	5"	27	324	47.65
MI-XHUB-6	6"	27	324	54.35
MI-XHUB-8	8"	15	180	111.70
MI-XHUB-10	10"	9	108	143.60
MI-XHUB-12	12"	5	60	150.00
MI-XHUB-15	15"	5	60	215.00




Tested and certified to ASTM Standard #C1540-06 and ASTM Standard #C564. All models are listed with IAPMO (U.P.C.).
3/8" driver required to tighten bolts.



U.P.C. Approved

Note: Tighten bolts from 80 inch lbs. minimum torque to 100 inch lbs. maximum torque.
Tested to maintain 15 p.s.i. maximum line pressure with 10' head.



CROSS REFERENCE

MIFAB	Anaco	Clamp-All	Fernco	Husky	Ideal	Mission	Tyler
MI-HUB	NH	-	NH	-	M8G	C	NH
MI-XHUB	-	Hi-Torq 125	HD	SD4000	H8G	HW	Wide Body

All sales subject to MIFAB's terms and warranties. Please refer to inside front cover.