

**CL / CLS PISTON TYPE WATER HAMMER ARRESTORS**

- Thick walled one piece, hard drawn “K” copper seamless body. Unique design eliminates separate end cap connection to ensure maximum integrity of the body and guarantees free movement of the piston for maximum performance.
- Ryton PPS piston with two Parco #5778-80 O-rings and Dow Corning #111 FDA approved silicone lubricant. Ribbed piston - design reduces secondary shock and flared piston skirt prevents hard particles suspended in the water supply from contacting the O-rings to provide increased product life.
- Large volume air chamber provides better dampening for superior water hammer arrestor performance.
- Temperature range: Maximum working temperature is 250 F.
- Operating pressure: Up to 350 P.S.I.G.
- Surge pressure: Up to 1,500 P.S.I.G.

Tested and certified to the A.S.S.E. 1010 and A.N.S.I. A112.26.1M Standards and listed with I.A.P.M.O.

**Patent # 6,539,976**

- No access door is required to service MIFAB’s water hammer arrestors.



Model Number	(A) Length	(B) Sweat Conn. Size	Master Carton Quantity	Master Carton Weight (Lbs.)	List Price
CLS-A	8 1/4"	1/2"	44	23.00	\$18.20
CLS-B	10"	3/4"	32	24.50	\$21.75
CLS-C	12 1/2"	1"	22	30.50	\$53.00
CLS-D	11"	1"	8	16.50	\$68.00
CLS-E	13 1/2"	1"	7	17.50	\$91.00
CLS-F	16"	1"	6	17.50	\$139.00

Model Number	ASSE Rating	Fixture Units	(A) Length	(B) Threaded Conn. Size	Master Carton Quantity	Master Carton Weight Lbs.	List Price
CL-AA	AA	1-3	4 3/4"	1/2"	50	16.50	\$13.50
CL-A	A	1-11	6"	1/2"	60	27.00	\$18.45
CL-B	B	12-30	7 1/2"	3/4"	42	23.00	\$22.25
CL-C	C	31-60	9"	1"	24	24.00	\$53.00
CL-D	D	61-113	10 1/2"	1 1/4"	8	19.00	\$69.00
CL-E	E	114-154	11 1/4"	1 1/2"	6	18.00	\$92.00
CL-F	F	155-330	13"	2"	6	35.00	\$139.00

All sales subject to MIFAB’s terms and warranties. Please refer to inside front cover.

**WATER HAMMER ARRESTORS**