

# Communication & Control Cables

## Communication & Control Cable 22 AWG Multiple Pair/ Unshielded featuring the PERFECT PAIR®



### Applications:

#### Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

### Description:

- ASTM Bare Copper • PVC insulation • Short overall twist construction • Overall PVC jacket

### Rating:

- NEC Type CMR
- (UL)-C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Standard spool size 1000ft.

Catalog No.	No. of Pairs	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding	Jacket Type & Thickness	Nom. O.D.	NEC Type	Nom. Capacitance	Jacket Color
			Inches		Inches				
251	2	22 AWG Solid 17.5 Ω/Mft	PVC .010	None	PVC .015	.179	CMR	--	Gray
252	3	22 AWG Solid 17.5 Ω/Mft	PVC .010	None	PVC .015	.193	CMR	--	Gray
253	4	22 AWG Solid 17.5 Ω/Mft	PVC .010	None	PVC .015	.212	CMR	--	Gray

Color Code
Colors
1. Black/ Red-Red
2. Black/ White-White
3. Black/ Green-Green
4. Black/ Blue-Blue
<b>JACKET:</b> Gray

### Special Notes:

- Select cables are available in our Easybox®
- Orange ripcord included on cables containing 3 or more pairs