

Communication & Control Cables

Communication & Control Cable

22 AWG Miniature Audio Cable/ Overall Shield

WEST PENN WIRE



Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Description:

- ASTM Bare Copper • Polypropylene insulation • Overall shield 100% coverage of aluminum polyester foil with TC drain wire • Twisted pair construction • Overall PVC jacket

Rating:

- NEC Type CM
- (UL)-C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1685

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding & % Coverage	Jacket Type & Thickness	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
			Inches	% Coverage	Inches				
450	2	22 AWG Solid 17.5 Ω/Mft	PP + .006	Al. Foil 100% 22 Solid	PVC .020	.118	CM	34 pf/ft* 67 pf/ft**	Black
451	3	22 AWG Solid 17.5 Ω/Mft	PP + .006	Al. Foil 100% 22 Solid	PVC .020	.130	CM	34 pf/ft* 67 pf/ft**	Black
452	2	22 AWG (7x30) 17 Ω/Mft	PP + .008	Al. Foil 100% 24 Strd.	PVC .020	.135	CM	32 pf/ft* 58 pf/ft**	Black

* Capacitance between conductors.

** Capacitance between one conductor and the other connected to the shield

PP + Polypropylene

Color Code

Color Code	
All Cables	1. Black, 2. Red, 3. White
	JACKET: Black

Special Notes:

- Select cables are available in our Easybox®