


# Communication & Control Cables

## Communication & Control Cable Multiple Conductor 22 AWG / Unshielded featuring the **PERFECT STRIPE**®



### Applications:

#### Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Standard spool size 1000ft.

### Description:

- ASTM Bare Copper • PVC insulation • Cabled construction • Overall PVC jacket

### Rating:

- NEC Type CMR
- (UL)-C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding	Jacket Type & Thickness	Nom. O.D.	NEC Type	Nom. Capacitance	Jacket Color
			Inches		Inches	Inches			
855	5	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.168	CMR	--	Gray
270	6	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.183	CMR	--	Gray
271	8	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.198	CMR	--	Gray
272	10	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.243	CMR	--	Gray
273	12	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.251	CMR	--	Gray
274	15	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .020	.278	CMR	--	Gray
275	20	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.308	CMR	--	Gray
276	25	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.343	CMR	--	Gray
277	30	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .020	.364	CMR	--	Gray

### Special Notes:

- Select cables are available in our Easybox®
- Orange ripcord under jacket

Color Code- See page 6