

Communication & Control Cables

WEST PENN WIRE



Communication & Control Cable Two Conductor / Unshielded

Description:

- ASTM Bare Copper • PVC insulation • Short overall twist lengths • Overall PVC jacket

Rating:

- NEC Type CMR or CL2R
- (UL)-C(UL) Listed or (ETL)us - c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness	Shielding	Jacket Type & Thickness	Nom. O.D.	NEC Type	Nom. Capacitance	Jacket Color
			Inches		Inches	Inches			
220	2	22 AWG Solid 17.5 Ω/Mft	PVC .010	None	PVC .015	.118	CMR	--	Gray
221	2	22 AWG (7x30) 17 Ω/Mft	PVC .010	None	PVC .015	.127	CMR	--	GY, BN, WH
222	2	20 AWG (7x28) 10.5 Ω/Mft	PVC .010	None	PVC .015	.141	CMR	--	GY, BN, WH
224	2	18 AWG (7x26) 6.2 Ω/Mft	PVC .010	None	PVC .015	.155	CMR	--	GY, BK, BN, WH, BL, YE
225	2	16 AWG (19x29) 4.2 Ω/Mft	PVC .010	None	PVC .015	.189	CMR	--	GY, BN, WH, BK, YE
226	2	14 AWG (19x27) 2.7 Ω/Mft	PVC .014	None	PVC .015	.234	CL2R*	--	GY, BN, WH, BK, YE
227	2	12 AWG (19x25) 1.7 Ω/Mft	PVC .014	None	PVC .015	.269	CL2R*	--	GY, BK, YE

Burglar Wire

Rating:

- NEC Type CM

S221	2	22 AWG (7x30) 17 Ω/Mft	Poly-propylene .008	None	PVC .015	.102	CM	--	GY, WH
------	---	---------------------------	---------------------	------	----------	------	----	----	--------

Special Notes:

- Selected Plenum Versions see pages 28
- Selected Indoor/Outdoor Aquaseal Water Resistant® Versions see pages 40 & 43
- Select cables are available in our Easybox®
- *- CL2R Meets 150V requirements for Low Voltage Circuits

Color Code			
Catalog Number	220, 221,222, 224,225	226, 227	S221
Primary Color Code	1. Black, 2. Red	1. Black, 2. White	1. Black, 2. Red
Jacket: GY-Gray, BK-Black, BN-Brown, WH-White, RD-Red, YE- Yellow, BL-Blue			