


Fire Alarm Cables

WEST PENN WIRE



Fire Alarm Cables Nonpower-Limited/ Unshielded

Applications:

Indoor for:

- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

Description:

- ASTM bare copper • PVC insulation with Nylon • Twisted pair or cabled construction • Overall PVC jacket

Rating:

- NEC Type NPLF
- (UL) or (ETL)us Listed
- Meets 150V requirements as specified in the NEC
- Flame Rating: UL1685

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation Type & Thickness Inches	Shielding	Jacket Type & Thickness Inches	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
1990	1 Pair	16 AWG Solid 4.1 Ω/Mft	PVC .016 Nylon .005	None	PVC .037	.252	NPLF	--	Red
1994	1 Pair	14 AWG Solid 2.6 Ω/Mft	PVC .016 Nylon .005	None	PVC .037	.278	NPLF	--	Red

Special Notes:

- Selected Plenum Versions see pages 56
- Orange rip cord under jacket

Color Code	
All Cables	1.Black, 2. Red
	JACKET: Red