

Description:

StretchKote is an elastomeric decorative and protective exterior wall coating. StretchKote provides excellent crack bridging qualities over cementitious exterior surfaces. StretchKote is available in a wide variety of colors. StretchKote offers excellent weather resistance, and a siliconized version is available by special order.

Uses:

StretchKote exterior elastomeric paint is for use over prepared masonry, concrete, stucco or synthetic substrates. StretchKote has a high elongation factor for bridging cracks.

Color:

White (a wide variety of colors is available upon request)

Packaging:

5 gallon plastic pail- 50 lbs. (22.6 kg.)

Coverage:

Approximate coverage is 225-350 sq. ft. per pail @ 10 mils. dry thickness (coverage will vary depending on substrate, surface texture and application technique).

Mixing:

Mix with drill mixer for 1 minute, or until consistent, prior to use.

Storage:

Keep from freezing. Keep out of direct sunlight for prolonged periods. Do not store at temperatures above 90°F or below 40°F.

Shelf Life:

1 year

Adhesion:

Excellent bonding to almost any surface except certain plastics, rubber metal and mastics. Glossy surfaces should be sanded prior to application.

Limitations:

StretchKote exterior elastomeric paint should be applied when surface and ambient conditions are between 45°F and 100°F.

Surface Preparation:

Surfaces must be clean and free of bond-inhibiting materials. Failure to correctly prepare the surface may result in product failure.

Application:

StretchKote exterior elastomeric paint may be applied by roller, brush or spray equipment. Always apply StretchKote in a continuous application, working to a wet edge to eliminate cold joints.

Curing/Drying:

Drying time will vary depending on ambient temperature, humidity and film thickness. StretchKote will dry completely within 12-24 hours.

Clean Up:

Clean tools and equipment with water immediately after use.

StretchKote

Technical Bulletin

Precautions:

KEEP OUT OF THE REACH OF CHILDREN. Not for internal consumption. Do not apply in non-ventilated area. Use protective equipment such as gloves, eye protection and clothing.

First Aid:

In case of eye contact, flush with water at least 15 minutes. In case of skin contact, wash affected areas with soap and water. If irritation persists, SEEK MEDICAL ATTENTION. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If discomfort continues, any breathing difficulty occurs or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. For additional information refer to the Material Safety Data Sheet (MSDS).

Disposal:

Dispose of in accordance with local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY

Spills:

Scrape up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Prop 65:

This product contains materials listed by the state of California known to cause cancer, birth defects, or other reproductive harm.

Technical Support:

For technical support call 1-602-352-0888. Information contained in this Technical Bulletin conforms to the standard detail recommendations and specifications for the installations of UltraKote products as of the date published on this document. UltraKote Products, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To insure that you are using the latest, most current information, contact UltraKote Products, Inc.
