


Communication & Control Cables

Communication & Control Cable Multiple Conductor 20 AWG / Overall Shielded

WEST PENN WIRE



Applications:

Indoor for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-limited Control Circuits

Description:

- ASTM Bare Copper • PVC insulation • Overall shield 100% coverage of aluminum polyester foil with 22 AWG Strd. TC drain wire • Cabled construction • Overall PVC jacket

Rating:

- NEC Type CMR
- (UL)-C(UL) Listed or c(ETL)us Listed
- Meets 300V requirements as specified in the NEC
- Flame Rating: UL1666

Standard spool size 1000ft.

Catalog No.	No. of Cond.	Conductor Type & Nom. D.C.R	Insulation	Shielding	Jacket Type	Nom. O.D. Inches	NEC Type	Nom. Capacitance	Jacket Color
			Type & thickness Inches	& % Coverage	& Thickness Inches				
3011	4	20 AWG (7x28) 10.5 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.176	CMR	60 pf/ft* 108 pf/ft**	Gray
3262	5	20AWG (7x28) 10.5 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.193	CMR	60 pf/ft* 108 pf/ft**	Gray
3263	7	20 AWG (7x28) 10.5 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.211	CMR	60 pf/ft* 108 pf/ft**	Gray
3264	9	20 AWG (7x28) 10.5 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.256	CMR	60 pf/ft* 108 pf/ft**	Gray
3265	12	20 AWG (7x28) 10.5 Ω/Mft	PVC .010	Al. Foil 100%	PVC .015	.288	CMR	60 pf/ft* 108 pf/ft**	Gray

* Capacitance between conductors.

** Capacitance between one conductor and the other connected to the shield

Special Notes:

- Select cables are available in our Easybox®
- Orange ripcord included on cables containing 5 or more conductors

Color Code		
Colors	Colors	Colors
1. Black	8. Yellow	15. White/Green
2. Red	9. Purple	16. White/Orange
3. White	10. Gray	17. White/Blue
4. Green	11. Pink	18. White/Brown
5. Brown	12. Tan	19. White/Yellow
6. Blue	13. White/Black*	20. White/Purple
7. Orange	14.. White/ Red	
JACKET: Gray		
*Conductors 13 and above have PERFECT STRIPE®		