Fusible link melts at 165°F (74°C) and cover snaps shut to extinguish flames.

Hinged lid reduces the spread of vapors.

Durable 18-gauge galvanized steel withstands abuse without distortion.



Proper grounding prevents the creation of an arc during filling or pouring.

Wide 10³/4" (273mm) mouth handles* rapid pouring without spills.

Lid latch accepts lock to prevent unauthorized access.

2.6-gallon (9.8L) capacity allows for fast transfer of liquids.

Epoxy powder paint finish provides excellent chemical resistance.

FM approved.

Fits all standard 2" bungs on ••• 30 or 55-gallon (110 & 200L) drums.

Tip-Over Protection System offers additional protection against spills and explosion.

So Simple and Safe!

- 1. Pour liquid into funnel. Close cover and latch.
- 2. Depress handle to manually open the ball valve.
- 3. Release handle to automatically close the valve, sealing the drum.

Tip-Over Protection System has all the features of Justrite's safety funnel No. 08207, with the addition of a self-closing ball valve and vent adapter. The integral self-closing ball valve threads into a 2" drum bung and minimizes vapor emissions as well as preventing spillage if the drum is accidentally tipped over. This makes it ideal for earthquake-prone areas. The system includes a separate brass vent adapter which fits into the 3⁄4" drum bung to provide pressure and vacuum relief for protection against drum rupture or explosion.

Tip-Over Protection System for Drum Funnel



08214



Funnel Size Mouth Funnel Approv./Lstg. Model Description Dia. x Ht (mm) Dia. (mm) **Capacity Gal** Regulation* No. Steel Funnel No. 08207 with Self-closing Cover and 6" (152mm) Flame Arrester and Tip-over Protection Kit. 10¾" x 10" (273 x 254) 10¾" (273) 2.6/10L FM 08203 Tip-over Protection Kit only (Self-close Valve with 2"(51mm) Bung Adapter and Brass Vent with ¾"(19mm) Bung Adapter). For use with Funnel Nos. 08207 or 08205. 08214 FM NOTE: Seals in valve are made from multifill PTFE

08203

Drum Equipment

08207

U

*See page 8 for Regulation Key.

111