

Turn ordinary drums into fire-safe hazardous waste collection centers AND control vapors to comply with EPA/NESAM requirements.

To meet growing green initiatives for controlling vapor releases and VOC emissions, these environmentally supportive Drum Lids offer an easy way to convert open-head drums into compliant hazardous waste receptacles. In addition to meeting EPA and NESAM, all are FM Approved for fire safety and comply with OSHA requirements for closed container storage of flammables. Lids are steel with a chemically resistant powder paint finish and they require only a screwdriver and wrench to install on a drum.

To control vapors when disposing of solvent-soaked rags and wipes, **Model No. 26752** complies with NESAM by offering a gasketed, manual latching lid to seal the drum – preventing vapor release. A vent is installed which relieves pressure buildup between 3 and 5 psig (0.2 and 0.35 bar) at elevated temperatures. Ideal for the aircraft, furniture and printing industries, and anywhere solvent-soaked cloths are used. Design accepts optional padlock for security.

**Model No. 26753** offers a greater degree of safety while meeting NESAM. This self-latching, vented drum cover simplifies your waste collection and containment efforts with a spring loaded, rotary latch mechanism and gasketed lid to control vapor release and VOC emissions. Because it automatically closes via gravity when released and then automatically latches, it prevents the drum from being left open by mistake. This eliminates the chance for oxygen to enter and start a fire.

Vapor Trap™ Lid No. 26754 controls odors and vapors with a gasketed lid and gasketed 4-3/4" (121mm) easy-access port for fast discards of smaller containers such as used lubricants, motor oils and additives, and non-reusable cosmetics such as demonstration colognes and skin products used in retail settings. Safety vent relieves pressure-build up at elevated temperatures. Manual latching lid is designed to accept an optional padlock to minimize access to contents.









Gasketed, vented, manual latching

Meets the National Emissions Standard for Aerospace Manufacturing (NESAM) Regulation 60 FR 45956; Subpart GG 63.741



Gasketed, vented, self-latching



Gasketed, vented, manual latching with added easy-access port for small items

<b>Environmental Drum Lids</b>	Approv./Lstg.	
Description	Regulation*	Model No.
Manual Drum Lid With Gasket and Vent for 55 gallon (200L) Drums	FM,NESAM	26752
Self-latching 55-gallon (200L) Drum Lid with Vent and Gasket	FM,NESAM	26753
Vapor Trap™ Drum Lid for 55 gallon (200L) Drums	FM,NESAM	26754 <b>New</b>
Open Head 55-gallon (200L) Drum		26054
Open Head 30-gallon (110L) Drum		26014

\*See page 8 for Regulation Key.

