

Type I Cans FOR FLAMMABLES

Counterbalance engineering offers easy, safe handling of flammable liquids.

- Fully compliant – meets OSHA and NFPA Code 30
- Passes independent rigorous testing – FM approved, UL/ULC listed, and TÜV certified. All are accepted under CARB
- Self-closing lid controls vapors and spills
- Full length, chemically resistant stainless steel flame arrester dissipates heat to prevent flashback ignition. Longer length allows easy, secure placement of gas nozzle
- Large ID Zone identifies contents to reduce misuse or to designate department, shift or crew
- Leakproof, positive pressure relief cap automatically vents to prevent rupture or explosion
- Rounded steel comfort handle doesn't cut into hand
- Premium 24-gauge coated steel body and handle for maximum durability and chemical resistance
- Large 1/2" (13mm) grip lip along bottom helps support pouring
- Reinforcing ribs strengthen side walls for extra "bumper guard" protection
- Double-lock seams provide four thicknesses of steel to guard against bumps and bangs
- Durable, high-gloss powder paint finish resists solvents, corrosion and humidity
- Trilingual warning label in English/Spanish/French
- 100% tested to guarantee leakproof construction
- Quality backed by exclusive Ten-Year Warranty



Safety Containers



7150110



11089



11202Y



Poly-funnel folds down for filling and storage!

To aid pouring into smaller openings, this two-position funnel easily attaches to Type I steel safety cans. Large rounded bowl provides protection from splashing and spillage. Innovative hinged design allows you to fill or pour from the can without removing the funnel and takes up less space during storage. Durable polypropylene material holds up to heavy use.

Type I Red Safety Cans for Flammables

Description and Capacity	Dimensions Outer Dia. x H (mm)	Approv./Lstg. Regulation*	Model No.
1 pint (0.5L) Steel Safety Can	4 ³ / ₈ " x 6 ³ / ₄ " (117 x 172)	FM,UL/ULC,TÜV	10001
1 quart (1L) Steel Safety Can	4 ³ / ₈ " x 8 ¹ / ₄ " (117 x 210)	FM,UL/ULC,TÜV	10101
1 gallon (4L) Steel Safety Can	9 ¹ / ₂ " x 11" (241 x 279)	FM,UL/ULC,TÜV	7110100
1 gallon (4L) Steel Safety Can w/11202Y Funnel	9 ¹ / ₂ " x 11" (241 x 279)	**FM,UL/ULC,TÜV	7110110
2 gallon (7.5L) Steel Safety Can	9 ¹ / ₂ " x 13 ³ / ₄ " (241 x 349)	FM,UL/ULC,TÜV	7120100
2 gallon (7.5L) Steel Safety Can w/11202Y Funnel	9 ¹ / ₂ " x 13 ³ / ₄ " (241 x 349)	**FM,UL/ULC,TÜV	7120110
2 1/2 gallon (9.5L) Steel Safety Can	11 ³ / ₄ " x 11 ¹ / ₂ " (298 x 292)	FM,UL/ULC,TÜV	7125100
2 1/2 gallon (9.5L) Steel Safety Can w/11202Y Funnel	11 ³ / ₄ " x 11 ¹ / ₂ " (298 x 292)	**FM,UL/ULC,TÜV	7125110
5 gallon (19L) Steel Safety Can	11 ³ / ₄ " x 16 ⁷ / ₈ " (298 x 429)	FM,UL/ULC,TÜV	7150100
5 gallon (19L) Steel Safety Can w/11202Y Funnel	11 ³ / ₄ " x 16 ⁷ / ₈ " (298 x 429)	**FM,UL/ULC,TÜV	7150110

** Approvals apply to safety can

Funnel Attachments for Type I Steel Safety Cans

Description	Dimensions Outer Dia. x L(mm)	Model No.
Bolt-on Funnel with Galvanized Hose; for Steel Cans only	1" x 14" (25 x 356)	11089
Polypropylene Funnel; for Steel Cans only sizes 1 gallon (4L) and above	1/2" x 11 ¹ / ₄ " (13 x 286)	11202Y

*See page 8 for Regulation Key.



1-800-798-9250 • Fax: 1-800-488-5877 • www.justritemfg.com