PRO-Line™ Temporary Horizontal Lifeline



Total
Compliance.
Absolute
Confidence.

A Simple,
Versatile
and Safe
Horizontal Lifeline
Designed for
Demanding
Jobsite.



Extremely Portable System Installs in Just Seconds!

- Extremely fast set-up, removal and storage with built-in tensioner and carrying bag - no special tools needed
- Complete kit includes two tie-off adaptors for simple anchorage to structure
- Built-in shock absorber reduces anchorage loadings to preserve the structure
- Fall arrest rated for two users provides jobsite flexibility
- 60 ft. (18m) web lifeline is compact, portable and versatile
- Meets all applicable industry standards including OSHA regulations

PRO-Line™ Temporary Horizontal Lifeline



Ultimate Jobsite Versatility

The PRO-Line™ horizontal lifeline systems are lightweight, easy to install and extremely portable. Just disassemble and take to the next job. PRO-Line™ systems will work alongside you during maintenance, bridge work, construction and manufacturing with absolute safety and reliability.

Fast and Easy Installation

The PRO-Line™ system installs in seconds, without special tools or equipment, maintaining

maintaining optimum worker productivity.

Simply attach the lifelline and tie-off adaptors to 5,000 lb. (22 kN) rated anchorage points and tension the lifeline with the integrated ratchet. The system is extremely lightweight and portable, allowing you to move it and reuse it over and over again. Refer to the user instruction manual for complete operating details including required clearance distances.

Complete Worker Confidence

The built-in shock absorber limits arresting forces during a fall and provides the user with a visual impact indicator for added safety. Connection to the lifeline is made by attaching the hook of a shock absorbing lanyard directly to the lifeline for complete ease-of-use. The carrying bag makes transporting and storing the system easy, reduces damage from dirt, moisture and UV degradation thus improving the longevity of the system.

Standards and Warranty

Reliability that saves you worry, time and money. PRO-Line™ complies with OSHA requirements. The reputation of Protecta stands behind every one of our products supported by a two year warranty on parts and workmanship.



PRO-Line™ Horizontal Lifeline System Models:

1200101: 60 ft. (18m) PRO-Line™ Horizontal Lifeline System; lifeline with tensioner, shock absorber and bag, and two 6 ft (1.8m) tie-off adaptors

1200105: 60 ft. (18m) PRO-Line™ Horizontal Lifeline System; lifeline with tensioner, shock absorber and bag

Specifications:

Lifeline Webbing: 2" (50mm) Polyester, 11,000 lbs. (50 kN) tensile strength **Tie-Off Adaptor Webbing:** 1-3/4" (44mm) Polyester Strength Member with 3" (75mm) Wear Pad **Hardware:** Zinc Plated Alloy Steel, 5,000 lb. (22 kN) tensile strength **Ratchet:** Zinc Plated Steel, 5,000 lb. (22 kN) tensile strength **Standards:** Meets OSHA standards

Capital Safety

USA: 800.328.6146 • Canada: 800.387.7484 • Latin America: +1 651.385.4301 • Asia: +65 6558 7758 • Australia: 1800 245 002 New Zealand: 0800 212 505 • Europe, Middle East, Africa: +33 (0)4 97 10 00 10 • Northern Europe: +44 (0) 1928 571324

Germany: +49 2634 8052 www.capitalsafety.com • info@capitalsafety.com

Form: 9700456 Rev: A

with and without

Tie-Off Adaptors