



## 3-Man Roof Anchor Provides the Ultimate in Worker Safety, Mobility and Productivity!

- Incorporates 3 independent anchorage points for simultaneous use by 3 workers for added jobsite versatility
- Each anchor point swivels 360 degrees for maximum freedom of movement and worker productivity
- Unique load distributing and shock absorbing design reduces the overall stress on the roof during a fall
- Fast, simple and safe installation, requiring only four fasteners per foot to mount
- Versatile design incorporates four articulating feet fitting multiple wood roof pitches from 4-12 to 12-12.
- Lightweight (only 39 lbs) and collapsible design makes transporting, set-up, dismantle and storage quick and easy
- Meets OSHA for up to 3 users, and ANSI requirements for one user



# 3-MAN SWIVELING ROOF ANCHOR

## Continuous Protection and Mobility

This roof anchor provides 360 degrees of protection and mobility for up to three workers. With three independent and rotating anchor points elevated off the roof deck, it is ideal for use with self retracting lifelines (SRL's). The SRL's lifeline extends as the worker moves away, and automatically retracts as the worker moves towards the device providing complete "hands-free" mobility while reducing snagging, dragging and trip-fall hazards. In the event of a fall, the SRL locks quickly reducing overall fall clearances and forces for added safety. With variable length SRL's available, a multiple user rated anchor and 360 degrees of mobility, this system is simply the ultimate in roofing safety and productivity!

**Fast and Efficient Installation** The 3-man roof anchor sets-up in only minutes. The unit is expanded from its storage/collapsed position, then the legs and anchorage mast are pinned into place. Finally, the roof anchor is fastened down through the wood sheathing and into the trusses using sixteen 3-1/2" #8 deck screws (4 screws per foot). The anchor's integrated articulating feet allow it to be mounted to a range of pitched wood roof structures from 4-12 to 12-12. Removal of the anchor is just as quick, and its compact storage design makes transport and relocation easy.

**Load Distributing Design** With a unique load distributing and shock absorbing design that deforms in the event of a fall, the anchor will help dissipate the energy from the fall evenly to the roof, reducing the chance of damage to the roof structure. This design also reduces the number of fasteners required (four per foot) to install the anchor to the roof, saving valuable time!



< 2103690  
Shown  
Ready for  
Installation

2103690 >  
Shown  
In Storage  
Position

## 3-Man Roof Anchor Models:

**2103690:** 3-Man Swiveling Roof Anchor, with 3 independent fall arrest rated anchor points that swivel 360 degrees, for use on wood roof structures with pitches ranging from 4-12 to 12-12.

NOTE: Order user equipment including self retracting lifelines, shock absorbing lanyards or rope grabs and lifelines separately.

## Specifications:

**Material:** Hot Rolled Steel Plate, Zinc Plated or Powder Coated, 6061-T6 Aluminum-Anodized, 304 Stainless Steel **Hardware:** Grade 5/Grade 8 Zinc Plated **Weight:** 39 lbs. (17.5kg) **Size (Collapsed):** 9" x 9" x 40" (22.5 x 22.5 x 100cm) **Size (Extended):** 36" x 36" x 54" (90 x 90 x 135cm) **Standards:** Meets OSHA for up to 3 users, and ANSI requirements for one user

## Capital Safety

USA : 800.328.6146 • Canada : 800.387.7484 • Asia : + 852 2992 0381 • Australia/New Zealand : 800 245 002  
Europe, Middle East, Africa : +33 (0) 497 10 00 10 • Northern Europe : +44 (0) 1928 571324  
[www.capitalsafety.com](http://www.capitalsafety.com) • [info@capitalsafety.com](mailto:info@capitalsafety.com)