

TALON™ 100% TIE-OFF SELF RETRACTING LIFELINE



Twin-Leg 100% Tie-Off Design Provides Continuous Fall Protection and Added Mobility.

- The industry's first twin-leg SRL is truly unique and innovative
- Quick-connect handle and built-in strap secures SRL directly to the harness and keeps unit in position
- Two separate 6 ft. lifelines extend and retract as the worker moves, providing continuous fall protection without restrictions
- Impact indicator on each lifeline makes inspections quick and easy
- Compact, lightweight design does not hinder movement providing added worker satisfaction and productivity
- Durable nylon plastic housing features a non-obtrusive design with rounded corners, providing all-day comfort
- Available with standard or large throat opening hooks for effective attachment to most anchorages
- Meets all applicable industry standards including OSHA, ANSI Z359.1, CSA Z259.2.2 (type 1), CE compliant models available.

Shown: 3102000
Attached to
Delta™ II Harness

TALON™
SELF RETRACTING LIFELINE

TALON™ 100% TIE-OFF SELF RETRACTING LIFELINE



Continuous Protection The 100% Tie-Off Talon with twin-legs provides continuous fall protection and a significant increase in mobility. The unique design allows the user to attach one lifeline leg to the anchor point, move to a new location and connect the second, then disconnect the first and move again. This “leap-frog” action provides 100% protection while moving from one location to another. Each lifeline works independently, extending up to 6 feet and automatically retracting providing fall protection and mobility 100% of the time!

Reduced Fall Distances and Forces Talon’s automatic, inertia activated brake will lock quickly stopping a falling worker within inches - providing more protection at low heights. With the lifeline secured overhead, the total fall distance (free-fall + deceleration) is limited to 42 inches or less. By reducing fall distance, the arresting forces are also minimized helping keep the worker safe and sound.

User Friendly Talon quickly and easily attaches directly to the back of the user’s harness by means of the built-in quick-connect handle. A securing strap holds the Talon in the correct position, preventing it from moving around during the users work activities. The twin-leg lifeline hooks can simply be attached to the front of the harness when not in use, keeping them out of the way. The small and lightweight housing comfortably stays on the user’s back, out of the way, but always ready to stop the fall.



< 3102000 Shown
Each Talon Includes
Delta™ Comfort Pad
and Two Lanyard
Keepers

Harness >
Attachment
Detail



Talon 100% Tie-Off Models:

3102000: Talon 100% Tie-Off SRL with 9502058 2-1/4” throat opening aluminum hook on each lifeline, includes Delta™ Comfort Back Pad (9501207) and two Lanyard Keepers (9504374)

3102001: Talon 100% Tie-Off SRL with 9502116 3/4” throat opening steel hook on each lifeline, includes Delta™ Comfort Back Pad (9501207) and two Lanyard Keepers (9504374)

3102002: Talon 100% Tie-Off SRL with 9502195 3/4” throat opening swiveling steel hook on each lifeline, includes Delta™ Comfort Back Pad (9501207) and two Lanyard Keepers (9504374)

3102003: Talon 100% Tie-Off SRL with 2109193 2-1/4” throat opening steel hook on each lifeline, includes Delta™ Comfort Back Pad (9501207) and two Lanyard Keepers (9504374)



9502116 9502195 2109193 9502058

Talon Lifeline Hook Options

Specifications:

Lifeline: 6 foot length each leg, 1 inch wide nylon lifeline **Housing:** Nylon plastic **Hooks:** 5,000 lb. minimum tensile strength, 9502116 = 3/4” gate opening, alloy steel, 9502195 = 3/4” gate opening, swiveling, alloy steel, 2109193 = 2-1/4” gate opening, alloy steel, 9502058 = 2-1/4” gate opening, aluminum **Capacity:** 75-310 lbs.
Anchorage Handle: Steel, locking type, quick-connect **Retraction Spring:** Stainless steel **Brake:** Heat treated alloy steel and stainless steel **Size:** 7.2” length x 3.8” width x 2.6” thick **Weight:** 5.4 lbs. (3102000 model) **Max. Arresting Force:** 900 lbs. **Maximum Arresting Distance:** 42 inches **Average Locking Speed:** 4.5 ft/sec **Standards:** Meets or exceeds all applicable industry standards including OSHA, ANSI Z359.1, CSA Z259.2.2 (type 1), CE compliant models available.

Capital Safety

USA : 800.328.6146 • Canada : 800.387.7484 • Asia : + 852 2992 0381 • Australia/New Zealand : 800 245 002
Europe, Middle East, Africa : +33 (0) 497 10 00 10 • Northern Europe : +44 (0) 1928 57 1324
www.capitalsafety.com • info@capitalsafety.com