

# PERIMETER LIMITER LEADING EDGE FALL PROTECTION SYSTEM



**The Perimeter Limiter leading edge anchor is ideal for concrete decking construction by providing overhead anchorages for up to 2 users.**



\*Winch & SRLs not included.

- The freestanding, non-penetrating design allows the anchor to be ready for use once placed on the decking structure.
- Overhead anchorages for two users reduce the fall distances imposed on the users while minimizing swing falls.
- Large foam filled trailer tires allow the Perimeter Limiter to be very maneuverable around the decking application, plus they will never go flat.
- The mast and anchorage arm can rotate around the weighted base and lock out in any position giving you ultimate freedom of movement.
- Accessory holes on the vertical and main horizontal arm for the addition of rescue retrieval winches or job site tool boxes.
- Additional weight and taller mast can be added to make unit extend from 7.5' to 9.5' tall.



**Rescue Retrieval Winch**  
*Attaches to Accessory Holes*



**Overhead Anchorage**  
*For up to 2 Users*

# PERIMETER LIMITER LEADING EDGE FALL PROTECTION SYSTEM



## Complete Job Site Flexibility:

The DBI-SALA Perimeter Limiter's design makes the anchor very versatile in how easy it is to initially set up and then use. Once craned into position on the deck, the Perimeter Limiter is pushed to a location and lowered onto the deck. That's it, no assembly or tools required, the anchor is now ready to use! When it comes time to relocate the anchor to another area, it can be maneuvered in two ways. The Perimeter Limiter's mast and anchorage arm can rotate around the counterweights making relocation to another close by area much quicker and more

efficient than the competition's. If the anchor has to move across the deck to an area further away, the foam filled trailer tires and up front push bars make the unit the most easy to maneuver and relocate in the industry today.



**Foamed-Filled  
Trailer Tires**

## Minimized Fall Distances:

Whether you are using the standard unit - which locates the anchorage connector for your personal fall arrest system at a 7.5 ft height - or you add the kit that replaces the standard mast with one that lengthens the unit to 9.5 ft, both yield the same result: an overhead anchor for up to two users minimizing fall distances while reducing swing falls.



**Overhead Anchorage  
For up to 2 Users**



## Perimeter Limiter:

**2100090:**  
**2100091:**

**Perimeter Limiter, 1655 lbs, 7.5 ft in height  
Kit to lengthen to 9.5 ft in height, additional  
mast and 200 lbs of counterweights.**

## Rescue Capabilities

Rescue Capabilities have been integrated into the Perimeter Limiter, which comes standard with an overhead pulley and mounting bracket that allows you to use a SALA or Advanced System's rescue winch in the event of a fall. Once attached to the winch via a 1st Man Up System, simply lower the fallen user to the next floor below.

## Specifications:

**Material:** Powder coated and galvanized steel. **D-rings:** zinc plated alloy steel. **Tires:** Foamed filled. **Capacity:** 2 users, 310 lbs each.

## Capital Safety

USA: 800.328.6146 • Canada: 800.387.7484 • Asia: + 852 2992 0381 • Australia: 1800 245 002 • New Zealand: 0800 212 505  
Europe, Middle East, Africa: +33 (0) 497 10 00 10 • Northern Europe: +44 (0) 1928 571324  
[www.capitalsafety.com](http://www.capitalsafety.com) • [info@capitalsafety.com](mailto:info@capitalsafety.com)