



Innovative Design Brings Rope Access Positioning To The Ultimate Comfort Full Body Harness.

- Includes both chest and waist D-ring attachment points ideal for use with rescue ascender during rope access
- Ergonomic hip pad and belt with side D-rings for positioning and tool rings to hold extra equipment
- Constructed in the shape of an "X" that wraps around the worker for ultimate comfort and no-tangle donning
- Removable shoulder and leg padding provides maximum comfort and makes washing easy
- Vest style design with built-in soft edging greatly reduces chaffing and rubbing
- Patented spring loaded "stand-up" dorsal D-ring ensures fast, easy and safe connections
- Durable one-handed quick-connect buckles make donning, adjusting and removing the harness fast and easy
- Built-in sub-pelvic strap absorbs forces in the event of a fall which is not standard on most rope rescue harnesses
- Meets all applicable industry standards including OSHA and ANSI Z359 (CSA Pending)



A Hybrid Harness Specifically Designed for the Demands of Rescue and Rigging

The ExoFit[®] XP Rescue Harness is a new breed of body support for the rope access/rescue professional. It incorporates a unique blend of fall arrest, positioning, suspension and rescue attachment points without sacrificing premier comfort and safety. The most dependable and comfortable harness in fall protection now features the essential components for rigging and rescue. Many rescue harnesses on the market are built by simply attaching shoulder straps to a mountaineering harness without recognizing the importance of fall arrest. DBI-SALA's engineers have created a hybrid for those who want both all-day comfort and safety while suspended at height or moving from one location to another.

Perfect Blend of Components

Whether performing rope rescue off of an I-beam on a construction site or rigging in the ceiling of an arena, professionals demand a comfortable harness that will help them get the job done right. The ExoFit[®] XP Rescue Harness incorporates both chest and waist D-ring attachment points that are ideal for suspension or for use with a rescue descender if required. An ergonomic hip pad and body belt with side D-rings provide added comfort and back support during rigorous work positioning activities. Unlike most other rescue harnesses on the market, DBI-SALA's ExoFit[®] XP uses a sub-pelvic strap to channel the energy of a fall throughout the body greatly reducing the chance of injury. Finally, the ExoFit[®] XP provides the ultimate in wrap around comfort with removable shoulder, leg and back padding and soft edging to help prevent rubbing and chaffing.

Easy to Use without Sacrificing Safety

One-handed quick-connect buckles and a spring loaded "stand-up" dorsal D-ring ensures fast donning and safe connections - an absolute must if a prompt rescue is needed. We've also built-in accessory/tool rings to the hip pad/belt for better support and comfort when carrying extra equipment and gear. Every DBI-SALA harness combines maximum comfort, freedom of movement and ease of use without sacrificing safety. They are all designed to securely retain a worker in case of a fall and distribute the impact forces throughout the body.

Whether you wear a harness 4 hours a day or 14 hours a day, it needs to feel good and fit right for optimum comfort, safety and productivity. DBI-SALA harnesses are designed to fit you, no matter what your size or shape!



Chest and Waist D-ring Attachment Points



Tool/Equipment Ring and Strap (one on each hip)



ExoFit™ XP Rescue Harness Models:

1111550 : ExoFit™ XP Rescue Harness with front, waist, side and back D-rings, hip pad and belt, quick-connect buckles (size Small)

1111551 : ExoFit™ XP Rescue Harness with front, waist, side and back D-rings, hip pad and belt, quick-connect buckles (size Medium)

1111552 : ExoFit™ XP Rescue Harness with front, waist, side and back D-rings, hip pad and belt, quick-connect buckles (size Large)

1111553 : ExoFit™ XP Rescue Harness with front, waist, side and back D-rings, hip pad and belt, quick-connect buckles (size Extra-Large)

NOTE: For CSA models in Canada, add a "C" at the end of the part number

Specifications:

Webbing: Polyester 1 ¾" (45mm) **Hardware:** Zinc plated alloy steel **Labels:** Vinyl **Capacity:** 420lbs **Standards:** Meets or exceeds all applicable industry standards including OSHA and ANSI Z359.1 (CSA Pending)

Capital Safety

USA: 800.328.6146 • Canada: 800.387.7484 • Asia: +65 6558 7758 • Australia: 1800 245 002 • New Zealand: 0800 212 505
Europe, Middle East, Africa: +33 (0)4 97 10 00 10 • Northern Europe: +44 (0) 1928 571324
www.capitalsafety.com • info@capitalsafety.com