



ASTM COMPLIANT PRODUCTS IN A CONVENIENT TRAVEL PACKAGE.

- Carry with you as you go from job to job
- Perfect for use in bucket truck applications; fast and easy use when working in any industry where high voltage electricity is a concern
- Complete fall protection and protection against an arc flash in one simple package
- Harness incorporates no metal above the waist and web loop to web loop connection ensures greater reduction of conductivity
- Meets ASTM F887-05 and ANSI Z359.1

DBI-SALA
Harnesses are



iSAFE[™]
INTELLIGENT
SAFETY SYSTEM
EQUIPPED

Standards & Arc Flash Testing

The American Society for Testing and Materials (ASTM) published its "Standard Specification for Personal Climbing Equipment" in March 2004 including only harnesses. In December 2005 ASTM F887-05 was published including both harnesses and shock absorbing lanyards. Testing for fall protection is performed in two steps. The first exposes the equipment to an arc flash at 40 cal/cm² and the second is a drop test compliant with ANSI Z359.1 after the exposure.

Criteria

Exposed specimens shall meet the following criteria:

1. No electric arc ignition
2. No melting or dripping
3. Pass drop test after the exposure
4. No greater than 5 seconds of after-flame.

All of DBI-SALA's arc flash equipment has been tested to perform in accordance with these criteria. Our Arc Flash kit provides you ASTM compliant fall protection gear in a convenient travel package. This kit is ideal for personnel who perform their work at height and around high voltage electricity.



Specifications:

Delta™ II Arc Flash Full Body Harness

- Meets ASTM F887-05 standard – electric arc performance of 40 cal/cm²
- Delta™ No-Tangle design holds the shape of the harness making it easier to don
- 7000 lb (28kN) Nylon webbing
- Pass-Thru buckles
- No metal above the waist style
- Dorsal web loop

EZ Stop® II Arc Flash Lanyards

- Meets ASTM F887-05 standard – electric arc performance of 40 cal/cm²
- Nomex®/Kevlar® fabric shock absorbing cover
- Single leg
- Resist technology webbing
- Nomex®/Kevlar® web loop
- Standard DBI-SALA Snap hook
- Limits arresting forces to 900 lbs. (4kN) or less

Available Options :

USA

1150054 : Arc Flash Kit LG
 1110751 Delta™ II Arc Flash Harness - LG
 1220861 EZ Stop® II Arc Flash Lanyard
 9511597 Carrying Bag

1150058 : Arc Flash Kit XL
 1110752 Delta™ II Arc Flash Harness - XL
 1220861 EZ Stop® II Arc Flash Lanyard
 9511597 Carrying Bag

Canada

1150054C : Arc Flash Kit LG
 1110751C Delta™ II Arc Flash Harness - LG
 1220861C EZ Stop® II Arc Flash Lanyard
 9511597 Carrying Bag

1150058C : Arc Flash Kit XL
 1110752C Delta™ II Arc Flash Harness - XL
 1220861C EZ Stop® II Arc Flash Lanyard
 9511597 Carrying Bag

Capital Safety

USA: 800.328.6146 • Canada: 800.387.7484 • Asia: +65 6558 7758 • Australia: 1800 245 002 • New Zealand: 0800 212 505
 Europe, Middle East, Africa: +33 (0)4 97 10 00 10 • Northern Europe: +44 (0) 1928 571324
www.capitalsafety.com • info@capitalsafety.com