

# DIAMOND SWITCHBOARD MATTING

#831

INSULATIVE/NON-CONDUCTIVE • "BEST"



- **Sales Tip:** We highly recommend that the mat be replaced every 12 months for optimum performance.
- **Where to Specify:** : In front of high voltage boxes, electrical fuse boxes, transformers.

- Insulative PVC matting is formulated to provide insulation to the worker from being grounded thus preventing electrical shock
- Each square foot of this matting is tested in conformance with ANSI/ASTM D-178 specifications and meets or exceeds the following:
  - Type 2 Compound: Polyvinyl Chloride
  - Class 2 Di-electric Strength: 30,000 volts
  - Proof test of 20,000 volts
  - Recommended maximum usage of 17,000 volts



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NoTRAX® INDUSTRIAL MATS

Black

Black / Yellow

<b>#831</b>			
<b>Roll Sizes - Black</b>	<b>2' x 75'</b>	<b>3' x 75'</b>	<b>4' x 75'</b>
<b>Weight (lbs.)</b>	240	360	480
<b>Custom Sizes - Black</b>	<b>2' Widths</b>	<b>3' Widths</b>	<b>4' Widths</b>
<b>Weight (lbs.)</b>	1.60/sq.ft.	1.60/sq.ft.	1.60/sq.ft.
<b>Roll &amp; Custom Sizes - Colored Borders</b>		<b>3' x 75'</b>	<b>3' Widths</b>
<b>Weight (lbs.)</b>		360	1.60/sq.ft.
Shipping Location: Superior Manufacturing Group - Moselle, MS 39459			

