## **Rebel™6 Self Retracting Lifeline (SRL)**

ehe

PROTECTA



The Rebel™6 incorporates all of the industry proven features of the 11 and 20 ft. (3.4m & 6m) web lifeline Rebel™ models, but is now available in a 6ft (1.8m) length. Lightweight and Compact SRL is Ideal for Replacing Lanyards

- Economically replace lanyards with the versatility and added safety of a 6 ft. (1.8m) self retracting lifeline
- Retractable technology reduces fall clearance and trip hazards for complete safety
- Rugged aluminum housing can withstand rough use, yet weighs only 2.6 lbs. (1.2kg)
- Unique super-strength thin webbing for total security and added length in a compact SRL
- 2-year warranty on parts and workmanship, plus no anual re-certification is required
- Meets all applicable industry standards including OSHA, ANSI Z359.1 and CSA

# **Rebel™6 Self Retracting Lifeline (SRL)**



#### Performance, Safety and Value

With a 6 ft. (1.8m) length and competitive pricing, employers can economically replace simple lanyards with the versatility and added safety of a self retracting lifeline. The retractable technology deployed in the Rebel<sup>™</sup> SRL's ensures falls are stopped within a few inches, making Rebel<sup>™</sup> SRL's safer than traditional lanyards.

#### Lightweight, Compact and Durable

The Rebel<sup>™</sup>6 incorporates a rugged aluminum housing and stainless steel working components that can withstand rough use, yet weighs only 2.6 lbs. (1.2kg). The unique thin webbing enables a compact size (4"dia. x 2" thick - 10cm x 5cm) that is easy to use.

#### **Ergonomic for Greater Worker Comfort**

With a smooth case and rounded corners, the Rebel<sup>™</sup>6 provides added comfort and ease-of-use. It increases worker productivity and reduces worker fatigue for ultimate worker satisfaction.

#### Limits Fall Clearance and Forces for Safety

A unique speed sensing brake keeps forces to a minimum, and reduces clearance requirements. With a maximum arresting force of 900 lbs. (4kn), it supports a capacity of 310 lbs. (140kg).



#### Rebel™6 Models - USA:

3101114: Rebel™6 SRL, 6 ft (1.8m) web lifeline, snap hook 3101116: Rebel™6 SRL, 6 ft (1.8m) web lifeline, snap hook, housing carabiner

#### **Rebel™6 Models - Canada:**

3101118C: Rebel™6 SRL, 6 ft web (1.8m) lifeline, snap hook, housing carabiner

Also Available with 11 and 20 ft (3.4m & 6m) web lifeline and 15 ft (4.5m) 3/16" cable lifeline.

### Specifications:

**Webbing:** 6 feet (1.8m) of 1" (2.5cm) wide polyester webbing (shock absorber is nylon) **Housing:** Anodized aluminum **Stainless Steel Components:** Drum spring, pawls, pawl springs, shaft, ratchet plate, end plates and external fasteners **Snap Hook:** Chrome plated alloy steel, 5,000 lb. (22kn) minimum tensile strength **Capacity:** 310 lbs. (140kg) **Weight:** 2.6 lbs. (1.2kg) **Size:** 4 inches diameter x 2 inches thick (10cm x 5cm) **Maximum Arresting Force:** 900 lbs. (4kn) **Standards:** Meets OSHA, ANSI Z359.1 and CSA

#### **Capital Safety:**

USA: 800-328-6146 • Canada: 800-387-7484 • Latin America: +1 651-385-4301 • Asia: +65 6558 7758 • Northern Europe: +44 (0) 1928 571324 Europe, Middle East & Africa: +33 (0)4 97 10 00 10 • Germany: +49 2634 8052 • Australia: 1800-245-002 • New Zealand: 0800 212 505 Or visit: WWW.CAPITALSAFETY.COM