

Total Compliance. Absolute Confidence.

*A Portable, Reusable,
Durable and Safe
Anchor for
Concrete
Applications*



Versatile and Easy-to-Use Anchor for Concrete Applications

- **Designed for temporary vertical wall, floor mount or overhead ceiling installation into concrete**
- **Portable and reusable anchor provides added jobsite flexibility and lower cost of ownership**
- **Unique forged connection ring provides a compatible tie-off point for added safety**
- **Constructed of stainless steel, aluminum and other non-corrosive materials for a longer service life**
- **For complete safety, 5,000 lbs. (22 kN) fall arrest rated, meets OSHA and ANSI Z359.1**

Reusable Concrete Anchor



Fast, Easy and Safe Installation

Installation is simple and efficient, taking just seconds utilizing standard concrete tools.

- Drill a 3-1/2" (8.89cm) to 4" (10.16cm) deep hole with rotary hammer and 3/4" (19.05mm) drill bit.
- Pull up on the trigger until it's fully retracted.
- Insert anchor into hole until release plug seats against concrete surface.
- Pull on the D-ring to set the anchor in place and connect your personal fall arrest system.

Release of the anchor is just as fast. Simply pull up on the trigger and you're ready to move to the next location. Refer to instruction manual for complete details.



Anchorage Requirements

The concrete must have a minimum compressive strength of 3000 psi (2,685 kPa). The concrete base material must be at least 5" (12.7cm) thick and the mounting hole location from the edge is dependent upon the concrete thickness and width (refer to instruction manual for complete details).

Standards and Warranty

Reliability that saves you worry, time and money. Complies with OSHA and ANSI requirements. The reputation of Protecta stands behind every one of our products supported by a two year warranty on parts and workmanship.

Capital Safety:

USA: 800-328-6146 • Canada: 800-387-7484 • Latin America: +1 651-385-4301 • Asia: +65 6558 7758 • Northern Europe: +44 (0) 1928 571324
Europe, Middle East & Africa: +33 (0)4 97 10 00 10 • Germany: +49 2634 8052 • Australia: 1800-245-002 • New Zealand: 0800 212 505

Or visit: WWW.CAPITALSAFETY.COM



Reusable Concrete Anchor:

2190053: Reusable Concrete Wedge Anchor

Specifications:

Size: 3/4 inch (19.05 mm) **Capacity:** 5,000 Lbs. (22 kN)
Rating: Single user fall protection up to 310 Lbs. (141 Kg)
Weight: 0.78 Lbs. (354 g) **Cable Material:** Galvanized Steel
Anchor Chocks & Shaft Material: Stainless Steel **Release Plug Material:** Zinc Plated Steel **Trigger Material:** Aluminum
D-Ring Material: Forged Steel **Standards:** OSHA and ANSI Z359.1