

**Three Phase,
Totally Enclosed,
460 & 230/460 Volts,
Foot Mounted**

1 thru 400 Hp

NEMA 143T thru 449T

Applications: Petro-chemical plants, mines, foundries, pulp and paper plants, waste management facilities, chemical plants, tropical climates and other processing industry applications requiring protection against corrosion caused by severe environmental operating conditions.

Features: ECP motors are XEX designs. 1.15 Service Factor, corrosion resistant epoxy finish, regreasable ball or roller bearings, oversized rotatable cast iron conduit box, cast iron frames, V-Ring shaft seal, moisture resistant copper windings, Class F insulation, stainless steel nameplate and corrosion resistant hardware. ECP/XEX Super-E® motors have NEMA Premium® efficiency and 3 year warranty. Positive lubrication system (PLS) on 360 frames and larger.



Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)	
1	3600	143T	TEFC	CP3580T-4	708	SD	12.75	50	77	460	1.5	D	1	
		143T	TEFC	ECP3580T	837	SD	12.88	55	84	208-230/460	1.4	A	1	
		143T	TEFC	ECP3580T-4	837	SD	12.88	55	84	460	1.4	A	1	
		143T	TENV	ENCP3580T-4	876	SD	11.38	56	84	460	1.3	C	1	
	1800	143T	TEFC	CP3581T	714	SD	12.75	55	82.5	208-230/460	1.6	D	1	
		143T	TEFC	CP3581T-4	714	SD	12.75	56	82.5	460	1.7	D	1	
		143T	TEFC	ECP3581T	920	SD	12.88	66	87.5	208-230/460	1.5	A	1	
		143T	TEFC	ECP3581T-4	920	SD	12.88	65	87.5	460	1.5	A	1	
	1200	143T	TENV	ENCP3581T-4	958	SD	11.36	60	85.5	460	1.4	C	1	
		145T	TEFC	CP3582T	849	SD	12.75	64	80	208-230/460	1.8	D	1	
		145T	TEFC	CP3582T-4	849	SD	12.75	65	80	460	1.8	D	1	
		145T	TEFC	ECP3582T	1,016	SD	12.88	67	82.5	208-230/460	1.8	A	1	
	1 1/2	3600	145T	TEFC	ECP3582T-4	1,016	SD	12.88	69	82.5	460	1.8	A	1
			184T	TEFC	ECP3687T-4	1,427	SD	15.93	143	82.5	460	1.8	B	1
			143T	TEFC	CP3583T-4	803	SD	12.75	59	82.5	460	2.1	D	1
			143T	TEFC	ECP3583T	952	SD	12.88	71	85.5	208-230/460	2	A	1
1800		143T	TEFC	ECP3583T-4	952	SD	12.88	66	85.5	460	2	A	1	
		145T	TEFC	CP3584T	729	SD	12.75	60	84	208-230/460	2.4	D	1	
		145T	TEFC	CP3584T-4	729	SD	12.75	62	84	460	2.1	D	1	
		145T	TEFC	ECP3584T	937	SD	12.88	68	88.5	208-230/460	2.1	A	1	
1200		145T	TEFC	ECP3584T-4	937	SD	12.88	71	88.5	460	2.1	A	1	
		182T	TEFC	CP3667T	977	SD	15.62	127	85.5	208-230/460	2.2	D	1	
		182T	TEFC	CP3667T-4	977	SD	15.62	125	85.5	460	2.2	D	1	
		182T	TEFC	ECP3667T	1,189	SD	15.93	142	87.5	208-230/460	2.4	A	1	
900		182T	TEFC	ECP3667T-4	1,189	SD	15.93	135	87.5	460	2.4	A	1	
		184T	TEFC	ECP3668T-4	1,776	SD	15.93	142	84	460	2.4	B	1	
		145T	TEFC	CP3586T-4	855	SD	12.75	64	84	460	2.6	D	1	
		145T	TEFC	ECP3586T	996	SD	12.88	73	86.5	208-230/460	2.5	A	1	
2	3600	145T	TEFC	ECP3586T-4	996	SD	12.88	72	86.5	460	2.5	A	1	
		145T	TEFC	CP3587T	749	SD	12.75	64	84	208-230/460	3.1	D	1	
		145T	TEFC	CP3587T-4	749	SD	12.75	64	84	460	2.8	D	1	
	1800	145T	TEFC	ECP3587T	978	SD	12.88	76	88.5	208-230/460	2.8	A	1	
		145T	TEFC	ECP3587T-4	978	SD	12.88	73	86.5	460	2.7	A	1	
		184T	TEFC	CP3664T	1,045	SD	15.62	132	86.5	208-230/460	2.9	D	1	
	1200	184T	TEFC	CP3664T-4	1,045	SD	15.62	124	86.5	460	2.9	D	1	
		184T	TEFC	ECP3664T	1,204	SD	15.93	150	88.5	208-230/460	3	A	1	
		184T	TEFC	ECP3664T-4	1,204	SD	15.93	137	88.5	460	2.8	A	1	
		184T	TEFC	ECP3664T-4	1,204	SD	15.93	137	88.5	460	2.8	A	1	
	900	213T	TEFC	ECP3772T-4	2,240	SD	20.19	204	85.5	460	3.2	B	1	

(a) See notes on inside back flap.

All ratings are 1.15 service factor at 40°C ambient. All ratings meet 50°C ambient at 1.00 service factor and weatherproof intent of IEEE 45 and USCG 259 marine duty (below deck).

Custom TEFC motors available through 2250 Hp; Open and WPII motors through 15000 Hp. Contact your Baldor•Reliance Sales Representative.

FOR OTHER 208-230/460 VOLT REQUIREMENTS, PLEASE SEE DIRTY DUTY MOTORS ON PAGE 84.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Totally Enclosed, 460 & 230/460 Volts, Foot Mounted

Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
3	3600	182T	TEFC	CP3660T-4	1,027	SD	15.62	109	85.5	460	4	D	1
		182T	TEFC	ECP3660T	1,178	SD	15.62	104	88.5	230/460	3.6	A	1
		182T	TEFC	ECP3660T-4	1,178	SD	15.62	121	88.5	460	3.6	A	1
	1800	182T	TEFC	CP3661T	1,053	SD	15.62	120	87.5	230/460	3.9	D	1, 30
		182T	TEFC	CP3661T-4	1,053	SD	15.62	121	87.5	460	3.9	D	1
		182T	TEFC	ECP3661T	1,238	SD	17.12	139	89.5	230/460	4.2	A	1, 30
	1200	182T	TEFC	ECP3661T-4	1,238	SD	15.62	134	89.5	460	4.2	A	1
		213T	TEFC	CP3764T	1,418	SD	19.31	152	87.5	208-230/460	4.4	D	1
		213T	TEFC	CP3764T-4	1,418	SD	19.31	154	87.5	460	4.4	D	1
	900	213T	TEFC	ECP3764T	1,738	SD	15.93	181	89.5	230/460	4.2	A	1, 30
		213T	TEFC	ECP3764T-4	1,738	SD	15.93	186	89.5	460	4.2	A	1
		215T	TEFC	ECP3775T-4	2,429	SD	20.19	216	85.5	460	4.7	B	1
5	3600	184T	TEFC	CP3663T-4	1,295	SD	15.62	127	87.5	460	6.1	D	1
		184T	TEFC	ECP3663T	1,449	SD	15.93	134	88.5	230/460	5.6	A	1
		184T	TEFC	ECP3663T-4	1,449	SD	15.93	127	88.5	460	6	A	1
	1800	184T	TEFC	CP3665T	1,087	SD	15.62	130	87.5	208-230/460	6.5	D	1
		184T	TEFC	CP3665T-4	1,087	SD	15.62	127	87.5	460	6.5	D	1
		184T	TEFC	ECP3665T	1,260	SD	15.93	139	89.5	230/460	6.6	A	1, 30
	1200	184T	TEFC	ECP3665T-4	1,260	SD	15.93	144	89.5	460	6.6	A	1
		215T	TEFC	CP3768T	1,650	SD	19.31	164	87.5	208-230/460	6.8	D	1
		215T	TEFC	CP3768T-4	1,650	SD	19.31	163	87.5	460	6.8	D	1
	900	215T	TEFC	ECP3768T	1,761	SD	20.19	199	89.5	230/460	6.8	A	1, 30
		215T	TEFC	ECP3768T-4	1,761	SD	20.19	197	89.5	460	6.8	A	1
		254T	TEFC	ECP2280T-4	3,866	SD	24.56	337	89.5	460	7.3	B	1
7 1/2	3600	213T	TEFC	CP3769T-4	1,630	SD	19.31	163	88.5	460	9	D	1
		213T	TEFC	ECP3769T	1,891	SD	19.31	181	90.2	230/460	8.6	A	1
		213T	TEFC	ECP3769T-4	1,891	SD	19.31	180	90.2	460	8.6	A	1
	1800	213T	TEFC	CP3770T	1,449	SD	19.31	158	89.5	208-230/460	9.5	D	1
		213T	TEFC	CP3770T-4	1,449	SD	19.31	168	89.5	460	10.3	D	1
		213T	TEFC	ECP3770T	1,586	SD	20.19	210	91.7	230/460	9.4	A	1
	1200	213T	TEFC	ECP3770T-4	1,586	SD	20.19	210	91.7	460	9.4	A	1
		254T	TEFC	CP2276T	1,793	SD	24.56	301	89.5	208-230/460	9.8	D	1
		254T	TEFC	CP2276T-4	1,793	SD	23.56	296	89.5	460	9.8	D	1
	900	254T	TEFC	ECP2276T	2,520	SD	25.07	344	91.7	230/460	10.7	A	1
		254T	TEFC	ECP2276T-4	2,520	SD	25.07	308	91.7	460	10.7	A	1
		256T	TEFC	ECP2401T-4	4,421	SD	24.56	332	90.2	460	10.5	B	1
10	3600	215T	TEFC	CP3771T-4	1,744	SD	19.31	168	89.5	460	11.7	D	1
		215T	TEFC	ECP3771T	2,014	SD	19.50	203	91.7	230/460	11.2	A	1
		215T	TEFC	ECP3771T-4	2,014	SD	19.50	215	91.7	460	11.2	A	1
	1800	215T	TEFC	CP3774T	1,571	SD	19.31	178	89.5	208-230/460	12.2	D	1
		215T	TEFC	CP3774T-4	1,571	SD	19.31	179	89.5	460	13	D	1
		215T	TEFC	ECP3774T	1,899	SD	19.50	231	92.4	230/460	12.5	A	1
	1200	215T	TEFC	ECP3774T-4	1,899	SD	19.50	231	92.4	460	12.5	A	1
		256T	TEFC	CP2332T	2,534	SD	24.56	319	89.5	230/460	12.9	D	1
		256T	TEFC	CP2332T-4	2,534	SD	24.56	308	89.5	460	12.9	D	1
	900	256T	TEFC	ECP2332T	3,274	SD	25.07	354	91.7	230/460	14.2	A	1
		256T	TEFC	ECP2332T-4	3,274	SD	25.07	300	91.7	460	14.2	A	1
		284T	TEFC	ECP2402T-4	5,157	SD	27.44	468	90.2	460	13.7	B	1

(a) See notes on inside back flap.

All ratings are 1.15 service factor at 40°C ambient. All ratings meet 50°C ambient at 1.00 service factor and weatherproof intent of IEEE 45 and USCG 259 marine duty (below deck).

Custom TEFC motors available through 2250 Hp; Open and WPII motors through 15000 Hp. Contact your Baldor•Reliance Sales Representative.

FOR OTHER 208-230/460 VOLT REQUIREMENTS, PLEASE SEE DIRTY DUTY MOTORS ON PAGE 84.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Totally Enclosed, 460 & 230/460 Volts, Foot Mounted

Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)	
15	3600	215T	TEFC	CP3773T-4	2,197	SD	19.32	226	90.2	460	17	D	1	
		254T	TEFC	CP2394T-4	2,245	SD	24.56	291	90.2	460	17.6	D	1	
		254T	TEFC	ECP2294T	2,576	SD	24.69	350	91.7	230/460	17.2	A	1	
		254T	TEFC	ECP2394T-4	2,576	SD	25.07	239	91.7	460	17.2	A	1	
	1800	254T	TEFC	CP2333T	2,087	SD	24.56	299	91	208-230/460	19.5	D	1	
		254T	TEFC	CP2333T-4	2,087	SD	21.94	297	91	460	18.5	D	1	
		254T	TEFC	ECP2333T	2,420	SD	25.07	255	92.4	230/460	18.5	A	1	
		254T	TEFC	ECP2333T-4	2,420	SD	25.07	255	92.4	460	18.5	A	1	
	1200	284T	TEFC	CP4100T	3,563	SD	27.56	383	90.2	230/460	21	D	1, 30	
		284T	TEFC	CP4100T-4	3,563	SD	26.03	386	90.2	460	21	D	1	
		284T	TEFC	ECP4100T	3,753	SD	27.44	439	92.4	230/460	18.7	A	1	
		284T	TEFC	ECP4100T-4	3,753	SD	27.44	441	92.4	460	18.7	A	1	
900	286T	TEFC	ECP2395T-4	6,884	SD	27.44	442	90.2	460	20	B	1		
20	3600	256T	TEFC	CP4106T-4	2,276	SD	24.56	298	90.2	460	23.8	D	1	
		256T	TEFC	ECP4106T	3,005	SD	24.69	265	92.4	230/460	22	A	1	
		256T	TEFC	ECP4106T-4	3,005	SD	25.07	265	92.4	460	23	A	1	
	1800	256T	TEFC	CP2334T	2,324	SD	24.56	316	91	230/460	25.4	D	1	
		256T	TEFC	CP2334T-4	2,324	SD	24.56	310	91	460	25.4	D	1	
		256T	TEFC	ECP2334T	2,596	SD	25.07	303	93	230/460	24	A	1	
	1200	256T	TEFC	ECP2334T-4	2,596	SD	24.69	303	93	460	24	A	1	
		286T	TEFC	CP4102T	4,153	SD	27.44	425	90.2	230/460	27	D	1	
		286T	TEFC	CP4102T-4	4,153	SD	27.44	414	90.2	460	27	D	1	
	900	286T	TEFC	ECP4102T	5,100	SD	27.44	453	92.4	230/460	24.8	A	1	
		286T	TEFC	ECP4102T-4	5,100	SD	27.44	456	92.4	460	24.8	A	1	
		324T	TEFC	ECP4112T-4	7,848	SD	30.16	608	91	460	28	B	1	
284TS		TEFC	CP4107T-4	2,850	SD	26.06	426	91	460	29.7	D	1		
25	3600	284TS	TEFC	ECP4107T	3,611	SD	24.66	299	92.4	230/460	27	A	1	
		284TS	TEFC	ECP4107T-4	3,611	SD	26.06	449	93	460	28.1	A	1	
		284T	TEFC	CP4103T	2,820	SD	27.44	411	92.4	230/460	31	D	1	
	1800	284T	TEFC	CP4103T-4	2,820	SD	27.44	414	92.4	460	29	D	1	
		284T	TEFC	ECP4103T	3,396	SD	27.93	395	93.6	230/460	30	A	1	
		284T	TEFC	ECP4103T-4	3,396	SD	27.93	395	93.6	460	30	A	1	
	1200	324T	TEFC	CP4111T	5,066	SD	30.44	575	91.7	230/460	33	D	1	
		324T	TEFC	CP4111T-4	5,066	SD	30.44	587	91.7	460	33	D	1	
		324T	TEFC	ECP4111T	5,329	SD	30.16	611	93	230/460	32	A	1	
	30	3600	324T	TEFC	ECP4111T-4	5,329	SD	30.16	648	93	460	32	A	1
			286TS	TEFC	CP4108T-4	3,117	SD	24.66	411	91	460	34	D	1
			286TS	TEFC	ECP4108T	4,402	SD	26.06	450	93	230/460	33.9	A	1
1800		286TS	TEFC	ECP4108T-4	4,402	SD	26.06	457	93	460	33.9	A	1	
		286T	TEFC	CP4104T	3,383	SD	27.44	427	92.4	230/460	37	D	1	
		286T	TEFC	CP4104T-4	3,383	SD	27.44	417	92.4	460	36	D	1	
1200		286T	TEFC	ECP4104T	4,033	SD	27.93	459	94.1	230/460	36	A	1	
		286T	TEFC	ECP4104T-4	4,033	SD	27.93	385	94.1	460	36	A	1	
		326T	TEFC	CP4117T	5,374	SD	30.44	608	91.7	230/460	38.9	D	1	
		326T	TEFC	CP4117T-4	5,374	SD	30.44	565	91.7	460	39	D	1	
		326T	TEFC	ECP4117T	6,870	SD	30.16	712	93	230/460	39	A	1	
		326T	TEFC	ECP4117T-4	6,870	SD	30.16	695	93	460	39	A	1	

(a) See notes on inside back.

All ratings are 1.15 service factor at 40°C ambient. All ratings meet 50°C ambient at 1.00 service factor and weatherproof intent of IEEE 45 and USCG 259 marine duty (below deck).

Custom TEFC motors available through 2250 Hp; Open and WPII motors through 15000 Hp. Contact your Baldor•Reliance Sales Representative.

FOR OTHER 208-230/460 VOLT REQUIREMENTS, PLEASE SEE DIRTY DUTY MOTORS ON PAGE 84.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Totally Enclosed, 460 & 230/460 Volts, Foot Mounted

Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status ^(a)	Notes ^(a)	
40	3600	324TS	TEFC	CP4109T-4	4,511	SD	28.94	587	91.7	460	45	D	1	
		324TS	TEFC	ECP4109T	6,048	SD	28.66	528	93.6	230/460	45	A	1	
		324TS	TEFC	ECP4109T-4	6,048	SD	28.66	608	93.6	460	47	A	1	
	1800	324T	TEFC	CP4110T	4,501	SD	30.44	628	93	230/460	49.5	D	1	
		324T	TEFC	CP4110T-4	4,501	SD	30.44	617	93	460	47	D	1	
		324T	TEFC	ECP4110T	5,276	SD	30.16	647	94.5	230/460	46	A	1	
	1200	324T	TEFC	ECP4110T-4	5,276	SD	30.16	659	94.5	460	46	A	1	
		364T	TEFC	CP4308T	7,439	SD	33.44	817	93	230/460	49.4	D	1	
		364T	TEFC	ECP4308T	8,562	SD	33.44	845	94.1	230/460	49.4	A	1	
	50	3600	326TS	TEFC	ECP4114T	6,338	SD	28.66	587	94.1	230/460	56	A	1
326TS			TEFC	ECP4114T-4	6,338	SD	28.66	647	94.1	460	56	A	1	
1800		326T	TEFC	CP4115T	5,313	SD	30.44	634	93	230/460	63.2	D	1	
		326T	TEFC	CP4115T-4	5,313	SD	30.44	628	93	460	60	D	1	
		326T	TEFC	ECP4115T	6,193	SD	30.16	732	94.5	230/460	57	A	1	
1200		326T	TEFC	ECP4115T-4	6,193	SD	30.16	655	94.5	460	57	A	1	
		365T	TEFC	CP4312T	7,923	SD	32.84	820	93	230/460	61	D	1	
		365T	TEFC	ECP4312T	9,120	SD	33.44	856	94.1	230/460	61	A	1	
60		3600	364TS	TEFC	ECP4310T	9,198	SD	31.31	748	95	230/460	65.1	A	1
			364TS	TEFC	ECP4310T-4	9,198	SD	31.31	901	95	460	65.1	A	1
	1800	364T	TEFC	CP4314T	7,191	SD	33.44	785	93.6	230/460	73.4	D	1	
		364T	TEFC	CP4314T-4	7,191	SD	33.44	793	93.6	460	71	D	1	
		364T	TEFC	ECP4314T	8,301	SD	33.44	900	95	230/460	69	A	1	
	1200	364T	TEFC	ECP4314T-4	8,301	SD	33.44	905	95	460	68	A	1	
		404T	TEFC	CP4403T	11,065	SD	38.31	1173	93.6	230/460	70	D	1	
		404T	TEFC	ECP4403T	12,458	SD	38.31	1257	94.5	230/460	72	A	1	
	75	3600	365TS	TEFC	ECP4313T	10,282	SD	31.31	964	95	230/460	80.7	A	1
			365TS	TEFC	ECP4313T-4	10,282	SD	31.31	966	95	460	80.7	A	1
1800		365T	TEFC	CP4316T	8,643	SD	33.44	874	94.1	230/460	87	D	1	
		365T	TEFC	CP4316T-4	8,643	SD	33.44	815	94.1	460	86	D	1	
		365T	TEFC	ECP4316T	9,699	SD	33.44	857	95.4	230/460	85.9	A	1	
1200		365T	TEFC	ECP4316T-4	9,699	SD	33.44	938	95.4	460	85.9	A	1	
		405T	TEFC	CP4404T	13,175	SD	38.31	1218	93.6	230/460	88	D	1	
		405T	TEFC	ECP4404T	15,161	SD	38.31	1305	95	230/460	88	A	1	
100		3600	405TS	TEFC	ECP4402T	12,924	SD	35.31	1119	94.1	230/460	116	A	1
			405TS	TEFC	ECP4402T-4	12,924	SD	35.31	1266	95	460	110	A	1
	1800	405T	TEFC	CP4400T-4	9,904	SD	38.31	1258	94.5	460	113	D	1	
		405T	TEFC	ECP4400T-4	12,732	SD	38.31	1329	95.4	460	112	A	1	
		405TS	TEFC	ECP4400TS-4	12,732	SD	35.31	1292	95.4	460	112	A	1	
	1200	444T	TEFC	ECP4409T-4	16,676	SD	44.75	1765	95	460	115	A	1	
		3600	444TS	TEFC	ECP4412T	15,187	SD	40.98	1654	95	230/460	144	A	1
			444TS	TEFC	ECP4412T-4	15,187	SD	40.98	1712	95.4	460	137	A	1
	125	1800	444T	TEFC	ECP4410T-4	15,052	SD	44.75	1781	95.8	460	139	A	1
		1200	445T	TEFC	ECP4411T-4	18,839	SD	44.75	1884	95.4	460	143	A	1
3600		445TS	TEFC	ECP4413T-4	17,804	SD	40.98	1953	96.2	460	164	A	1	
150	1800	445T	TEFC	CP4406T-4	16,002	SD	44.75	1730	95	460	170	D	1	
		445T	TEFC	ECP4406T-4	17,633	SD	44.75	1946	96.2	460	165	A	1	
	1200	445T	TEFC	ECP44156T-4	21,240	SD	48.24	2006	95.8	460	170	A	1	
		447T	TEFC	ECP44156TR-4	22,322	SD	48.24	2048	96.2	460	173	A	1, 5	

^(a) See notes on inside back flap.

All ratings are 1.15 service factor at 40°C ambient. All ratings meet 50°C ambient at 1.00 service factor and weatherproof intent of IEEE 45 and USCG 259 marine duty (below deck).

Custom TEFC motors available through 2250 Hp; Open and WPII motors through 15000 Hp. Contact your Baldor•Reliance Sales Representative.

FOR OTHER 208-230/460 VOLT REQUIREMENTS, PLEASE SEE DIRTY DUTY MOTORS ON PAGE 84.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Totally Enclosed, 460 & 230/460 Volts, Foot Mounted

Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
200	3600	445TS	TEFC	ECP44202T-4	21,082	SD	44.48	1986	96.2	460	222	A	1
		447T	TEFC	CP44404T-4	19,475	SD	40.88	1841	95	460	220	D	1
		447TS	TEFC	ECP4416T-4	21,082	SD	44.48	2129	96.2	460	222	A	1
	1800	445T	TEFC	CP44204TR-4	20,780	SD	44.63	1961	95	460	225	D	1, 5
		447T	TEFC	ECP4407T-4	21,212	SD	48.24	2417	96.2	460	221	A	1, 27
		447T	TEFC	ECP4407TR-4	22,293	SD	48.24	2077	96.2	460	221	A	1, 5
		447TS	TEFC	ECP4407TS-4	21,518	SD	44.48	2358	96.2	460	221	A	1, 27
1200	449T	TEFC	ECP44206T-4	27,823	SD	53.24	2809	96.2	460	223	A	1, 27	
	449T	TEFC	ECP44206TR-4	28,904	SD	53.24	2848	96.2	460	223	A	1, 5	
250	3600	449TS	TEFC	ECP44252T-4	32,238	SD	49.48	2424	96.2	460	275	B	1, 27
		447T	TEFC	CP44254TR-4	25,365	SD	48.24	2363	95.4	460	278	D	1, 5
	1800	449T	TEFC	ECP4408T-4	26,918	SD	53.24	2745	96.2	460	272	B	1, 27
		449T	TEFC	ECP4408TR-4	27,999	SD	53.24	2764	96.2	460	272	B	1, 5
	1200	449T	TEFC	ECP44256T-4	38,815	SD	53.24	2973	96.2	460	283	B	1, 27
		449T	TEFC	ECP44256TR-4	39,896	SD	53.24	2999	96.2	460	283	B	1, 5
300	3600	449TS	TEFC	ECP44302T-4	47,117	SD	49.48	2626	96.2	460	326	B	1, 27
		449T	TEFC	ECP44304T-4	37,101	SD	53.24	2853	96.2	460	326	B	1, 27
	1800	449T	TEFC	ECP44304TR-4	38,183	SD	53.24	2925	96.2	460	326	B	1, 5
350	3600	449TS	TEFC	ECP44352T-4	56,554	SD	49.48	2848	96.2	460	375	B	1, 27
	1800	449T	TEFC	ECP44354T-4	44,520	SD	60.21	3041	96.2	460	392	B	1, 27
400	3600	449TS	TEFC	ECP44402T-4	66,165	SD	49.48	2845	96.2	460	435	B	1, 27
	1800	L449T	TEFC	ECP44404T-4	55,606	SD	60.21	3459	95.8	460	442	B	1, 27, 64

(a) See notes on inside back flap.

All ratings are 1.15 service factor at 40°C ambient. All ratings meet 50°C ambient at 1.00 service factor and weatherproof intent of IEEE 45 and USCG 259 marine duty (below deck).

Custom TEFC motors available through 2250 Hp; Open and WPII motors through 15000 Hp. Contact your Baldor•Reliance Sales Representative.

FOR OTHER 208-230/460 VOLT REQUIREMENTS, PLEASE SEE DIRTY DUTY MOTORS ON PAGE 84.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors