

**Standard-E & Super-E 1/2 thru 2 Hp**  
**Stainless Steel,**  
**Three Phase,**  
**Totally Enclosed,**  
**C-Face**

**NEMA 56C thru 145TC**

**Applications:** Food processing, packaging, outdoor and highly corrosive environments.

**Features:** All external surfaces 300 series stainless steel: motor frame, endplates, conduit box, shaft and base. Moisture resistant insulation system. Four condensate drains in each endplate. Endplate rabbets sealed and conduit box gasketed. Labyrinth seals each end. Especially effective in highly corrosive environments where paint or other finishes do not hold up. Super-E® motors have NEMA Premium® efficiency and 3 year warranty.



Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
<b>Foot Mounted</b>													
1/2	1800	56C	TENV	CSSWDM3538-5	1,178	WD	11.09	37	80	575	0.6	C	
3/4	1800	56C	TENV	CSSWDM3542-5	1,219	WD	11.09	44	82.5	575	0.9	C	
1	1800	56C	TENV	CSSWDM3546-5	1,252	WD	11.09	45	85.5	575	1.1	C	
		143TC	TENV	CESSWDM3546T-5	1,257	WD	11.09	42	87.5	575	1.1	C	
1 1/2	1800	145TC	TEFC	CESSWDM3554T-5	1,281	WD	13.42	45	87.5	575	1.6	A	
2	1800	145TC	TEFC	CESSWDM3558T-5	1,539	WD	15.67	62	88.5	575	2.2	A	

(a) See notes on inside back flap.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes