

**Single Phase,
ODP, C-Face**

1/6 thru 5 Hp

NEMA 56C thru 184TC

Applications: Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.



Features: Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
C-Face, Foot Mounted, No Drip Cover												
1/3	1800	56C	CL1301	325	K	10.10	23	60	115/230	3	C	30
1/2	3600	56C	CL1303	288	K	10.06	22	66	115/230	3.5	C	30
	1800	56C	CL1304	370	K	10.35	25	62	115/230	4.2	C	30
3/4	1800	56C	CL1307	424	K	12.06	34	68	115/230	5.1	C	30
1	1800	56C	CL1310	487	K	11.06	35	66	115/230	6.7	C	30
3	1800	184TC	CL1408TM	892	L1	15.00	78	78	115/230	16	C	
5	1800	184TC	CL1410TM	1,075	L1	16.50	88	82.5	230	23	C	1, 30
C-Face, Foot Mounted, Drip Cover												
5	1800	184TC	CL1430TM	1,075	L1	16.55	84	80	230	24	C	1, 30, 65
C-Face, Footless, Drip Cover												
1/6	1800	56C	KL1200	263	K	11.22	18	49	115/230	1.9	C	30
1/4	1800	56C	KL1203	268	K	11.22	20	55	115/230	2.5	C	30
1/3	3600	56C	KL1205	255	K	11.22	21	55	115/208-230	3	C	30
		56C	KL1205A	261	K	11.35	21	55	115/230	3	C	30
1/2	1800	56C	VL1301	308	K	11.22	22	60	115/230	3	C	30
	3600	56C	VL1303	280	K	11.22	21	66	115/230	3.5	C	30
	1800	56C	VL1304	339	K	11.47	24	62	115/230	4.2	C	30
3/4	1200	56C	VL1305	663	K	13.24	36	62	115/230	4.1	C	30
	3600	56C	VL1306	335	K	12.85	27	72	115/230	4.7	C	30
	1800	56C	VL1307	414	K	13.22	33	68	115/230	5.1	C	30
1	1200	56C	VL1308	743	K	13.24	43	68	115/230	5	C	30
	3600	56C	VL1309	352	K	12.72	32	65	115/230	7.5	C	30
	1800	56C	VL1310	451	K	12.24	34	66	115/230	6.7	C	30
1 1/2	3600	56C	VL1318	490	K	13.24	42	67	115/230	6.2	C	30
		56C	VL1313	487	K	12.73	32	77	115/230	6.4	C	30
	1800	56C	VL1319	576	K	13.24	42	68	115/230	9	C	30
2	145TC		VL1321T	652	L1	14.17	49	70	115/230	10.5	C	30
	3600	56C	VL1317	641	K	13.24	43	70	115/230	13	C	30
	1800	145TC	VL1322T	664	L1	14.18	47	75.5	115/230	10.2	C	65
3	3600	182TC	VL1406T	807	L1	15.18	59	75.5	115/230	13.6	C	30, 65
	1800	184TC	VL1408T	817	L1	16.55	76	78	115/230	16	C	30, 65

(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors