

Woodworking,  
Single Phase, TEFC

1 thru 3 Hp

NEMA 48Z thru 184YZ

Applications: Woodworking equipment such as table saws, planers, etc.



Features: Motor swivels on rod for belt tensioning. Shaft supplied with full key and keyway. Extra high breakdown torques for maximum cutting power. 1.00 Service Factor.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
1	3600	48Z	WWL3509	437	K	13.35	33	65	115/230	6.3	C	67
2	3600	145TYZ	WWL3515T	713	L1	13.56	53	70	115/230	12	C	20, 65
3	3600	184YZ	WWL3606	911	L1	14.89	71	72	230	15.5	C	

(a) See notes on inside back flap.

Pre-1952 NEMA,  
Single and  
Three Phase,  
Foot Mounted

1/2 thru 5 Hp

NEMA 66 thru 254

Applications: Applications requiring pre-1952 NEMA frame dimensions.



Features: Heavy-gauge seam-welded base, ball bearings, copper windings.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
<b>Single Phase, Totally Enclosed Fan Cooled</b>												
1/2	1800	66	L3576M	613	K	13.62	36	64	115/230	4	C	
3/4	1800	66	L3565M	729	K	13.62	38	66	115/230	5.3	C	
1	1800	66	L3566M	792	K	13.62	40	67	115/230	6.5	C	30
1 1/2	1800	66	L3567M	960	K	14.50	50	75.5	115/230	8	C	2, 65
<b>Three Phase, Totally Enclosed Fan Cooled</b>												
1/2	1800	66NA	M3564	591	K	13.62	30	72	208-230/460	1.1	C	30
3/4	1800	66NA	M3565	621	K	13.62	31	72	230/460	1.5	C	30
1	1800	66NA	M3566	652	K	13.62	33	75.5	208-230/460	1.8	C	
1 1/2	1800	66NA	M3567	684	K	13.62	37	78.5	208-230/460	2.5	C	
<b>Single Phase, Open Drip Proof</b>												
1	1800	203	L1413	1,118	L1	14.37	51	70	115/230	7	C	30
1 1/2	1800	204	L1414	1,307	L1	14.37	56	68	115/230	9.5	C	30
<b>Three Phase, Open Drip Proof</b>												
1	1800	203	M3233	968	L1	14.38	47	77	208-230/460	1.6	C	
1 1/2	1800	204	M3234	1,026	L1	14.38	49	81.5	208-230/460	2.4	C	
2	1800	224NA	M3324	1,381	L1	16.32	77	79	208-230/460	3.3	C	
3	1800	225NA	M3325	1,423	L1	16.32	81	80	208-230/460	4.5	C	
5	1800	254NA	M3326	1,735	L1	18.32	94	84	208-230/460	6.8	C	

(a) See notes on inside back flap.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes