

**Grain Dryer/  
Centrifugal Fan,  
Single and  
Three Phase,  
TEFC and ODP**

**5 thru 50 Hp**

**NEMA 184TZ thru 326TZ**

**Applications:** High pressure grain drying and storage for commercial and farm applications.

**Features:** Shaft length is 1" longer than NEMA standard. Screens to protect against entry of trash, snakes and rodents. Three phase ratings meet EPAct efficiencies.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
<b>Single Phase, Open Drip Proof</b>												
5	1800	184TZ	<b>GDL1605T</b>	1,431	L1	19.06	98	80	230	22.5	C	2, 20
7 1/2	1800	215TZ	<b>GDL1607T</b>	1,882	L1	22.57	161	82.5	230	32	C	1
10	1800	215TZ	<b>GDL1610T</b>	2,178	L1	22.85	164	84	230	40	C	2, 20
16	1800	256TZ	<b>GDL1615T</b>	3,240	L1	24.19	288	86.5	208-230	62	C	2, 20
<b>Three Phase, Open Drip Proof</b>												
5	1800	184TZ	<b>GDM3218T</b>	791	L1	16.00	69	87.5	208-230/460	6.9	C	
7 1/2	1800	213TZ	<b>GDM3311T</b>	1,123	L1	18.00	92	88.5	208-230/460	10	C	
10	1800	215TZ	<b>GDM3313T</b>	1,361	L1	17.32	129	89.5	208-230/460	13.4	C	
15	1800	254TZ	<b>GDM2513T</b>	1,675	L1	21.00	172	91	208-230/460	19	C	1
20	1800	254TZ	<b>GDM2515T</b>	2,206	L1	23.25	165	91.7	230/460	24	C	30
25	1800	284TZ	<b>GDM2531T</b>	2,710	L1	24.44	329	91.7	230/460	31	C	30
30	1800	284TZ	<b>GDM2535T</b>	3,152	L1	25.94	351	92.4	230/460	36	C	30
<b>Three Phase, Totally Enclosed Fan Cooled</b>												
3	1800	182TZ	<b>GDM3611T</b>	793	L1	16.14	59	84	208-230/460	4.1	C	1
5	1800	184TZ	<b>GDM3615T</b>	918	L1	17.55	77	85.5	208-230/460	6.6	C	1
7 1/2	1800	213TZ	<b>GDM3710T</b>	1,169	L1	18.90	115	89.5	208-230/460	10.1	C	1
10	1800	215TZ	<b>GDM3714T</b>	1,886	L1	20.03	139	89.5	208-230/460	13.5	C	1
15	1800	254TZ	<b>GDM2333T</b>	2,493	L1	22.07	231	89.5	208-230/460	18.9	C	1
20	1800	256TZ	<b>GDM2334T</b>	2,669	L1	23.83	322	91	230/460	25	C	1, 30
25	1800	284TZ	<b>GDM4103T</b>	3,798	L1	26.93	322	92.4	230/460	29	C	1, 30
30	1800	286TZ	<b>GDM4104T</b>	4,485	L1	26.93	322	92.4	230/460	36	C	1, 30
40	1800	324TZ	<b>GDM4110T</b>	5,956	L1	31.39	485	93	230/460	47	C	1
50	1800	326TZ	<b>GDM4115T</b>	6,169	L1	31.28	552	91	230/460	60	C	1, 30

(a) See notes on inside back flap.

■ Cast Iron Frame

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes