

# Fan and Blower, Split Phase and Capacitor Start

## Totally Enclosed, Resilient Base (Single & Two-Speed)



### Features:

- Thermal protection, as noted
- 1.0 Service Factor (except as noted)
- Heavy gauge steel constructions
- Split phase (except as noted)
- Ball bearings
- UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT. NO.	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/6	1725	115	48	NONE	HG178	5KH32EN79	*			\$225	F1	4.0	9.92	
	1725	115	48	AUTO	H291	5KH32EN72X	*			\$237	F1	4.0	9.92	
	1140	115	48	NONE	H233	5KH36PN109	*			\$312	F1	4.0	10.98	
1/4	1725	115	48	AUTO	H234	5KH39QN9105X	*	B501	48S17T2002	\$165	F1	5.1	9.92	
	1725	115	48	NONE	B1502	5KH39QN9105	*	B502	48S17T2003	\$158	F1	5.1	9.92	
	1725	115/230	48	NONE	C247	5KC32GN13	*			\$279	F1	5.4/2.7	9.92	2
	1725/1140	115	48	NONE	HG189	5KH36PN108	*			\$312	F1	4.2/2.7	10.98	
	1140	115/230	56	NONE	HG182	5KH49MN6060	*			\$359	F1	5.6/2.8	11.54	
1/3	1725	115	56	NONE	B1504	5KH35MN56	*	B504	56S17F5302	\$195	F1	5.9	10.93	
	1725	115	56	AUTO	H236	5KH35MN56X	*	B500	56S17F5305	\$202	F1	5.9	10.93	
	1725/1140	115	56	NONE	H190	5KH49MN3035	*			\$387	F1	5.7/3.2	11.54	
	1140	115	56	NONE	HG186	5KH46PN6059	*			\$413	F1	7.0	11.94	
1/2	1725	115	56	AUTO	B506	56S17F5303	*			\$277	F1	8.4	12.30	
	1725	115	56	NONE	B1507	5KH42GN0336	*	B507	56S17F5304	\$234	F1	8.0	11.11	19
	1725	115/230	56	AUTO	C289	5KC42GN0309X	*			\$377	F1	8.6/4.3	11.11	2,18
	1725/1140	115	56	NONE	HG191	5KH46PN3033	*			\$431	F1	8.0/4.2	11.94	
	1725/1140	230	56	NONE	H293	5KH46PN3034	*			\$442	F1	3.8/1.9	11.94	
	1140	115	56	NONE	HG188	5KH49UN6064	*			\$526	F1	9.0	13.07	
3/4	1725	115/230	56	AUTO	C806	5KC49PN0281X	*			\$438	F1	11.0/5.5	12.54	2,17
1	1725	115/230	56	AUTO	C292	5KC49TN0285X	*			\$484	F1	13.2/6.6	13.07	2

## Fan & Blower - Three Phase

### TEAO, Resilient Base

**Applications:** Designed for applications like commercial fans and blowers, direct and belt drive air handlers and exhaust fans.

### Features:

- Ball bearings
- 1.0 Service Factor
- .62" extended thru-bolts
- UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	230/460	48	K281	5K32GN48	*	\$262	F1	1.4/0.7	8.94	
	1200	230/460	56	K282	5K35MN294	*	\$377	F1	1.4/0.7	9.89	
1/3	1800	230/460	48	K283	5K33KN52	*	\$294	F1	1.5/0.8	9.19	
1/2	1800	208-230/460	56	K284	5K42HN4128	*	\$330	F1	2.3-2.2/1.1	10.05	
	1200	208-230/460	56	K285	5K49MN6080	*	\$442	F1	2.6-2.6/1.3	10.48	
	1200	208-230/460	56	K541	5K49MN6081	*	\$478	F1	2.6-2.6/1.3	11.54	
3/4	1800	208-230/460	56	K286	5K49KN4142	*	\$356	F1	3.3-3.0/1.5	10.48	
1	1800	208-230/460	56	K525	5K49MN4114	*	\$374	F1	3.6-3.8/1.9	10.48	