

Globetrotter® IEC (Metric) Frame, Three Phase

Totally Enclosed, B3 Mounting, Rigid Base



Applications: For use on fans, pumps, compressors, conveyors, and other equipment requiring IEC dimensions and electrical standards. The Globetrotter is not only designed to International standards but meets NEMA performance and efficiency standards making it suitable for requirements worldwide.

Features:

- Aluminum (63-90 frame) or Cast Iron (180-250 frame) frame construction
- Nameplated 60/50 hertz at same HP/KW
- Max Guard® Class F Insulation, Class B rise @ rated KW
- IP55 weatherproof enclosure
- Rotatable/Removable Base (63/90 frame)
- Wye Start-Delta Run on 160 Frame and larger
- 10:1 Variable Torque, Constant Torque speed range as noted
- Meets EFF2 European, EPAct and NRCan Canadian efficiencies, as noted
- Top Mounted/Oversized gasketed terminal box
- Meets IEEE45, IEC60092 & USCG
- CFR46 Marine Duty (63-90 frame "Below Deck")
- 1.15 Service Factor on 60 Hz sine wave, 1.0 SF or VFD
- IEC Design "N" with NEMA "B" Torques
- Terminal Blocks, Stud Type, Zero Creepage
- Kits or MOD Central for B3/B5 or B3/B14 mounting
- Meets IEC 34 electrical standards
- Meets IEC 72 dimensions and tolerances
- CE Marked
- 1 Year Warranty



**CONSULT
MARATHON ELECTRIC
FOR SPECIAL IEC
MOTORS**

Multiplier Symbol F4

Suitable for use on VFD per guidelines on page 17.

| HP/ KW | RPM 60/50 HZ | 60 HZ VOLTS | 50 HZ VOLTS | IEC FRAME | CAT. NO. | MODEL NO. | STOCK | CT SPEED RANGE† | LIST PRICE | NOM. EFF. | 60 HZ F.L. AMPS | APPROX. WGHT. LBS. | IEC "L" DIM. (MM) | FOOT NOTES | B5/FF FLANGE |
|------------------|-----------------|----------------|----------------|--------------|-------------|--------------|-------|--------------------|---------------|--------------|--------------------|--------------------------|----------------------|---------------|-----------------|
| 1/4-.18 | 3600/3000 | 230/460 | 200/400 | 63 | R300 | 63T34FH5301 | * | 20:1 | \$175 | 72.0 | 0.8/0.4 | 11 | 217 | DS | A569 |
| | 3600/3000 | 575 | 480 | 63 | R400 | 63T34FH5303 | * | 20:1 | \$175 | 72.0 | 0.3 | 11 | 217 | d,DS | A569 |
| | 1800/1500 | 230/460 | 200/400 | 63 | R301 | 63T17FH5326 | * | 20:1 | \$182 | 68.0 | 1.0/0.5 | 12 | 217 | DS | A569 |
| | 1800/1500 | 575 | 480 | 63 | R401 | 63T17FH5327 | * | 20:1 | \$182 | 68.0 | 0.4 | 12 | 217 | DS | A569 |
| | 1200/1000 | 230/460 | 200/400 | 71 | R302 | 71T11FH5376 | * | 20:1 | \$311 | 64.0 | 1.2/0.6 | 13 | 240 | DS | A570 |
| 1/3-.25 | 3600/3000 | 230/460 | 200/400 | 63 | R303 | 63T34FH5302 | * | 20:1 | \$205 | 72.0 | 1.1/.55 | 12 | 217 | DS | A569 |
| | 1800/1500 | 230/460 | 200/400 | 71 | R304 | 71T17FH5326 | * | 20:1 | \$213 | 68.0 | 1.4/.7 | 14 | 240 | DS | A570 |
| | 1800/1500 | 575 | 480 | 71 | R404 | 71T17FH5330 | * | 20:1 | \$213 | 68.0 | 0.6 | 14 | 240 | d,DS | A570 |
| | 1200/1000 | 230/460 | 200/400 | 80 | R305 | 80T11FH5376 | * | 20:1 | \$334 | 70.0 | 1.3/.65 | 20 | 282 | DS | A571 |
| 1/2-.37 | 3600/3000 | 230/460 | 200/400 | 71 | R306 | 71T34FH5301 | * | 20:1 | \$218 | 74.0 | 1.6/.8 | 14 | 240 | DS | A570 |
| | 1800/1500 | 230/460 | 200/400 | 71 | R307 | 71T17FH5327 | * | 20:1 | \$222 | 74.0 | 1.8/.9 | 15 | 240 | DS | A570 |
| | 1800/1500 | 575 | 480 | 71 | R407 | 71T17FH5331 | * | 20:1 | \$222 | 74.0 | 0.7 | 16 | 240 | DS | A570 |
| | 1200/1000 | 230/460 | 200/400 | 80 | R308 | 80T11FH5377 | * | 20:1 | \$348 | 72.0 | 1.9/.95 | 22 | 282 | DS | A571 |
| 3/4-.55 | 3600/3000 | 230/460 | 200/400 | 71 | R309 | 71T34FH5302 | * | 20:1 | \$229 | 74.0 | 2.4/1.2 | 16 | 240 | DS | A570 |
| | 3600/3000 | 575 | 480 | 71 | R409 | 71T34FH5304 | * | 20:1 | \$229 | 74.0 | 0.9 | 16 | 240 | DS | A570 |
| | 1800/1500 | 230/460 | 200/400 | 80 | R310 | 80T17FH5326 | * | 20:1 | \$241 | 74.0 | 2.5/1.25 | 21 | 282 | DS | A571 |
| | 1800/1500 | 575 | 480 | 80 | R410 | 80T17FH5330 | * | 20:1 | \$241 | 74.0 | 1.0 | 22 | 282 | d,DS | A571 |
| | 1200/1000 | 230/460 | 200/400 | 80 | R311 | 80T11FH5378 | * | 20:1 | \$374 | 72.0 | 2.7/1.35 | 25 | 282 | DS | A571 |
| 1-.75 | 3600/3000 | 230/460 | 200/400 | 80 | R312 | 80T34FH5301 | * | 20:1 | \$260 | 75.5 | 2.8/1.4 | 24 | 282 | DS | A571 |
| | 3600/3000 | 575 | 480 | 80 | R412 | 80T34FH5305 | * | 20:1 | \$260 | 75.5 | 1.1 | 24 | 282 | DS | A571 |
| | 1800/1500 | 230/460 | 200/400 | 80 | R313 | 80T17FH5327 | * | 20:1 | \$264 | 80.0 | 3.2/1.6 | 29 | 282 | DS | A571 |
| | 1800/1500 | 575 | 480 | 80 | R413 | 80T17FH5331 | * | 20:1 | \$264 | 80.0 | 1.4 | 28 | 282 | d,DS | A571 |
| | 1200/1000 | 230/460 | 200/400 | 90S | R314 | 90ST11FH5376 | * | 20:1 | \$389 | 80.0 | 3.3/1.7 | 33 | 326 | DS | A572 |
| 1 1/2-1.1 | 3600/3000 | 230/460 | 200/400 | 80 | R315 | 80T34FH5302 | * | 20:1 | \$287 | 84.0 | 4.0/2.0 | 30 | 282 | DS | A571 |
| | 3600/3000 | 575 | 480 | 80 | R415 | 80T34FH5303 | * | 20:1 | \$287 | 84.0 | 1.6 | 29 | 282 | DS | A571 |
| | 1800/1500 | 230/460 | 200/400 | 90S | R316 | 90ST17FH5326 | * | 20:1 | \$295 | 85.5 | 4.6/2.3 | 40 | 326 | DS | A572 |
| | 1800/1500 | 575 | 480 | 90S | R416 | 90ST17FH5327 | * | 20:1 | \$295 | 85.5 | 1.8 | 39 | 326 | DS | A572 |
| 2-1.5 | 3600/3000 | 230/460 | 200/400 | 90S | R318 | 90ST34FH5301 | * | 20:1 | \$307 | 85.5 | 5.2/2.6 | 36 | 326 | DS | A572 |
| | 3600/3000 | 575 | 480 | 90S | R418 | 90ST34FH5302 | * | 20:1 | \$307 | 85.5 | 2.1 | 36 | 326 | DS | A572 |
| | 1800/1500 | 230/460 | 200/400 | 90L | R319 | 90LT17FH5326 | * | 20:1 | \$317 | 84.0 | 5.8/2.9 | 41 | 326 | DS | A572 |
| | 1800/1500 | 575 | 480 | 90L | R419 | 90LT17FH5327 | * | 20:1 | \$317 | 84.0 | 2.4 | 39 | 326 | DS | A572 |
| | 1200/1000 | 230/460 | 200/400 | 100L | R320 | 100LTFC4576 | | 2:1 | \$495 | 86.5 | 7.6/3.8 | 82 | 380 | DS | A573 |

Blue shaded areas are Cast Iron Frames

† Requires nameplate modification Catalog numbers (Cat No.) highlighted in bold blue have efficiency levels that meet or exceed U.S. EPAct and/or NRCan Canadian standards.

Continued on next page.

Globetrotter® IEC (Metric) Frame, Three Phase

Totally Enclosed, B3 Mounting, Rigid Base

Multiplier Symbol F4

GLOBETROTTER® - IEC

| HP/ KW | RPM 60/50 HZ | 60 HZ VOLTS | 50 HZ VOLTS | IEC FRAME | CAT. NO. | MODEL NO. | STOCK | CT SPEED RANGE† | LIST PRICE | NOM. EFF. | 60 HZ F.L. AMPS | APPROX. WGHT. LBS. | IEC "L" DIM. (MM) | FOOT NOTES | B5/FF FLANGE |
|------------------|-----------------|----------------|----------------|--------------|-------------|--------------|-------|--------------------|---------------|--------------|--------------------|--------------------------|----------------------|---------------|-----------------|
| 3-2.2 | 3600/3000 | 230/460 | 200/400 | 90L | R321 | 90LT34FH5301 | ★ | 20:1 | \$442 | 86.5 | 7.2/3.6 | 42 | 326 | DS | A572 |
| | 3600/3000 | 575 | 480 | 90L | R421 | 90LT34FH5302 | ★ | 20:1 | \$442 | 86.5 | 2.9 | 42 | 326 | DS,d | A572 |
| | 1800/1500 | 230/460 | 200/400 | 100L | R322 | 100LTFC4526 | ★ | 20:1 | \$480 | 88.5 | 9.0/4.5 | 84 | 380 | DS | A573 |
| | 1200/1000 | 230/460 | 200/400 | 112M | R323 | 112MTFC4576 | ★ | 20:1 | \$699 | 87.5 | 9.0/4.5 | 100 | 400 | DS | A573 |
| 4-3 | 3600/3000 | 230/460 | 200/400 | 100L | R351 | 100LTFC4501 | ★ | 20:1 | \$512 | 87.5 | 9.2/4.6 | 71 | 380 | DS | A573 |
| | 1800/1500 | 230/460 | 200/400 | 100L | R352 | 100LTFC4536 | ★ | 20:1 | \$521 | 88.5 | 11.0/5.5 | 84 | 380 | DS | A573 |
| | 1200/1000 | 230/460 | 200/400 | 132S | R353 | 132STFC4586 | ★ | 2:1 | \$846 | 87.5 | 13/6.5 | 154 | 475 | DS | A575 |
| 5 1/2-4 | 3600/3000 | 230/460 | 200/400 | 112M | R324 | 112MTFC4511 | ★ | 20:1 | \$659 | 87.5 | 12.8/6.4 | 104 | 400 | DS | A574 |
| | 1800/1500 | 230/460 | 200/400 | 112M | R325 | 112MTFC4536 | ★ | 20:1 | \$635 | 87.5 | 14.0/7.0 | 104 | 400 | DS | A574 |
| | 1200/1000 | 230/460 | 200/400 | 132M | R326 | 132MTFC4586 | ★ | 2:1 | \$977 | 87.5 | 17/8.5 | 176 | 475 | DS | A575 |
| 7 1/2-5.5 | 3600/3000 | 230/460 | 200/400 | 132S | R327 | 132STFC4501 | ★ | 20:1 | \$826 | 90.2 | 17.6/8.8 | 152 | 475 | DS | A575 |
| | 1800/1500 | 230/460 | 200/400 | 132S | R328 | 132STFC4526 | ★ | 20:1 | \$826 | 90.2 | 19.6/9.8 | 150 | 475 | DS | A575 |
| | 1200/1000 | 230/460 | 200/400 | 132M | R329 | 132MTFC4587 | ★ | 2:1 | \$1,175 | 89.5 | 23.4/11.7 | 180 | 475 | DS | A575 |
| 10-7.5 | 3600/3000 | 230/460 | 200/400 | 132S | R330 | 132STFC4502 | ★ | 20:1 | \$884 | 89.5 | 23.2/11.6 | 163 | 475 | DS | A575 |
| | 1800/1500 | 230/460 | 200/400 | 132M | R331 | 132MTFC4536 | ★ | 2:1 | \$980 | 91.0 | 26/13 | 174 | 475 | DS | A575 |
| | 1200/1000 | 230/460 | 200/400 | 160M | R332 | 160MTFC4586 | ★ | 2:1 | \$1,524 | 89.5 | 28/14 | 251 | 600 | YD,DS | A576 |
| 15-11 | 3600/3000 | 230/460 | 200/400 | 160M | R333 | 160MTFC4511 | ★ | 2:1 | \$1,432 | 91.7 | 35.2/17.6 | 260 | 600 | YD,DS | A576 |
| | 1800/1500 | 230/460 | 200/400 | 160M | R334 | 160MTFC4536 | ★ | 10:1 | \$1,432 | 91.0 | 37.8/18.9 | 264 | 600 | YD,DS | A576 |
| | 1200/1000 | 230/460 | 200/400 | 160L | R335 | 160LTFC4588 | ★ | 2:1 | \$1,956 | 90.2 | 38.8/19.4 | 330 | 600 | YD,DS | A576 |
| 20-15 | 3600/3000 | 230/460 | 200/400 | 160M | R336 | 160MTFC4512 | ★ | 10:1 | \$1,680 | 91.7 | 46.8/23.4 | 269 | 600 | YD,DS | A576 |
| | 1800/1500 | 230/460 | 200/400 | 160L | R337 | 160LTFC4538 | ★ | 2:1 | \$1,771 | 91.0 | 47/23.5 | 311 | 600 | YD,DS | A576 |
| | 1200/1000 | 230/460 | 200/400 | 180L | R338 | 180LTFC4588 | ★ | 2:1 | \$2,743 | 90.2 | 54/27 | 385 | 710 | YD,DS | A577 |
| 25-18.5 | 3600/3000 | 230/460 | 200/400 | 160L | R339 | 160LTFC4513 | ★ | 2:1 | \$2,045 | 91.7 | 57.6/28.8 | 319 | 645 | YD,DS | A576 |
| | 1800/1500 | 230/460 | 200/400 | 180M | R340 | 180MTFC4536 | ★ | 20:1 | \$2,251 | 92.4 | 59.2/29.6 | 381 | 670 | YD,DS | A577 |
| | 1200/1000 | 230/460 | 200/400 | 200L | R341 | 200LTFC4588 | ★ | 2:1 | \$3,440 | 91.7 | 63/31.5 | 467 | 775 | YD,DS | A578 |
| 30-22 | 3600/3000 | 230/460 | 200/400 | 180M | R342 | 180MTFC4511 | ★ | 2:1 | \$2,430 | 92.4 | 68.8/34.4 | 355 | 670 | YD,DS | A577 |
| | 1800/1500 | 230/460 | 200/400 | 180L | R343 | 180LTFC4538 | ★ | 20:1 | \$2,530 | 92.4 | 69.2/34.6 | 427 | 710 | YD,DS | A577 |
| | 1200/1000 | 230/460 | 200/400 | 200L | R344 | 200LTFC4589 | ★ | 2:1 | \$3,897 | 91.7 | 76/38 | 467 | 775 | YD,DS | A578 |
| 40-30 | 3600/3000 | 230/460 | 200/400 | 200L | R345 | 200LTFC4511 | ★ | 20:1 | \$3,460 | 92.4 | 89.6/44.8 | 522 | 775 | YD,DS | A578 |
| | 1800/1500 | 230/460 | 200/400 | 200L | R346 | 200LTFC4538 | ★ | 2:1 | \$3,725 | 94.1 | 95/47.5 | 531 | 775 | YD,DS | A578 |
| | 1200/1000 | 230/460 | 200/400 | 225M | R347 | 225MTFC4586 | ★ | 2:1 | \$5,855 | 93.0 | 100/50 | 633 | 845 | YD,DS | A579 |
| 50-37 | 3600/3000 | 230/460 | 200/400 | 200L | R348 | 200LTFC4513 | ★ | 10:1 | \$4,538 | 92.4 | 111.4/55.7 | 546 | 775 | YD,DS | A578 |
| | 1800/1500 | 230/460 | 200/400 | 225S | R349 | 225STFC4526 | ★ | 10:1 | \$5,168 | 93.6 | 117.6/58.8 | 632 | 845 | YD,DS | A579 |
| | 1200/1000 | 230/460 | 200/400 | 250M | R350 | 250MTFC4586 | ★ | 2:1 | \$8,207 | 93.0 | 125/62.5 | 655 | 930 | YD,DS | NA |

Blue shaded areas are Cast Iron Frames

† Requires nameplate modification

Catalog numbers (Cat No.) highlighted in bold blue have efficiency levels that meet or exceed U.S. EPCa and/or NRCa Canadian standards.

Globetrotter® IEC (Metric) Frame, Three Phase

Totally Enclosed, Flange/Base Mounting

Multiplier Symbol F4

B3/B5 "FF"

| HP/ KW | RPM 60/50 HZ | 60 HZ VOLTS | 50 HZ VOLTS | IEC FRAME | CAT. NO. | MODEL NO. | STOCK | CT SPEED RANGE† | LIST PRICE | NOM. EFF. | 60 HZ F.L. AMPS | APPROX. WGHT. LBS. | IEC "L" DIM. (MM) | FOOT NOTES |
|------------------|-----------------|----------------|----------------|--------------|-------------|--------------|-------|--------------------|---------------|--------------|--------------------|--------------------------|----------------------|---------------|
| 1/4-.18 | 3600/3000 | 230/460 | 200/400 | 63D | R380 | 63T34FH5501 | ★ | 20:1 | \$201 | 72.0 | 0.8/0.4 | 10 | 217 | DS |
| | 1800/1500 | 230/460 | 200/400 | 63D | R381 | 63T17FH5502 | ★ | 20:1 | \$208 | 68.0 | 1.0/0.5 | 11 | 217 | DS |
| | 1200/1000 | 230/460 | 200/400 | 71D | R382 | 71T11FH5503 | ★ | 20:1 | \$357 | 64.0 | 1.2/0.6 | 12 | 240 | DS |
| 1/3-.25 | 3600/3000 | 230/460 | 200/400 | 63D | R383 | 63T34FH5504 | ★ | 20:1 | \$233 | 72.0 | 1.1/1.55 | 11 | 217 | DS |
| | 1800/1500 | 230/460 | 200/400 | 71D | R384 | 71T17FH5505 | ★ | 20:1 | \$240 | 68.0 | 1.4/1.7 | 13 | 240 | DS |
| | 1200/1000 | 230/460 | 200/400 | 80D | R385 | 80T11FH5506 | ★ | 20:1 | \$384 | 70.0 | 1.3/1.65 | 17 | 282 | DS |
| 1/2-.37 | 3600/3000 | 230/460 | 200/400 | 71D | R386 | 71T34FH5507 | ★ | 20:1 | \$239 | 74.0 | 1.6/1.8 | 13 | 240 | DS |
| | 1800/1500 | 230/460 | 200/400 | 71D | R387 | 71T17FH5508 | ★ | 20:1 | \$247 | 74.0 | 1.8/1.9 | 14 | 282 | DS |
| | 1200/1000 | 230/460 | 200/400 | 80D | R388 | 80T11FH5509 | ★ | 20:1 | \$399 | 72.0 | 1.9/1.95 | 19 | 282 | DS |
| 3/4-.55 | 3600/3000 | 230/460 | 200/400 | 71D | R389 | 71T34FH5510 | ★ | 20:1 | \$253 | 74.0 | 2.4/1.2 | 15 | 282 | DS |
| | 1800/1500 | 230/460 | 200/400 | 80D | R390 | 80T17FH5511 | ★ | 20:1 | \$269 | 74.0 | 2.5/1.25 | 18 | 282 | DS |
| | 1200/1000 | 230/460 | 200/400 | 80D | R391 | 80T11FH5512 | ★ | 20:1 | \$423 | 72.0 | 2.7/1.35 | 22 | 320 | DS |
| 1-.75 | 3600/3000 | 230/460 | 200/400 | 80D | R392 | 80T34FH5513 | ★ | 20:1 | \$278 | 75.5 | 2.8/1.4 | 21 | 282 | DS |
| | 1800/1500 | 230/460 | 200/400 | 80D | R393 | 80T17FH5514 | ★ | 20:1 | \$291 | 80.0 | 3.2/1.6 | 26 | 282 | DS |
| | 1200/1000 | 230/460 | 200/400 | 90SD | R394 | 90ST11FH5515 | ★ | 20:1 | \$445 | 80.0 | 3.3/1.7 | 35 | 320 | DS |
| 1 1/2-1.1 | 3600/3000 | 230/460 | 200/400 | 80D | R395 | 80T34FH5516 | ★ | 20:1 | \$317 | 84.0 | 4.0/2.0 | 30 | 282 | DS |
| | 1800/1500 | 230/460 | 200/400 | 90SD | R396 | 90ST17FH5517 | ★ | 20:1 | \$322 | 85.5 | 4.6/2.3 | 37 | 320 | DS |
| 2-1.5 | 3600/3000 | 230/460 | 200/400 | 90SD | R397 | 90ST34FH5518 | ★ | 20:1 | \$351 | 85.5 | 5.2/2.6 | 33 | 320 | DS |
| | 1800/1500 | 230/460 | 200/400 | 90SD | R398 | 90LT17FH5519 | ★ | 20:1 | \$361 | 84.0 | 5.8/2.9 | 38 | 320 | DS |
| 3-2.2 | 3600/3000 | 230/460 | 200/400 | 90LD | R399 | 90LT34FH5520 | ★ | 20:1 | \$497 | 86.5 | 7.2/3.6 | 39 | 320 | DS |

B3/B14 "FT"

| HP/ KW | RPM 60/50 HZ | 60 HZ VOLTS | 50 HZ VOLTS | IEC FRAME | CAT. NO. | MODEL NO. | STOCK | CT SPEED RANGE† | LIST PRICE | NOM. EFF. | 60 HZ F.L. AMPS | APPROX. WGHT. LBS. | IEC "L" DIM. (MM) | FOOT NOTES |
|------------------|-----------------|----------------|----------------|--------------|-------------|--------------|-------|--------------------|---------------|--------------|--------------------|--------------------------|----------------------|---------------|
| 1/4-.18 | 3600/3000 | 230/460 | 200/400 | 63C | R360 | 63T34FH5401 | ★ | 20:1 | \$197 | 72.0 | 0.8/0.4 | 10 | 217 | DS |
| | 1800/1500 | 230/460 | 200/400 | 63C | R361 | 63T17FH5402 | ★ | 20:1 | \$205 | 68.0 | 1.0/0.5 | 11 | 217 | DS |
| | 1200/1000 | 230/460 | 200/400 | 71C | R362 | 71T11FH5403 | ★ | 20:1 | \$357 | 64.0 | 1.2/0.6 | 12 | 240 | DS |
| 1/3-.25 | 3600/3000 | 230/460 | 200/400 | 63C | R363 | 63T34FH5404 | ★ | 20:1 | \$231 | 72.0 | 1.1/1.55 | 11 | 217 | DS |
| | 1800/1500 | 230/460 | 200/400 | 71C | R364 | 71T17FH5405 | ★ | 20:1 | \$234 | 68.0 | 1.4/1.7 | 13 | 240 | DS |
| | 1200/1000 | 230/460 | 200/400 | 80C | R365 | 80T11FH5406 | ★ | 20:1 | \$384 | 70.0 | 1.3/1.65 | 17 | 282 | DS |
| 1/2-.37 | 3600/3000 | 230/460 | 200/400 | 71C | R366 | 71T34FH5407 | ★ | 20:1 | \$235 | 74.0 | 1.6/1.8 | 13 | 240 | DS |
| | 1800/1500 | 230/460 | 200/400 | 71C | R367 | 71T17FH5408 | ★ | 20:1 | \$244 | 74.0 | 1.8/1.9 | 14 | 282 | DS |
| | 1200/1000 | 230/460 | 200/400 | 80C | R368 | 80T11FH5409 | ★ | 20:1 | \$399 | 72.0 | 1.9/1.95 | 19 | 282 | DS |
| 3/4-.55 | 3600/3000 | 230/460 | 200/400 | 71C | R369 | 71T34FH5410 | ★ | 20:1 | \$247 | 74.0 | 2.4/1.2 | 15 | 282 | DS |
| | 1800/1500 | 230/460 | 200/400 | 80C | R370 | 80T17FH5411 | ★ | 20:1 | \$265 | 74.0 | 2.5/1.25 | 18 | 282 | DS |
| | 1200/1000 | 230/460 | 200/400 | 80C | R371 | 80T11FH5412 | ★ | 20:1 | \$423 | 72.0 | 2.7/1.35 | 22 | 320 | DS |
| 1-.75 | 3600/3000 | 230/460 | 200/400 | 80C | R372 | 80T34FH5413 | ★ | 20:1 | \$272 | 75.5 | 2.8/1.4 | 21 | 282 | DS |
| | 1800/1500 | 230/460 | 200/400 | 80C | R373 | 80T17FH5414 | ★ | 20:1 | \$284 | 80.0 | 3.2/1.6 | 26 | 282 | DS |
| | 1200/1000 | 230/460 | 200/400 | 90SC | R374 | 90ST11FH5415 | ★ | 20:1 | \$445 | 80.0 | 3.3/1.7 | 35 | 320 | DS |
| 1 1/2-1.1 | 3600/3000 | 230/460 | 200/400 | 80C | R375 | 80T34FH5416 | ★ | 20:1 | \$310 | 84.0 | 4.0/2.0 | 30 | 282 | DS |
| | 1800/1500 | 230/460 | 200/400 | 90SC | R376 | 90ST17FH5417 | ★ | 20:1 | \$316 | 85.5 | 4.6/2.3 | 37 | 320 | DS |
| 2-1.5 | 3600/3000 | 230/460 | 200/400 | 90SC | R377 | 90ST34FH5418 | ★ | 20:1 | \$344 | 85.5 | 5.2/2.6 | 33 | 320 | DS |
| | 1800/1500 | 230/460 | 200/400 | 90LC | R378 | 90LT17FH5419 | ★ | 20:1 | \$351 | 84.0 | 5.8/2.9 | 38 | 320 | DS |
| 3-2.2 | 3600/3000 | 230/460 | 200/400 | 90LC | R379 | 90LT34FH5420 | ★ | 20:1 | \$497 | 86.5 | 7.2/3.6 | 39 | 320 | DS |

† Requires nameplate modification Catalog numbers (Cat No.) highlighted in bold blue have efficiency levels that meet or exceed U.S. EPCa and/or NRCa Canadian standards.