



Pneumatic actuators

GEMÜ 9415

Plastic quarter turn actuator

Actuator size:	Size 0: 50 mm Size 1: 70 mm Size 2: 100 mm Size 3: 140 mm
Max. control pressure:	Size 0, 1, 2 = 6 bar, Size 3 = control function 1 (NC): 5 bar control function 3 (DA) 4 bar
Max. temp. of control medium:	60° C
Max. ambient temperature:	60° C
Control function:	Normally closed (NC), Normally open (NO), Double acting (DA)
Can be used for:	GEMÜ 410, 415, 450



Antriebsgröße 0

GEMÜ DR/SC

Metal quarter turn actuator

Actuator size:	8 Nm to 5500 Nm
Control pressure:	6 - 8 bar
Max. temp. of control medium:	80° C
Max. ambient temperature:	80° C
Control function:	Normally closed (NC), Normally open (NO) Double acting (DA) Mounting flange to DIN/ISO 5211, Interface for accessories to VDE/VDI 3845
Can be used for:	GEMÜ 451, 471, 481, D481, 491



GEMÜ ADA/ASR

Metal quarter turn actuator

Actuator size:	10 Nm to 5000 Nm
Control pressure:	6 - 8 bar
Max. temp. of control medium:	100° C
Max. ambient temperature:	80° C
Control function:	Normally closed (NC), Normally open (NO) Double acting (DA) Mounting flange to DIN/ISO 5211, Interface for accessories to VDE/VDI 3845
Can be used for:	GEMÜ 471, 481, D481, 491

