

# Condenser Fan/Heat Pump, PSC, Open Air Over


## Thru-Bolt, Shaft Up or Horizontal

HVAC

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
<b>1/3</b>	1075/1	208-230	48Y	X214	48A11O1525	★	\$129	F1	2.3-2.6	4 1/2	1/2 x 6	45
	1075/1	208-230	48Y	X088	48A11O2032	★	\$133	F1	3.0-3.0	4 3/4	1/2 x 6	
	1075/1	460	48Y	X424	48A11O2054	★	\$160	F1	1.4	4 3/4	1/2 x 6	36
	825/1	208-230	48Y	X086	48A8O2001	★	\$206	F1	2.4-2.4	5 1/4	1/2 x 6	
<b>1/2</b>	1625/1	460	48Y	X422	48A17O172	★	\$232	F1	1.7	5	1/2 x 6	36
	1625/1	575	48Y	X454	48A17O250	★	\$232	F1	1.35	5	1/2 x 6	36
	1075/1	208-230	48Y	X096	48A11O840	★	\$178	F1	4.2-4.2	5 1/2	1/2 x 6	
	1075/1	208-230	48Y	X089	48A11O2035	★	\$150	F1	4.2-4.2	5 1/4	1/2 x 6	d
	1075/1	208-230	48Y	X221	48A11O1526	★	\$157	F1	2.7-2.6	5	1/2 x 6	45
	1075/1	460	48Y	X400	48A11O2017	★	\$180	F1	1.8	5	1/2 x 6	35
	1075/1	575	48Y	X453	48A11O1771	★	\$180	F1	1.15	5	1/2 x 6	35
	825/1	208-230	48Y	X098	48A8O181	★	\$247	F1	3.3-3.3	5 1/2	1/2 x 6	
	825/1	208-230	56Z	X208	56A8O5	★	\$379	F1	3.4-3.4	8 5/8	5/8 x 6 w/key/flat	30
<b>3/4</b>	1075/2	208-230	48Y	X085	48A11O678	★	\$206	F1	5.1-5.1	5 1/2	1/2 x 6	
	1075/1	208-230	48Y	X298	48A11O2059	★	\$172	F1	4.0-4.2	5 1/4	1/2 x 6	d
	1075/1	208-230	48Y	X090	48A11O2007	★	\$194	F1	4.6-4.6	5 1/2	1/2 x 6	
	1075/1	460	48Y	X099	48A11O2016	★	\$207	F1	2.5	5 1/2	1/2 x 6	34
	1075/1	460	48YZ	X426	48A11O1375	★	\$251	F1	2.2	5 1/2	5/8 x 4.5 w/key	69
	1075/1	575	48Y	X455	48A11O1770	★	\$207	F1	1.7	5 1/2	1/2 x 6	35
<b>1</b>	1075/1	200-230/460	56Z	P190	5KCP49Z2N9617T	★	\$444	F1	6.7-6.8/3.4	9.0	5/8 x 4	

# Condenser Fan/Heat Pump, PSC, Open Air Over

## Thru-Bolt Mount, Shaft Down



**Applications:** Direct drive condenser fans mounted vertically, shaft down. These motors need to be mounted within the airflow of the fan for proper cooling.

- Features:**
- Frame and opposite shaft end bracket are enclosed for vertical shaft down mounting
  - Weather resistant reversing plug
  - 30" Long leads
  - Shaft slinger
  - 1-1/4" Extended thru-bolts on shaft end, except where noted
  - Automatic reset thermal protector
  - Ball Bearings
  - UL Recognized and CSA Certified
  - **Capacitor not included, see Accessories section**

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
<b>1/8</b>	825	208-230	48Y	X278	48A8O206	★	\$168	F1	0.9-0.9	4 1/4	1/2 X 4 3/4	37,44
<b>1/6</b>	1075	208-230	48Y	X440	48A11O2065	★	\$111	F1	1.0-0.9	4	1/2 X 6	
<b>1/5</b>	1075	208-230	48Y	X216	48A11O1097	★	\$124	F1	1.8-1.6	3 3/4	1/2 X 6	37,44,60
<b>1/4</b>	1075	208-230	48Y	X441	48A11O2062	★	\$136	F1	1.35-1.35	4 1/4	1/2 X 6	
<b>1/3</b>	1075	208-230	48Y	X442	48A11O2064	★	\$145	F1	2.0-1.95	4 3/4	1/2 X 6	
	1075	208-230	48Y	X297	48A11T509	★	\$131	F1	1.8-1.8	4 1/4	1/2 X 3 3/4	N,29,41,60
<b>1/2</b>	1075	208-230	48Y	X443	48A11O2063	★	\$161	F1	3.9-3.9	5 1/4	1/2 X 6	
<b>3/4</b>	1075	208-230	48Y	X444	48A11O1596	★	\$214	F1	4.3-4.7	5 1/2	1/2 X 6	