

Three Phase,
Open Drip Proof,
Foot Mounted

1/4 thru 450 Hp

NEMA 48 thru 449T

Applications: Pumps, compressors, fans, conveyors, machine tools and other general purpose three phase applications.

Features: Copper windings, ball bearings and heavy duty steel or cast iron frames. Mount in any position. EM Super-E® motors have NEMA Premium® efficiency and 3 year warranty.



General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
1/4	1800	48	M3003	257	K	9.13	18	64	230/460	0.7	C	30
	1200	48	M3004	416	K	9.13	19	68	230/460	0.7	C	30
		56	M3101	416	K	9.50	20	68	230/460	0.7	C	30
1/3	3600	48	M3006	261	K	9.13	19	72	230/460	0.7	C	30
	1800	48	M3007	276	K	9.13	20	68	230/460	0.8	C	30
		56	M3104	265	LS	9.50	20	68	230/460	0.8	C	30
	1200	48	M3008	407	K	9.13	21	70	230/460	0.9	C	30
		56	M3105	435	K	10.25	22	70	230/460	0.9	C	30
	3600	48	M3009	276	K	9.13	19	68	230/460	1	C	30
1/2	3600	56	M3107	276	K	9.50	19	68	230/460	1	C	30
		48	M3010	346	K	9.13	22	74	230/460	1	C	30
	1800	56	M3108	301	LS	9.50	22	74	230/460	1	C	30
		56	M3108A	409	K	10.25	23	74	230/460	1	C	30
	1200	48	M3011	450	K	9.38	23	72	230/460	1.2	C	30
		56	M3109	478	K	11.25	25	72	230/460	1.2	C	30
	900	56	M3160	727	K	12.07	33	66	208-230/460	1.3	C	
	3/4	3600	48	M3012	331	K	9.13	21	74	230/460	1.3	C
56			M3111	324	K	9.50	21	74	230/460	1.3	C	30
1800		48	M3013	385	K	9.75	25	75.5	208-230/460	1.5	C	
		56	M3112	336	LS	10.12	25	75.5	208-230/460	1.5	C	
1200		56	M3112A	447	K	11.25	26	74	230/460	1.5	C	30
		56	M3153	516	K	12.25	32	77	208-230/460	1.5	C	
1	3600	56	EM3115	483	K	11.06	32	84	230/460	1.4	C	1, 30
		56	M3115	375	K	9.50	23	75.5	230/460	1.8	C	30
	1800	56	M3116	379	LS	11.75	29	78.5	208-230/460	1.7	C	
		56	M3116A	497	K	11.75	27	78.5	208-230/460	2	C	
		143T	EM3116T	628	LS	11.62	36	85.5	230/460	1.5	A	1, 30
		143T	M3116T	381	LS	11.12	32	82.5	208-230/460	1.6	D	
	1200	182	M3203	628	L1	12.62	35	82.5	208-230/460	1.6	B	
		56/56H	M3156	549	K	11.75	37	75.5	208-230/460	1.7	C	36
		145T	EM3156T	641	L1	13.00	44	82.5	230/460	1.7	A	1, 30
		145T	M3156T	536	L1	11.62	39	80	208-230/460	1.9	D	
	900	182T	M3216T	913	L1	13.62	56	74	230/460	2.2	B	30
	1 1/2	3600	56	M3120	419	K	11.00	29	80	208-230/460	2.3	C
143T			EM3120T	539	L1	11.12	36	84	208-230/460	2.1	A	1
143T			M3120T	450	L1	11.12	34	82.5	208-230/460	2	D	
1800		56	M3154	438	LS	12.25	33	77	208-230/460	2.8	C	
		56	M3154A	496	K	11.07	33	78.5	208-230/460	2.4	C	
		145T	EM3154T	656	LS	13.00	44	86.5	230/460	2.1	A	1, 30
1200	145T	M3154T	446	LS	11.12	34	84	208-230/460	2.4	D		
	184	M3206	654	L1	12.62	38	84	208-230/460	2.4	B		
	56/56H	M3159	624	K	11.75	38	75.5	230/460	2.5	C	36	
	182T	EM3207T	750	L1	15.00	72	86.5	208-230/460	2.6	A	1	
900	182T	M3207T	630	L1	14.63	63	84	208-230/460	2.6	D	1, 30	
184T	M3220T	1,110	L1	15.00	64	75.5	230/460	2.9	B	1		

(a) See notes on inside back flap.

Cast Iron Frame

Three Phase, Open Drip Proof, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)	
2	3600	56	M3155	489	K	11.00	32	80	208-230/460	2.9	C		
		143T	EM3155T	633	L1	11.62	40	85.5	208-230/460	2.5	A	1	
		145T	M3155T	498	L1	11.62	38	84	208-230/460	2.6	D		
		184	M3208	803	L1	12.62	40	84	208-230/460	2.8	B		
	1800	145TY	EM3157TA	727	L1	13.00	41	86.5	208-230/460	2.8	A		
		56H	M3157	456	LS	11.75	37	78.5	208-230/460	3.2	C	36	
		56HZ	M3157TA	568	K	12.13	39	81.5	208-230/460	2.9	D	37	
		145T	EM3157T	703	LS	13.00	46	86.5	230/460	2.8	A	1	
		145T	M3157T	456	LS	11.62	37	84	208-230/460	3.2	D		
		184	M3209	704	L1	12.62	41	84	208-230/460	3.2	B		
	1200	184T	EM3215T	767	L1	16.50	85	87.5	208-230/460	3.5	A	1	
		184T	M3215T	617	L1	15.00	67	85.5	230/460	3.6	D	1, 30	
900	213T	M3303T	1,370	L1	16.32	88	85.5	208-230/460	3.5	B			
3	3600	56/56H	M3158	504	K	11.75	40	80	208-230/460	4	C	36	
		145T	EM3158T	641	L1	13.00	52	85.5	230/460	3.7	A	1, 30	
		145T	M3158T	528	L1	12.13	45	84	208-230/460	3.7	D		
		184	M3210	853	L1	12.62	43	84	208-230/460	3.8	B		
	1800	56HZ	M3161TA	630	K	14.38	57	84	208-230/460	4.2	D	37	
		145T	M3161T	545	L1	14.38	53	86.5	208-230/460	4.1	D	1	
		182T	EM3211T	758	LS	15.00	75	89.5	230/460	4	A	1, 30	
		182T	EM3211TA	852	L1	15.00	75	89.5	230/460	4	A	1, 30	
		182T	M3211T	476	LS	14.63	61	86.5	208-230/460	4	D	1	
		182T	M3211T/36	546	L1	15.00	62	86.5	208-230/460	4.3	D	1	
		182T	M3211TA	665	L1	14.63	59	86.5	208-230/460	4	D		
		184	M3211	706	L1	12.62	47	86.5	208-230/460	4.3	B	1	
	1200	213	M3304	860	L1	16.63	67	86.5	208-230/460	4.3	B		
		213T	EM3305T	976	L1	16.32	117	88.5	230/460	4.4	A	1, 30	
	900	213T	M3305T	725	L1	16.32	106	86.5	208-230/460	4.6	D		
		215T	M3306T	1,579	L1	17.45	111	86.5	208-230/460	5.2	B		
	5	3600	182T	EM3212T	700	L1	15.00	76	86.5	208-230/460	5.6	A	1
			182T	M3212T	547	L1	14.00	56	85.5	208-230/460	6.1	D	
213			M3307	958	L1	16.62	67	85.5	208-230/460	6	B		
1800		184T	EM3218T	830	LS	16.50	85	89.5	230/460	6.6	A	1, 30	
		184T	EM3218TA	902	L1	16.50	85	89.5	230/460	6.6	A	1, 30	
		184T	M3218T	526	LS	15.00	70	87.5	208-230/460	7.2	D		
		184T	M3218TA	703	L1	15.00	70	87.5	208-230/460	7	D		
		215	M3308	902	L1	16.62	69	87.5	208-230/460	7	B		
1200		215T	EM3309T	1,279	L1	17.45	126	89.5	230/460	7.3	A	1, 30	
		215T	M3309T	950	L1	16.32	117	87.5	208-230/460	7.6	D		
900		254T	M2504T	2,207	L1	19.75	129	87.5	230/460	9.8	B		
7 1/2		3600	184T	EM3219T	1,110	L1	16.50	89	88.5	230/460	8	A	1
	184T		M3219T	750	L1	15.00	68	87.5	208-230/460	8.7	D		
	215		M3310	1,213	L1	16.62	75	87.5	208-230/460	9	B		
	1800	213T	EM3311T	1,220	LS	16.32	117	91	230/460	9.6	A	1, 30	
		213T	M3311T	746	LS	17.00	95	88.5	208-230/460	10	D		
		254U	M2505	1,841	L1	19.51	106	88.5	208-230/460	10.4	B		
	1200	254T	EM2506T	1,533	L1	23.19	245	90.2	230/460	10.7	A	1, 30	
		254T	M2506T	1,172	L1	19.75	247	88.5	208-230/460	10.6	D	1	
	900	256T	M2508T	2,762	L1	23.19	255	88.5	208-230/460	12.7	B	1, 30	
	10	3600	213T	EM3312T	1,269	L1	17.45	130	89.5	230/460	11.5	A	1, 30
213T			M3312T	942	L1	16.32	106	88.5	208-230/460	11.6	D		
1800		215T	EM3313T	1,477	LS	17.45	128	91.7	230/460	12.5	A	1, 30	
		215T	M3313T	913	LS	16.32	110	89.5	208-230/460	13.4	D		
		256U	M2510	2,223	L1	21.44	177	89.5	230/460	13.6	B	1, 30	
1200		256T	EM2511T	1,995	L1	23.19	249	91.7	230/460	14.3	A	1, 30	
	256T	M2511T	1,516	L1	23.19	228	90.2	230/460	14.7	D	1, 30		

(a) See notes on inside back flap.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Open Drip Proof, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)	
15	3600	215T	EM3314T	1,803	L1	17.45	147	90.2	230/460	17	A	1, 30	
		215T	M3314T	1,376	L1	16.32	125	89.5	208-230/460	17.5	D		
	1800	254T	EM2513T	2,091	LS	21.69	217	93	230/460	17.7	A	1, 30	
		254T	EM2513T-CI	1,986	L1	20.63	255	93	230/460	17.8	A	30	
		254T	M2513T	1,380	LS	19.75	187	91	208-230/460	19	D	1	
		284U	M2523	2,907	L1	23.69	272	91	230/460	21	B	1, 30	
		284T	EM2524T	2,690	L1	23.81	375	91.7	230/460	20	A	1, 30	
	20	3600	254T	EM2514T	2,118	L1	21.69	206	91	230/460	22.5	A	1, 30
			254T	M2514T	1,759	L1	21.69	167	90.2	230/460	24	D	1, 30
		1800	256T	EM2515T	2,290	L1	21.69	237	93	230/460	23.5	A	1, 30
256T			EM2515T-12	2,334	L1	21.69	237	93	230/460	23.5	A	1, 25, 30	
256T			EM2515T-CI	2,496	L1	22.38	283	93	230/460	24	A	30	
256T			M2515T	1,774	L1	22.25	187	91.7	230/460	24	D	1, 30	
256T			M2515T-12	1,818	L1	21.69	272	91	230/460	25	D	1, 25, 30	
25		3600	256T	EM2516T	2,543	L1	21.69	242	91.7	230/460	28	A	1, 30
			256T	M2516T	2,128	L1	21.69	202	91	230/460	29	D	1, 30
		1800	284T	EM2531T	2,791	L1	23.81	330	93.6	230/460	30	A	1, 30
	284T		EM2531T-12	2,845	L1	23.81	330	93.6	230/460	30	A	1, 25, 30	
	284T		EM2531T-CI	3,043	L1	23.44	420	93.6	230/460	30	A	30	
	284T		M2531T	2,150	L1	23.44	245	91.7	230/460	31	D	1, 30	
	284T		M2531T-12	2,203	L1	23.44	245	91.7	230/460	31	D	25	
	30	3600	326U	M2531	4,568	L1	26.56	387	91.7	230/460	31	B	1, 30
			324T	EM2532T	3,954	L1	27.69	478	93	208-230/460	32	A	1
		1800	324T	M2532T	3,416	L1	26.19	374	91.7	208-230/460	33	D	
284TS			EM2534T	3,001	L1	22.44	323	91.7	208-230/460	34	A	1	
284TS			M2534T	2,252	L1	22.06	261	91	208-230/460	35	D		
286T			EM2535T	3,052	L1	25.06	372	94.1	230/460	35	A	1, 30	
286T			EM2535T-12	3,114	L1	25.06	372	94.1	230/460	35	A	1, 25, 30	
286T			EM2535T-CI	3,327	L1	24.94	425	94.1	230/460	35	A	30	
286T			M2535T	2,514	L1	24.94	287	92.4	230/460	36	D	1, 30	
286T			M2535T-12	2,576	L1	24.94	283	92.4	230/460	36	D	1, 25, 30	
40	3600	326U	M2535	5,013	L1	26.56	412	92.4	230/460	37	B		
		326T	EM2536T	4,125	L1	28.69	474	93.6	230/460	38	A	1, 30	
	1800	326T	M2536T	3,599	L1	27.19	367	92.4	208-230/460	39	D		
		286TS	EM2538T	3,866	L1	23.69	378	92.4	208-230/460	45	A	1	
		286TS	EM2538T-CI	4,215	L1	23.57	437	92.4	208-230/460	45	A		
		286TS	M2538T	3,170	L1	23.56	320	91.7	208-230/460	46	D		
		324T	EM2539T	3,982	L1	26.69	441	94.1	230/460	46	A	1, 30	
		324T	EM2539T-12	4,061	L1	26.69	441	94.1	230/460	46	A	1, 25, 30	
		324T	EM2539T-CI	4,341	L1	26.13	579	94.1	230/460	46	A	30	
		324T	M2539T	3,205	L1	26.19	354	93	208-230/460	49	D		
1200	324T	M2539T-12	3,284	L1	26.19	392	93	230/460	49	D	25		
	364T	EM2540T	5,579	L1	29.81	565	94.1	230/460	50	A	1, 30		
	364T	EM2540T-CI	5,876	L1	29.69	827	94.1	230/460	50	A	1, 30		
	364T	M2540T	5,282	L1	28.56	567	93	230/460	49	D	1, 30		

(a) See notes on inside back flap.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Open Drip Proof, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)		
50	3600	324TS	EM2542T	4,211	L1	25.69	447	93	208-230/460	54	A	1		
		324TS	EM2542T-CI	4,775	L1	24.62	585	93	208-230/460	56	A			
		324TS	M2542T	3,285	L1	24.69	386	92.4	208-230/460	58	D			
	1800	326T	EM2543T	4,394	L1	27.69	472	94.5	230/460	57	A	1, 30		
		326T	EM2543T-12	4,487	L1	27.69	536	94.5	230/460	57	A	1, 25, 30		
		326T	EM2543T-CI	4,790	L1	27.63	578	94.5	230/460	57	A			
		326TS	EM2543TS-12	4,487	L1	26.75	536	94.5	230/460	57	A	1, 25, 30		
		326T	M2543T	3,762	L1	27.19	413	93	208-230/460	60	D			
		326T	M2543T-12	3,855	L1	27.19	390	93	230/460	62	D	1, 25, 30		
		326TS	M2543TS-12	3,855	L1	25.69	382	93	230/460	60	D	1, 25, 30		
	1200	365T	EM2544T	6,737	L1	29.69	807	94.1	230/460	62	A	1, 30		
		365T	EM2544T-CI	7,114	L1	29.69	857	94.1	230/460	62	A			
365T		M2544T	6,359	L1	29.94	610	93	230/460	62	D	1, 30			
60	3600	326TS	EM2546T	5,328	L1	25.19	463	93.6	230/460	65	A	1		
		326TS	M2546T	4,588	L1	24.69	389	93	230/460	68	D	1, 30		
	1800	364T	EM2547T	5,532	L1	30.69	698	95	230/460	68	A	1, 30		
		364T	EM2547T-12	5,648	L1	30.69	698	95	230/460	68	A	1, 25, 30		
		364T	EM2547T-CI	6,029	L1	30.69	704	95	230/460	68	A			
		364TS	EM2547TS-12	5,648	L1	30.69	698	95	230/460	68	A	1, 25, 30		
		364T	M2547T	4,640	L1	27.94	487	93.6	230/460	72	D	1, 30		
		364T	M2547T-12	4,756	L1	27.94	523	93.6	230/460	72	D	1, 25, 30		
	1200	404T	EM2548T	8,300	L1	33.22	850	95	230/460	0	A	1		
		404T	EM2548T-4CI	9,031	L1	34.00	1127	95	460	72	A			
		404T	M2548T	7,568	L1	33.22	830	93.6	230/460	75	D	1, 30		
		404T	M2548T-4	8,300	L1	33.22	850	95	230/460	0	A	1		
75	3600	364TS	EM2549T	6,989	L1	25.81	507	93.6	208-230/460	82	A	1		
		364TS	M2549T	5,475	L1	25.81	479	93	230/460	84	D	1, 30		
	1800	365T	EM2551T	6,790	L1	33.72	808	95	230/460	86	A	1, 30		
		365T	EM2551T-12	6,931	L1	33.72	808	95	230/460	86	A	1, 25		
		365T	EM2551T-CI	7,400	L1	29.69	727	95	230/460	86	A			
		365TS	EM2551TS-12	6,931	L1	32.78	808	95	230/460	86	A	1, 25		
		365T	M2551T	5,695	L1	29.94	593	94.1	230/460	87	D	1, 30		
		365TS	M2551T-12	5,836	L1	29.94	593	94.1	230/460	87	D	1, 25, 30		
	1200	405T	EM2552T-4	10,055	L1	34.00	1092	94.5	460	88	A	1, 25		
		405T	M2552T	8,934	L1	33.22	610	93.6	230/460	94	D	1, 30		
		100	3600	365TS	EM2550T	7,471	L1	26.81	810	93.6	208-230/460	109	A	1
				365TS	M2550T	6,190	L1	26.81	561	93	230/460	113	D	1, 30
1800	404T		EM2555T-12	8,058	L1	36.97	898	95.4	230/460	115	A	1, 25		
	404T		EM2555T-4	7,900	L1	36.97	898	95.4	460	115	A	1, 25		
	404T		EM2555T-CI	8,610	L1	34.00	1039	95.4	230/460	115	A			
	404T		M2555T	6,343	L1	33.22	797	94.1	230/460	119	D	1, 30		
	404T		M2555T-12	6,501	L1	35.22	820	94.1	230/460	119	D	1, 25, 30		
	404TS		EM2555TS-12	8,058	L1	34.16	898	95.4	230/460	115	A	1, 25		
1200	444T		EM2583T-4	11,067	L1	39.62	1349	95	460	123	A	1, 25		
	444T		M2583T	9,658	L1	39.62	1312	94.1	230/460	119	D			
	125		3600	404TS	EM2554T-4	9,376	L1	33.60	1074	94.1	460	138	A	1, 25
				404TS	EM2554T-4CI	11,187	L1	31.00	1021	94.1	460	138	A	
404TS		M2554T-4		7,209	L1	31.85	575	93.6	460	140	D	25		
1800		405T	EM2559T-4	9,691	L1	34.47	1238	95.4	460	143	A	1, 25		
		405T	EM2559T-4CI	10,562	L1	34.00	1129	95.4	460	143	A			
		405TS	EM2559TS-4	9,691	L1	31.47	1238	95.4	460	143	A	1		
		405T	M2559T-4	7,293	L1	34.47	937	94.5	460	146	D	25		
		405TS	M2559TS-4	7,293	L1	31.10	725	94.5	460	146	D	25		
1200		445T	EM2557T-4	11,952	L1	39.62	1535	95	460	146	A	1, 25		
		445T	M2557T-4	10,336	L1	39.62	1321	94.1	460	151	D	25		

(a) See notes on inside back flap.

Custom TEFC motors available through 2,250 Hp; Open and WPIL custom motors through 15,000 Hp. Contact your Baldor•Reliance Sales Representative.

■ Cast Iron Frame

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Three Phase, Open Drip Proof, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
150	3600	405TS	EM2556T-4	11,566	L1	34.60	831	94.1	460	164	A	1, 25
		405TS	M2556T-4	9,730	L1	31.85	612	93.6	460	164	D	25
	1800	444T	EM2558T-4	10,765	L1	39.62	1405	95.8	460	170	A	1, 25
		444TS	EM2558TS-4	10,765	L1	35.81	1405	95.8	460	170	A	1
		444T	M2558T-4	9,439	L1	39.62	1392	95	460	173	D	25
		444TS	M2558TS-4	9,439	L1	34.88	1386	95	460	173	D	25
1200	445T	EM2560T-4	14,076	L1	39.62	1620	95.4	460	176	A	1, 25	
	445T	M2560T-4	11,171	L1	39.62	1421	94.5	460	178	D	25	
200	3600	444TS	EM2562T-4	13,107	L1	35.88	1326	95	460	217	A	1, 25
		444TS	M2562T-4	10,731	L1	35.88	1321	94.5	460	233	D	25
	1800	445T	EM2563T-4	13,452	L1	39.62	1496	95.8	460	226	A	1, 25
		445T	M2563T-4	11,012	L1	39.62	1495	95	460	228	D	25
	1200	445T	M2564T-4	14,220	L1	39.62	1522	94.5	460	239	D	25
		447T	EM2564T-4	18,503	L1	48.12	1909	95.4	460	234	A	1, 25
250	3600	445TS	M2565T-4	13,369	L1	35.88	1291	94.5	460	272	B	25
		447T	EM2566T-4	15,085	L1	39.62	1592	95.8	460	280	B	1, 25
	445TS	M2566T-4	13,310	L1	39.62	1511	95.4	460	291	B	25	
300	3600	445TS	M2568T-4	20,897	L1	35.88	1378	94.5	460	329	B	25
		445T	EM2569T-4	19,771	L1	39.62	1702	95.8	460	335	B	1, 25
	445T	M2569T-4	17,442	L1	35.88	1528	95.4	460	346	B	25	
350	3600	445TS	M2571T-4	23,915	L1	35.88	1395	95	460	381	B	25
		449TS	M25352T-4	23,915	L1	44.38	1599	95	460	381	B	1, 25, 63
	1800	449T	M2572T-4	23,628	L1	48.18	2039	95.8	460	388	B	1, 25, 63
400	3600	449TS	M25402T-4	28,058	L1	44.38	2300	95.4	460	440	B	1, 25, 63
	1800	449T	M25404T-4	25,644	L1	48.12	2059	95.4	460	448	B	1, 25, 63
450	3600	449TS	M25452T-4	30,896	L1	44.42	1819	95.8	460	472	B	1, 63
	1800	449T	M25454T-4	29,002	L1	48.18	2229	95.8	460	550	B	2, 20, 25, 63

(a) See notes on inside back flap.

Custom TEFC motors available through 2,250 Hp; Open and WPIL custom motors through 15,000 Hp. Contact your Baldor•Reliance Sales Representative.

■ Cast Iron Frame

General Information
Premium Efficient Super-E® Motors
Single Phase Motors
General Purpose Industrial Motors
Severe Duty Motors
Washdown Duty Motors
Explosion Proof Motors
Pump Motors
Light Industrial/Commercial Motors
HVAC Motors