

**Three Phase, ODP**

**1/4 thru 5 Hp**

**NEMA 56 thru 184T**

**Applications:** Ventilators, direct-drive or belted fan and ventilation applications.



**Features:** Heavy-gauge steel base, ball bearings, suitable for mounting in any position. Dynamically balanced rotors for reduced vibration and quiet operation.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status <sup>(a)</sup>	Notes <sup>(a)</sup>	
<b>Foot Mounted</b>													
1/2	1800	56	HM3108	305	K	9.51	22	74	230/460	1	C	1, 30	
		56	HM3108A	391	K	10.34	23	74	230/460	1	C	30	
3/4	1800	56	HM3112	337	K	10.97	26	75.5	208-230/460	1.5	C		
		56	HM3112A	431	K	10.97	26	74	230/460	1.5	C	30	
1	1800	56HZ	HM3116	380	K	12.13	32	78.5	230/460	1.7	D	30	
1 1/2	1800	56HZ	HM3154	437	K	12.13	36	81.5	208-230/460	2.2	D		
		56HZ	HM3154A	524	K	12.13	33	81.5	208-230/460	2.2	D		
2	1800	56HZ	HM3157	459	K	12.13	39	81.5	208-230/460	2.9	D		
		56HZ	HM3157A	546	K	12.13	40	81.5	208-230/460	2.9	D		
3	1800	56HZ	HM3161A	595	K	13.00	47	82.5	208-230/460	4.1	D		
		184T	EHM3218TA	948	L1	16.50	82	89.5	208-230/460	6.6	A		
5	1800	184T	HM3218TA	672	L1	15.00	72	87.5	208-230/460	7	D		
		184T	HM3218TA	672	L1	15.00	72	87.5	208-230/460	7	D		
<b>Resilient Base</b>													
1/4	1800	48	RHM3003	267	K	10.34	19	64	230/460	0.7	C	30	
1/3	1800	48	RHM3007	271	K	10.34	17	68	230/460	0.8	C	30	
		56	RHM3104	306	K	10.97	21	68	230/460	0.8	C	30	
1/2	1800	48	RHM3010	339	K	10.34	22	72	230/460	1	C	30	
		56	RHM3108	351	K	10.97	24	74	230/460	1	C	30	
		56H	RHM3108A	406	K	11.59	24	74	230/460	1	C	30	
3/4	3600	56H	RHM3111A	409	K	11.59	23	74	230/460	1.3	C	30	
		1800	56	RHM3112	387	K	12.47	31	77	230/460	1.2	C	30
			56H	RHM3112A	437	K	11.59	26	74	230/460	1.5	C	30
1	3600	56	RHM3115	375	K	10.97	24	75.5	230/460	1.8	C	30	
		56H	RHM3115A	433	K	11.59	24	75.5	230/460	1.6	C	30	
	1800	56	RHM3116	407	K	12.47	32	78.5	230/460	1.7	C	30	
		56H	RHM3116A	461	K	12.47	33	78.5	230/460	1.7	C	30	
1 1/2	3600	56H	RHM3120A	489	K	12.47	32	81.5	230/460	2	C	30	
		1800	56H	RHM3154	469	K	11.42	37	81.5	208-230/460	2.2	C	
			56H	RHM3154A	474	K	11.42	38	81.5	208-230/460	2.2	C	
2	3600	56H	RHM3155A	567	K	12.47	33	80	230/460	2.7	C	30	
		1800	56H	RHM3157	510	K	12.42	38	81.5	208-230/460	2.9	C	
			56H	RHM3157A	546	K	12.42	38	81.5	208-230/460	2.9	C	
3	3600	56H	RHM3158	628	K	12.42	42	82.5	208-230/460	3.8	C		
		1800	145T	RHM3161TA	602	L1	15.04	60	86.5	208-230/460	4	D	1
5	3600	56HZ	RHM3162TA	844	K	13.64	53	80	208-230/460	6.5	D	1	
		145TY	ERHM3162TA	1,003	L1	15.02	55	86.5	208-230/460	5.6	A		

<sup>(a)</sup> See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors