

# REGAL-BELOIT SpinMaster™ AC Adjustable Speed Drives

## Volts/Hertz Constant Torque, Micro Inverter



**REGAL-BELOIT**  
SpinMaster®

**Applications:** Constant torque or constant horsepower applications. Typical applications include conveyors, packaging machinery, machine tool, printing equipment, and specialty equipment.

- Features:**
- Current limit to 180% with frequency foldback
  - Adjustable carrier frequency
  - Independent accel and decel adjustment
  - Adjustable DC injection braking
  - Programmable inputs
  - Fixed boost for high starting torque
  - UL Listed and UL Certified for Canada under File No. E197830
  - IP20 enclosure
  - Unlimited lead length with microMAX™, Black Max® or Blue Max®, AC motor
  - 2 year warranty

### Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS 230 VAC	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
<b>.33 / .25</b>	120	6.8	1.7	T201	★	\$345	D3	1.5	5.75/146	3.66/93	3.26/83	
<b>.5 / .37</b>	120	9.2	2.4	T202	★	\$375	D3	1.5	5.75/146	3.66/93	3.26/83	
<b>1 / .75</b>	120	16.6	4.2	T204	★	\$498	D3	2.7	5.75/146	4.52/115	4.88/124	
<b>1.5 / 1.1</b>	120	24.0	6.0	T205	★	\$565	D3	3.0	5.75/146	4.52/115	4.88/124	

### Single Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
<b>.33 / .25</b>	208/240	3.9/3.4	1.9/1.7	T211		\$320	D3	2.0	5.75/146	3.66/93	3.26/83	
<b>.5 / .37</b>	208/240	5.8/5.0	2.8/2.4	T212	★	\$337	D3	2.0	5.75/146	3.66/93	3.26/83	
<b>.75 / .55</b>	208/240	6.9/6.0	3.7/3.2	T213		\$356	D3	2.6	5.75/146	3.66/93	3.63/92	
<b>1 / .75</b>	208/240	10.6/9.2	4.8/4.2	T214	★	\$375	D3	3.6	5.75/146	3.66/93	3.63/92	
<b>1.5 / 1.1</b>	208/240	13.9/12.0	6.9/6.0	T215	★	\$452	D3	4.0	5.75/146	4.52/115	4.88/124	
<b>2 / 1.5</b>	208/240	18.4/16.0	8.1/7.0	T216	★	\$530	D3	4.1	5.75/146	4.52/115	4.88/124	
<b>3 / 2.2</b>	208/240	24.0/21.0	11.0/9.6	T217	★	\$624	D3	4.9	5.75/146	4.52/115	5.53/140	

### Three Phase Input / Three Phase Output

HP / kW	INPUT VOLTAGE	INPUT AMPS	OUTPUT AMPS	CAT. NO.	STOCK MODEL	LIST PRICE	MULT. SYMB.	APPROX. WGT. LBS.	HEIGHT	WIDTH	DEPTH	FOOT NOTES
									IN / MM	IN / MM	IN / MM	
<b>.5 / .37</b>	208/240	3.1/2.7	2.8/2.4	T222	★	\$320	D3	1.4	5.75/146	3.66/93	3.26/83	
<b>1 / .75</b>	208/240	5.8/5.1	4.8/4.2	T224	★	\$355	D3	1.7	5.75/146	3.66/93	3.63/92	
<b>1.5 / 1.1</b>	208/240	8.0/6.9	6.9/6.0	T225	★	\$422	D3	2.4	5.75/146	3.66/93	5.56/141	
<b>2 / 1.5</b>	208/240	9.1/7.9	8.1/7.0	T226	★	\$481	D3	2.5	5.75/146	3.66/93	5.56/141	
<b>3 / 2.2</b>	208/240	12.4/10.8	11.0/9.6	T227	★	\$533	D3	3	5.75/146	4.52/115	5.53/140	
<b>5 / 3.7</b>	208/240	19.6/17.1	17.5/15.2	T228	★	\$680	D3	4.6	5.75/146	4.52/115	6.74/171	FN
<b>7.5 / 5.5</b>	208/240	28.0/25.0	25.0/22.0	T229		\$939	D3	7.3	7.75/197	5.76/147	7.18/182	FN
<b>10 / 7.5</b>	208/240	34.0/32.0	30.0/28.0	T220		\$1,167	D3	7.5	7.75/197	5.76/147	7.18/182	FN
<b>15 / 11</b>	208/240	54.0/48.0	48.0/42.0	T221		\$1,720	D3	13.0	9.75/248	7.68/195	8.00/203	FN
<b>.5 / .37</b>	480	1.4	1.1	T232	★	\$427	D3	2.0	5.75/146	3.66/93	3.94/100	
<b>1 / .75</b>	480	2.5	2.1	T234	★	\$457	D3	2.4	5.75/146	3.66/93	4.74/120	
<b>1.5 / 1.1</b>	480	3.6	3.0	T235	★	\$496	D3	2.9	5.75/146	3.66/93	5.74/146	
<b>2 / 1.5</b>	480	4.0	3.4	T236	★	\$529	D3	3.1	5.75/146	3.66/93	5.74/146	
<b>3 / 2.2</b>	480	5.4	4.8	T237	★	\$581	D3	3.2	5.75/146	4.52/115	5.74/146	
<b>5 / 3.7</b>	480	8.8	7.8	T238	★	\$695	D3	4.6	5.75/146	4.52/115	6.74/171	FN
<b>7.5 / 5.5</b>	480	12.4	11	T239		\$903	D3	7.2	5.75/146	4.52/115	6.74/171	FN
<b>10 / 7.5</b>	480	15.8	14	T230		\$1,167	D3	7.5	7.75/197	5.76/147	7.18/182	FN
<b>15 / 11</b>	480	24.0	21	T231		\$1,272	D3	8.0	7.75/197	5.76/147	7.18/182	FN