

BALDOR • RELIANCE®

**Stainless Steel,  
Three Phase,  
Totally Enclosed,  
C-Face,  
Foot Mounted**

**1 thru 20 Hp**

**NEMA 143TC thru 256TC**

**Applications:** Food processing, packaging, outdoor and highly corrosive environments.

**Features:** All external surfaces 300 series stainless steel: motor frame, endplates, conduit box, shaft and base. Moisture resistant insulation system. Four condensate drains in each endplate. Endplate rabbets sealed and conduit box gasketed. Labyrinth seals each end. Especially effective in highly corrosive environments where paint or other finishes do not hold up. Super-E® motors have NEMA Premium® efficiency and 3 year warranty.



General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
1	1800	143TC	<a href="#">CESSWDM3546T</a>	1,257	WD	11.09	42	87.5	208-230/460	1.5	C	
		143TC	<a href="#">CESSWDM3546T-5</a>	1,257	WD	11.09	42	87.5	575	1.1	C	
1 1/2	3600	143TC	<a href="#">CESSWDM3550T</a>	1,261	WD	13.23	50	85.5	208-230/460	1.8	C	
	1800	145TC	<a href="#">CESSWDM3554T</a>	1,281	WD	13.42	45	87.5	208-230/460	2.1	A	
			145TC	<a href="#">CESSWDM3554T-5</a>	1,281	WD	13.42	45	87.5	575	1.6	A
2	3600	145TC	<a href="#">CESSWDM3555T</a>	1,529	WD	14.30	55	86.5	230/460	2.5	A	
	1800	145TC	<a href="#">CESSWDM3558T</a>	1,539	WD	15.67	62	88.5	208-230/460	2.8	A	
			145TC	<a href="#">CESSWDM3558T-5</a>	1,539	WD	15.67	62	88.5	575	2.2	A
3	3600	145TC	<a href="#">CESSWDM3559T</a>	1,842	WD	15.67	44	86.5	208-230/460	3.7	A	
		182TC	<a href="#">CESSWDM3610T</a>	1,967	WD	16.82	82	88.5	208-230/460	3.7	A	
	1800	182TC	<a href="#">CESSWDM3611T</a>	1,799	WD	16.82	94	89.5	230/460	4	A	1
5	3600	184TC	<a href="#">CESSWDM3613T</a>	2,093	WD	18.32	107	90.2	230/460	5.7	A	1
	1800	184TC	<a href="#">CESSWDM3615T</a>	2,025	WD	18.32	115	90.2	230/460	6.4	A	1, 30
7 1/2	3600	213TC	<a href="#">CESSWDM3709T</a>	2,456	WD	19.03	164	91	230/460	8.3	A	1
	1800	213TC	<a href="#">CESSWDM3710T</a>	2,533	WD	20.16	157	91.7	230/460	9.5	A	1
10	3600	215TC	<a href="#">CESSWDM3711T</a>	2,741	WD	20.16	185	91.7	208-230/460	10.6	A	1
	1800	215TC	<a href="#">CESSWDM3714T</a>	2,794	WD	21.66	190	92.4	230/460	12.5	A	1
15	3600	254TC	<a href="#">CESSWDM23994T</a>	5,595	WD	24.67	240	91	208-230/460	16.5	A	1
	1800	254TC	<a href="#">CESSWDM23933T</a>	5,506	WD	24.67	246	92.4	230/460	17.5	A	1, 30
20	3600	256TC	<a href="#">CESSWDM41906T</a>	6,422	WD	24.67	292	91	230/460	21.5	A	1
	1800	256TC	<a href="#">CESSWDM23934T</a>	6,386	WD	24.67	300	93	230/460	23.4	A	1, 30

(a) See notes on inside back flap.