

Fan and Blower - Direct Drive, PSC

Open Air Over, Resilient Ring


Applications: Single speed PSC motors designed to replace PSC and Shaded pole motors, used in direct drive furnace, air conditioners, and others blowers.

- Features:**
- Open frame and brackets
 - Heavy gauge steel constructions
 - Shaft with flat
 - **70°C ambient**
 - 37" Leads
 - Thermal overload protection
 - 1/4" terminals on the capacitor leads
 - 2 1/4" resilient rings, includes 2 1/2" expanders
 - **Capacitor not included, see Accessories section**

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
1/6	1625	115	48Y	X477	48A17O128	★	\$128	F1	2.6	4	1/2 x 4	
	1625	230	48Y	X475	48A17O123	★	\$128	F1	1.3	4	1/2 x 4	
	1075	115	48Y	X473	48A11O1046	★	\$124	F1	2.9	4	1/2 x 4	
	1075	230	48Y	X471	48A11O1044	★	\$124	F1	1.3	4	1/2 x 4	
1/4	1625	230	48Y	X476	48A17O124	★	\$137	F1	1.8	4 1/4	1/2 x 4	
	1075	115	48Y	X472	48A11O1045	★	\$129	F1	4.0	4 1/4	1/2 x 4	
	1075	230	48Y	X474	48A11O1047	★	\$129	F1	2.0	4 1/4	1/2 x 4	

Fan and Blower - Direct Drive, PSC

Open Air Over, Torsion Flex Mount



Applications: Residential and commercial furnaces, air conditioners, exhaust fans, and other air handling equipment installed in clean and dry environments.

- Features:**
- Open frames and brackets
 - Three lug mount fits 9" or 10" bolt circle. Mounting holes on lugs are .435" dia., with grommets and sleeves for .26" dia. option.
 - **Multi-speed capability**
 - Weather resistant reversing plug
 - 30" long leads
 - Automatic reset thermal protector
 - Ball Bearings
 - UL Recognized and CSA Certified
 - **Capacitor not included, see Accessories section**

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
1/4	1075/4	115	48Y	X034	48A11O1773	★	\$149	F1	3.3	4 1/2	1/2 x 6	
1/3	1075/4	115	48Y	X035	48A11O1774	★	\$160	F1	4.5	4 1/2	1/2 x 6	
1/2	1075/4	115	48Y	X036	48A11O1772	★	\$177	F1	6.0	5	1/2 x 6	

Fan & Blower - Direct Drive, PSC

Open Air Over, Extended Thru-Bolt, 460 Volt



Applications: Residential and commercial furnaces, air conditioners, exhaust fans, and other air handling equipment installed in clean and dry environments.

- Features:**
- Enclosed frame and open end brackets
 - **Multi-speed capability**
 - Grommeted lead exit
 - Weather resistant reversing plug
 - Automatic reset thermal protector
 - 7/8" extended thru-bolts on shaft end
 - Ball Bearings
 - UL Recognized and CSA Certified
 - **Capacitor not included, see Accessories section**

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	FRAME LENGTH	SHAFT DIM.	FOOT NOTES
1/3	1075/2	460	48Y	X037	48A11O1876	★	\$278	F1	1.0	4 3/4	1/2 X 6	51
1/2	1075/2	460	48Y	X038	48A11O1874	★	\$284	F1	1.6	5 1/4	1/2 X 6	51
3/4	1075/2	460	48Y	X039	48A11O1875	★	\$289	F1	2.1	5 1/2	1/2 X 6	51