

**Washdown Duty,
Three Phase,
Totally Enclosed**

1 thru 20 Hp

NEMA 56C thru 256TC

Applications: Food processing and other applications where motors receive washdown on a regular basis.



Features: 300 series stainless steel hardware, moisture sealant on bolt heads, between frame and endplates. Neoprene gaskets. Double sealed ball bearings. Lip and V-Ring seal on drive end; slinger on ODE of TEFC motors. Stainless steel shaft extension. Electrostatically applied epoxy finish. Class F insulation. Super-E® motors have NEMA Premium® efficiency and 3 year warranty.

Hp	RPM	NEMA Frame	Encl.	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status ^(a)	Notes ^(a)
Foot Mounted													
1	1800	143T	TENV	EWDM3546T	817	WD	12.12	42	85.5	208-230/460	1.4	C	1, 60
1 1/2	1800	145T	TENV	EWDM3554T	898	WD	13.00	47	86.5	230/460	2	C	1, 30, 60
2	1800	145T	TEFC	EWDM3558T	1,054	WD	14.18	49	86.5	208-230/460	2.7	A	1
3	1800	182T	TEFC	EWDM3611T	1,316	WD	16.54	72	89.5	208-230/460	4.1	A	1
5	1800	184T	TEFC	EWDM3615T	1,498	WD	18.03	93	89.5	230/460	6.5	A	1, 30
7 1/2	1800	213T	TEFC	EWDM3710T	1,875	WD	19.04	134	91.7	230/460	9.4	A	1, 30
10	1800	215T	TEFC	EWDM3714T	2,043	WD	20.54	158	91.7	230/460	12	A	1, 30
C-Face, Foot Mounted													
1	3600	56C	TEFC	CEWDM3545	916	WD	12.24	34	84	230/460	1.4	C	1, 60
	1800	56C	TENV	CEWDM3546	920	WD	12.94	44	85.5	230/460	1.4	C	1
		143TC	TENV	CEWDM3546T	939	WD	12.13	40	85.5	208-230/460	1.4	C	1, 60
		56C	TEFC	CEWDM3556	1,033	WD	13.24	41	82.5	208-230/460	1.8	C	1, 60
1 1/2	3600	56C	TENV	CEWDM3550	941	WD	12.07	44	85.5	208-230/460	2	C	1, 60
	1800	145TC	TENV	CEWDM3554T	983	WD	13.00	48	86.5	230/460	2	C	1, 30, 60
2	3600	56HCY	TEFC	CEWDM3555	1,018	WD	14.12	51	85.5	208-230/460	2.5	C	1
		145TC	TEFC	CEWDM3555T	1,038	WD	14.17	51	85.5	208-230/460	2.5	A	1
	1800	145TC	TEFC	CEWDM3558T	1,083	WD	14.16	47	86.5	208-230/460	2.7	A	1
		1200	184TC	TEFC	CEWDM3614T	1,270	WD	18.05	79	88.5	208-230/460	3.3	A
3	3600	145TC	TEFC	CEWDM3559T	1,279	WD	15.55	59	86.5	230/460	3.6	A	1, 30
		182TC	TEFC	CEWDM3610T	1,206	WD	15.18	67	86.5	230/460	3.7	A	1
	1800	182TC	TEFC	CEWDM3611T	1,423	WD	16.54	75	89.5	208-230/460	4.1	A	1
		1200	213TC	TEFC	CEWDM3704T	1,674	WD	19.76	130	89.5	230/460	4.6	A
5	3600	184TC	TEFC	CEWDM3613T	1,693	WD	16.54	84	88.5	208-230/460	5.6	A	1
	1800	184TC	TEFC	CEWDM3615T	1,612	WD	18.04	96	89.5	230/460	6.5	A	1, 30
	1200	215TC	TEFC	CEWDM3708T	1,983	WD	20.51	142	89.5	230/460	7.2	A	1, 30
7 1/2	3600	184TC	TEFC	CEWDM3616T	2,012	WD	18.04	99	89.5	208-230/460	8.4	A	1
		213TC	TEFC	CEWDM3709T	2,385	WD	19.78	139	89.5	208-230/460	8.6	A	1
	1800	213TC	TEFC	CEWDM3710T	2,040	WD	19.78	129	91.7	230/460	9.4	A	1, 30
		1200	254TC	TEFC	CEWDM22976T	3,404	WD	23.57	247	91	230/460	10.7	A
10	3600	215TC	TEFC	CEWDM3711T	2,625	WD	19.78	151	90.2	230/460	11.2	A	1, 30
	1800	215TC	TEFC	CEWDM3714T	2,319	WD	21.27	158	91.7	230/460	12.5	A	1
	1200	256TC	TEFC	CEWDM23932T	3,870	WD	23.57	280	91	230/460	14.4	A	1, 30
15	3600	215TC	TEFC	CEWDM3713T	3,298	WD	21.26	174	91	230/460	16.6	A	1
		254TC	TEFC	CEWDM23994T	4,633	WD	21.94	158	91	230/460	16.6	A	1
	1800	254TC	TEFC	CEWDM23933T	4,560	WD	23.57	226	92.4	230/460	18	A	1
20	3600	256TC	TEFC	CEWDM41906T	5,318	WD	23.57	242	91	230/460	22.5	A	1
	1800	256TC	TEFC	CEWDM23934T	5,289	WD	23.57	280	93	208-230/460	24	A	1

^(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors