

General Purpose, Single Phase

(NEMA Service Factor), Dripproof



Features:

- Ball bearings, mechanically locked on shaft end
- NEMA Service Factors
- Heavy gauge steel constructions
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- UL Recognized and CSA Certified

C-Face Footed (Rigid Base)

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115/208-230	56C	AUTO	K234	56C17D2114				\$203	F1	5.0/2.3-2.5	10.30	
1/3	1800	115/208-230	56C	AUTO	K235	56C17D2115	*			\$236	F1	6.4/3.0-3.2	10.30	
	1800	100-120/200/240	56C	MANUAL	E250	5KCR46JN0083Y	*			\$283	F1	4.0-3.8/2.0-1.9	10.77	ES,1,68
	1800	100-120/200/240	56C	AUTO	E252	5KCR46JN0083X	*			\$236	F1	4.0-3.8/2.0-1.9	10.77	ES,1,68
1/2	1800	100-120/200-240	56C	AUTO	E261	5KCR46MN0090X	*	K236	56C17D2116	\$274	F1	5.8-5.6/2.9-2.8	10.77	ES,1,68
	1800	100-120/200-240	56C	MANUAL	E259	5KCR46MN0090Y	*			\$328	F1	5.8-5.6/2.9-2.8	10.77	ES,1,68
3/4	1800	100-120/200-240	56C	AUTO	E270	5KCR49PN0095X	*	K237	56B17D2015	\$333	F1	9.0-8.8/4.5-4.4	11.37	ES,1,68
	1800	100-120/200-240	56C	MANUAL	E268	5KCR49PN0095Y	*			\$379	F1	9.0-8.8/4.5-4.4	11.37	ES,1,68
1	1800	100-120/200-240	56C	MANUAL	EG277	5KCR48UN0102Y	*			\$439	F1	11.8-11.4/5.9-5.7	12.65	ES,1,68
2	3600	115/208-230	56C	MANUAL	C1269	5KC49SN2537Y	*			\$561	F1	15.6/8.8-7.8	11.34	
3	3600	208-230	56C	MANUAL	C1270	5KC49ZN2539Y	*			\$686	F1	13.0-12.0	12.84	