

**Fan and Blower,
Single and
Three Phase, ODP,
Resilient Base**

1/4 thru 3 Hp

NEMA 48 thru 56H

Applications: Ventilators, summer cooling fans, band saws, drill presses, farm equipment, etc.

Features: Heavy-gauge steel base, ball bearings, suitable for mounting in any position. Dynamically balanced rotors for reduced vibration and quiet operation.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status ^(a)	Notes ^(a)
Single Phase												
1/2	1800	56	RL1304A	382	K	11.59	26	62	115/230	4.2	C	2, 30, 66
		56	RL1323A	348	K	10.97	24	62	115/230	4	C	2, 66
3/4	3600	56	RL1306A	351	K	11.59	26	71	115/230	5.5	C	2, 30, 66
	1800	56H	RL1307A	469	K	12.97	35	68	115/230	5.1	C	30, 66
			56	RL1324A	377	K	12.47	31	71	115/230	5	C
1	3600	56H	RL1309A	404	K	11.42	34	63	115/230	7.3	C	30, 66
	1800	56H	RL1310A	509	K	11.42	33	66	115/230	6.7	C	2, 30, 66
1 1/2	3600	56H	RL1313A	521	K	12.42	39	68	115/230	9	C	30, 66
	1800	56H	RL1319A	616	K	12.42	42	68	115/230	9	C	30, 66
2	3600	56H	RL1317A	647	K	12.42	43	70	115/230	12	C	30, 66
Single Phase, 277 Volt												
1/3	1800	56	RL1301A277	393	K	10.97	23	60	277	2.5	C	66
1/2	1800	56	RL1304A277	409	K	11.59	26	62	277	3.6	C	66
3/4	1800	56H	RL1307A277	563	K	11.42	34	63	277	5.1	C	66
1	1800	56H	RL1310A277	579	K	12.42	42	66	277	5.4	C	66
1 1/2	1800	56H	RL1319A277	630	K	13.30	46	70	277	8.5	C	66
Three Phase												
1/4	1800	48	RM3003	280	K	10.34	19	64	230/460	0.7	C	30
1/3	3600	48	RM3006	268	K	10.34	20	72	230/460	0.7	C	30
	1800	48	RM3007	283	K	10.34	21	68	230/460	0.8	C	30
			56	RM3104	322	K	10.97	22	68	230/460	0.8	C
1/2	3600	48	RM3009	283	K	10.34	19	68	230/460	1	C	30
	1800	48	RM3010	356	K	10.34	23	74	230/460	1	C	30
			56	RM3108	366	K	10.97	23	74	230/460	1	C
3/4	3600	56	RM3111	372	K	10.97	22	74	230/460	1.3	C	30
	1800	56	RM3112	407	K	11.59	27	75.5	208-230/460	1.5	C	
1	3600	56	RM3115	393	K	10.97	24	75.5	230/460	1.8	C	30
	1800	56	RM3116	431	K	12.47	33	78.5	230/460	1.7	C	30
1 1/2	3600	56H	RM3120	478	K	12.47	31	80	208-230/460	2.3	C	
	1800	56H	RM3154	496	K	12.97	34	77	208-230/460	2.8	C	
2	3600	56H	RM3155	555	K	12.47	33	80	208-230/460	2.9	C	
	1800	56/56H	RM3157	536	K	12.42	37	78.5	208-230/460	3.2	C	
3	3600	56/56H	RM3158	574	K	12.42	39	80	208-230/460	4	C	

^(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors