


Woodworking/Power Tool, Single Phase

Totally Enclosed, Rigid Base



Applications: Replacement motors for table saws, planers, lathes, and other equipment found in the woodworking and metalworking trades. These totally enclosed, fan cooled motors are well suited for use in dusty and dirty environments or where wood or metal shavings are present.

- Features:**
- Capacitor start design for high starting torque with low amps
 - Double sealed ball bearings
 - Heavy gauge steel frame and base
 - 1.15 Service Factor
 - Manual reset thermal protector
 - Dependable, dust-proof centrifugal starting switch
 - On/off toggle switch and 8 foot cord with 115 volt plug included on 1/2 to 1-1/2 HP models
 - UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/2	1800	115/208-230	56	MANUAL	T010	56C17F5351		\$341	F1	8.8/4.2-4.4	11.82	2
3/4	3600	115/208-230	56	MANUAL	T013	56C34F5340	★	\$309	F1	10.6/5.3-5.3	12.32	2
	1800	115/208-230	56	MANUAL	T014	56C17F5350		\$399	F1	11.0/5.4-5.5	12.32	2
1	3600	115/208-230	56	MANUAL	T015	56C34F5339	★	\$343	F1	12.4/6.7-6.2	12.32	2
	1800	115/208-230	56	MANUAL	T016	56C17F5349	★	\$422	F1	13.4/6.8-6.7	12.82	d,2
1 1/2	3600	115/208-230	56	MANUAL	T017	56B34F5332	★	\$421	F1	14.2/7.7-7.1	12.82	1
	1800	115/208-230	56	MANUAL	T018	56B17F5328		\$513	F1	13.6/7.5-6.8	13.73	1
2	3600	115/230	56H	MANUAL	T019	56B34F5333	★	\$459	F1	17.5/8.7	13.41	1,5
	1800	115/230	56H	MANUAL	T030	56B17F5329	★	\$566	F1	18.8/9.4	14.82	1,5,d
3	3600	208-230	145T	MANUAL	T031	145TBFR5309	★	\$636	S1	13.1/11.8	14.87	1

50 Hertz, Three Phase

Dripproof, Rigid Base



- Features:**
- Ball bearings
 - 1.15 Service Factor
 - Nameplated 190-200-208/380-400-416 (except as noted)
 - 12 Lead delta capability
 - UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	NOM. EFF.	F.L. AMPS	"C" DIM.	FOOT NOTES
2	1500	220/380	145T	KG319	5K49UN8052	★	\$426	E6	81.5	6.4/3.7	14.24	d
	1500	190-208/380-416	145T	H952	145TTDR5647		\$426	E6	82.5	7.2-7.3/3.6-3.65	12.99	F,YD,5,14
3	1500	190-208/380-416	182T	H1953	182TTDW8353		\$474	E6	81.5	10.0-9.8/5.0-4.9	13.22	F,YD,25
5	1500	190-208/380-416	184T	H954	184TTDR9040	★	\$603	E6	82.5	16.2-15.6/8.1-7.8	14.72	d,F,YD,13,25
	1500	190-208/380-416	184T	H1954	184TTDW9040	★	\$603	E6	82.5	16.2-15.6/8.1-7.8	14.72	F,YD,13,25
7 1/2	1500	190-208/380-416	213T	H955	213TTDW7053		\$792	E6	85.5	22.6-19.0/9.5-11.3	17.30	YD
10	1500	190-208/380-416	215T	H956	215TTDW7053	★	\$942	E6	88.5	31.0-29.1/15.5-14.5	17.30	YD
15	1500	190-208/380-416	254T	H957	254TTDX8338		\$1,247	E6	88.5	46.0-44.0/23.0-22.0	22.32	F,YD