

# General Purpose, Single Phase

## (NEMA Service Factor), Dripproof



### Features:

- Ball bearings, mechanically locked on shaft end
- Heavy gauge steel constructions
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- Service Factor, as noted
- UL Recognized and CSA Certified

### C-Face Footless

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115/208-230	56C	NONE	C1296	5KC35JN70	★	\$189	F1	5.2/2.7-2.6	9.61	d,20
	1800	115/208-230	56C	NONE	G212	56C17D2084	★	\$189	F1	5.0/2.3-2.5	10.69	20
	1800	115/208-230	56C	AUTO	C354	5KC35JN70X	★	\$248	F1	5.2/2.7-2.6	9.61	20
1/3	3600	115/208-230	56C	NONE	G216	56C34D2117	★	\$162	F1	4.4/2.2-2.2	10.19	20
	1800	100-120/200-240	56C	NONE	E251	5KCR46JN0084	★	\$365	F1	4.0-3.8/2.0-1.9	10.77	ES,1,20,68
	1800	115/208-230	56C	AUTO	C356	5KC36LN83X	★	\$287	F1	6.0/3.2-3.0	10.35	20,68
	1800	115/208-230	56C	NONE	C355	5KC36LN83	★	\$222	F1	6.0/3.2-3.0	10.35	d,20,68
	1800	115/208-230	56C	NONE	G230	56C17D2085	★	\$222	F1	6.4/3.0-3.2	10.69	20
1/2	3600	115/208-230	56C	NONE	G232	56C34D2108	★	\$179	F1	8.4/3.8-4.2	10.69	19
	1800	100-120/200-240	56C	NONE	E260	5KCR46MN0091	★	\$416	F1	5.8-5.6/2.9-2.8	10.77	ES,1,19,68
	1800	115/208-230	56C	NONE	C358	5KC49GN0009		\$261	F1	8.8/4.2-4.4	10.38	19
	1800	115/208-230	56C	NONE	G234	56C17D2044	★	\$261	F1	8.6/4.1-4.3	11.19	19
	1800	115/230	56C	AUTO	C359	5KC49GN0009X	★	\$326	F1	8.8/4.4	10.38	19
	1200	115/208-230	56C	NONE	G278	56C11D5304	★	\$417	F1	10.6/5.1-5.3	11.94	19
3/4	3600	115/208-230	56C	NONE	G238	56C34D2101	★	\$229	F1	9.6/4.4-4.8	10.94	19
	1800	100-120/200-240	56C	NONE	E269	5KCR49PN0096	★	\$451	F1	9.0-8.8/4.5-4.4	11.38	ES,1,19,68
	1800	115/230	56C	AUTO	CG362	5KC46LN0159X	★	\$392	F1	13.2/6.6	10.78	19
	1800	115/208-230	56C	NONE	CG361	5KC46LN0159	★	\$320	F1	13.2/6.2-6.6	10.78	d,17
	1800	115/208-230	56C	NONE	G250	56B17D2011	★	\$320	F1	11.0/5.5-5.5	11.72	1,19
1	3600	115/208-230	56C	NONE	G254	56B34D2031	★	\$263	F1	10.6/5.5-5.3	11.68	1,19
	1800	100-120/200-240	56C	NONE	E278	5KCR48UN0103	★	\$519	F1	11.8-11.4/5.9-5.7	12.65	ES,1,18,68
	1800	115/230	56C	AUTO	CG363	5KC49PN0163X	★	\$438	F1	13.6/6.8	11.38	18
	1800	115/208-230	56C	NONE	C1297	5KC49PN0163	★	\$343	F1	13.6/6.7-6.8	11.38	d,18
	1800	115/208-230	56C	NONE	G256	56C17D5310	★	\$343	F1	13.4/6.8-6.7	11.44	18
1 1/2	3600	115/208-230	56C	NONE	G258	56B34D2023		\$341	F1	14.2/7.7-7.1	11.68	1,18
	1800	115/208-230	56C	NONE	G270	56C17D5311	★	\$399	F1	18.0/9.3-9.0	12.44	18
2	3600	115/208-230	56C	NONE	G272	56B34D5319	★	\$418	F1	19.2/10.5-9.6	11.44	1,18
	1800	115/208-230	56C	NONE	G274	56B17D5303	★	\$487	F1	21.0/11.3-10.5	13.44	1,18
3	3600	115/208-230	182TC	NONE	C173	182TCDR8007		\$559	S1	32.0/17.5-16.0	13.96	18
	1800	115/230	184TC	NONE	C1174	184TCDW9627		\$546	S1	33.0/16.5	15.96	13,18

SINGLE PHASE