

**Pressure Washer,
Single Phase,
TEFC and ODP**

1-1/2 thru 5 Hp

NEMA 56 thru 184TC

Applications: Pressure washers, steam cleaners, portable and self contained stationary system for direct drive mount and doubled mount designs.



Features: Ball bearing design. 1 1/2 horsepower ratings are rated at 14 amps or less on 115 volts. Manual thermal overload located in the conduit box. UL and CSA recognized component approval. 200°C copper windings. Capacitor start, capacitor run (two value capacitor).

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
Totally Enclosed Fan Cooled												
1 1/2	3600	56	PL3513M	559	K	13.25	38	75.5	115/230	6.6	C	
	1800	56	PL3514M	742	K	14.12	50	82.5	115/230	6	C	
2	3600	56	PL3515M	676	K	13.25	42	77	115/230	8.8	C	1
	1800	56HZ	L3516TM	919	K	13.31	46	82.5	230	8.1	C	1, 57
3	3600	56	PL3519M	741	K	14.12	50	85.5	230	12.5	C	1, 30
	1800	184T	L3609TM	1,015	L1	16.54	79	78	115/230	14.5	C	2, 20
5	3600	184T	L3608TM	1,169	L1	18.05	86	83	230	19.5	C	2, 20
	1800	184T	L3612TM	1,180	L1	18.05	99	80	230	23	C	2, 20
Totally Enclosed Fan Cooled, C-Face												
1 1/2	3600	56C	PCL3513M	598	K	13.25	38	75.5	115/230	6.6	C	
	1800	56C	PCL3514M	780	K	14.12	50	82.5	115/230	6	C	
2	3600	56C	PCL3515M	709	K	13.24	43	77	115/230	8.8	C	1
	1800	145TC	CL3516TM	927	L1	14.16	52	78	230	8.3	C	1
3	3600	56C	PCL3519M	777	K	14.12	52	85.5	230	12.5	C	1, 30
	1800	184TC	CL3619TM	1,206	L1	16.54	81	81.5	230	13.2	C	2, 20
5	3600	184TC	CL3608TM	1,306	L1	18.05	91	83	230	19.5	C	2, 20
	1800	184TC	CL3612TM	1,264	L1	18.05	101	80	230	23	C	2, 20
Open Drip Proof												
1 1/2	3600	56H	PL1313M	486	K	11.75	34	75.5	115/230	6.6	C	36
	1800	56	PL1319M	645	K	12.06	39	74	115/230	7	C	
2	3600	56	PL1317M	634	K	12.06	41	77	115/230	8.8	C	
	1800	56	PL1322M	676	K	12.94	47	78.5	115/230	9.2	C	
3	3600	56	PL1326M	700	K	12.94	50	85.5	230	12.5	C	30
	1800	184T	L1408TM	844	L1	15.00	78	78	115/230	16	C	
5	3600	56/56H	PL1327M	721	K	13.81	56	74.2	230	23	C	2, 20, 30, 36
	1800	184T	L1410TM	1,027	L1	16.50	84	82.5	230	23	C	1, 30
Open Drip Proof, C-Face												
1 1/2	3600	56C	PCL1313M	527	K	12.06	38	75.5	115/230	6.6	C	
	1800	56C	PCL1319M	676	K	12.06	43	74	115/230	7	C	
2	3600	56C	PCL1317M	676	K	12.06	43	77	115/230	8.8	C	
	1800	56C	PCL1322M	701	K	12.94	48	78.5	115/230	9.2	C	
3	3600	56C	PCL1326M	741	K	12.94	49	85.5	230	12.5	C	30
	1800	184TC	CL1408TM	892	L1	15.00	78	78	115/230	16	C	
5	3600	56HCY	PCL1327M	759	K	14.11	57	74.2	230	23	C	2, 20, 30, 37, 47
	1800	184TC	CL1410TM	1,075	L1	16.50	88	82.5	230	23	C	1, 30

(a) See notes on inside back flap.

Farm Duty Motors

Definite Purpose Motors

Unit Handling Motors

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Starters & Dynamic Brakes