

Three Phase, Open Drip Proof, C-Face, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
50	1800	326TC	CEM2543T	5,103	L1	28.94	475	94.5	230/460	57	A	1, 30
		326TC	CM2543T	4,470	L1	27.19	382	93	230/460	62	D	30
60	1800	364TC	CEM2547T	6,347	L1	30.69	468	95	230/460	68	A	1, 30
		364TC	CM2547T	5,455	L1	27.94	474	93.6	230/460	72	D	30
75	1800	365TC	CEM2551T	7,605	L1	35.22	820	95	230/460	86	A	1
		365TC	CM2551T	6,510	L1	29.94	608	94.1	230/460	87	D	30
100	1800	404TC	CEM2555T	8,802	L1	36.97	920	95.4	230/460	115	A	1
		404TC	CM2555T	7,245	L1	35.22	538	94.1	230/460	119	D	30

(a) See notes on inside back flap.

Three Phase, Open Drip Proof, C-Face, Footless

1/4 thru 30 Hp

NEMA 56C thru 284TC

Applications: Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.



Features: Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing and heavy-gauge steel frames.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	EISA Status (a)	Notes (a)
1/4	1800	56C	KM3003	274	K	11.35	19	64	230/460	0.7	C	30
		56C	VM3104	282	LS	11.22	20	68	230/460	0.8	C	30
1/2	1800	56C	VM3107	295	K	11.22	19	68	230/460	1	C	30
		56C	VM3108	320	LS	11.22	22	74	230/460	1	C	30
		56C	VM3109	497	K	12.35	25	72	230/460	1.2	C	30
3/4	3600	56C	VM3111	415	K	11.22	21	74	230/460	1.3	C	30
		56C	VM3112	354	LS	11.84	25	75.5	208-230/460	1.5	C	
		56C	VM3153	534	K	13.35	33	77	208-230/460	1.5	C	
		143TC	VM3153T	534	L1	13.41	33	77	208-230/460	1.5	C	
1	1800	56C	VM3115	393	K	11.22	23	75.5	230/460	1.8	C	30
		56C	VM3116	397	LS	12.35	29	78.5	208-230/460	1.7	C	1
		143TC	VM3116T	431	LS	12.41	30	82.5	208-230/460	1.7	B	1
		145TC	VM3156T	599	L1	13.30	37	80	208-230/460	1.7	B	
1 1/2	3600	56C	VM3120	437	K	12.72	30	80	208-230/460	2.3	C	
		143TC	VM3120T	504	L1	13.10	31	82.5	208-230/460	2.3	B	
	1800	56C	VM3154	456	LS	13.22	34	77	208-230/460	2.8	C	
		145TC	VM3154T	502	LS	13.60	35	84	208-230/460	2.8	B	
	1200	145TC	VM3159T	653	L1	13.30	41	84	230/460	2.5	B	
2	3600	56C	VM3155	508	K	13.22	32	80	208-230/460	2.9	C	
		143TC	VM3155T	556	L1	13.10	33	84	208-230/460	2.9	B	
	1800	56C	VM3157	472	LS	13.24	38	78.5	208-230/460	3.2	C	
		145TC	VM3157T	517	LS	13.30	38	84	208-230/460	3.2	B	
	1200	184TC	VM3215T	680	L1	15.18	58	85.5	230/460	3.4	B	

(a) See notes on inside back flap.

General Information

Premium Efficient Super-E® Motors

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors